



PUSH-TO-CONNECTS

PUSH-TO-CONNECTS

Push-to-Connect Products provided through Pneuline Supply include Acetal, Polypropylene, PVDF, PBT, 316 Stainless, Nickel Plated Brass, and Brass.



PBT PUSH TO CONNECTS

Our PBT push-to-connects come in many sizes and orientations such as Ts, elbows, straights, and Ys.



PUYR - PBT STRAIGHT COMPACT WYE REDUCER PUSH-TO-CONNECT REDUCER

Compact Straight Wye Reducer fitting has three push-to-connect ports in a wye pattern with two smaller ports side by side opposite the third larger port. The body is PBT resin with Nickel-plated Brass threads. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.



PUY - PBT THREE PORT WYE PUSH-TO-CONNECT

Compact straight fitting with three push-to-connect ports in a Wye pattern with two ports side by side opposite the third port. The body is PBT resin with Nickel-Plated Brass threads. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

| SKU | DESCRIPTION |
|----------|--------------------------|
| PUY-12P | 1/2 OD Parallel PBT Wye |
| PUY-14P | 1/4 OD Parallel PBT Wye |
| PUY-18P | 1/8 OD Parallel PBT Wye |
| PUY-316P | 3/16 OD Parallel PBT Wye |
| PUY-38P | 3/8 OD Parallel PBT Wye |
| PUY-516P | 5/16 OD Parallel PBT Wye |
| PUY-532P | 5/32 OD Parallel PBT Wye |



PUTR PUSH-TO-CONNECT REDUCER TEE

Union Tee fitting with 2 push-to-connect ports of equal sizes and 1 push-to-connect port that is a reducer located 90° apart. The body is PBT resin. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

| SKU | DESCRIPTION |
|---------------|-------------------------------------|
| PUTR-12-38P | 1/2 OD by 3/8 OD PBT Reducing Tee |
| PUTR-12-516P | 1/2 OD by 5/16 OD PBT Reducing Tee |
| PUTR-14-18P | 1/4 OD by 1/8 OD PBT Reducing Tee |
| PUTR-14-316P | 1/4 OD by 3/16 OD PBT Reducing Tee |
| PUTR-316-532P | 3/16 OD by 5/32 OD PBT Reducing Tee |
| PUTR-38-14P | 1/4 OD by 3/8 OD PBT Reducing Tee |
| PUTR-38-516P | 3/8 OD by 5/16 OD PBT Reducing Tee |
| PUTR-4532P | 1/4 OD by 5/32 OD PBT Reducing Tee |
| PUTR-516-14P | 5/16 OD by 1/4 OD PBT Reducing Tee |
| PUTR-516-532P | 5/16 OD by 5/32 OD PBT Reducing Tee |

PUT EQUAL PUSH-TO-CONNECT UNION TEE



Union Tee fitting has 3 push-to-connect ports of equal sizes. The body is PBT resin. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

| SKU | DESCRIPTION |
|-----------|----------------------------------|
| PUT-12N | 1/2 OD Push-to-Connect Tee Nylon |
| PUT-14P | 1/4 OD PBT Push-to-Connect Tee |
| PUT-18P | 1/8 OD PBT Push-to-Connect Tee |
| PUT-316P | 3/16 OD PBT Push-to-Connect Tee |
| PUT-38-P | 3/8 OD PBT Push-to-Connect Tee |
| PUT-532-P | 5/32 OD PBT Push-to-Connect Tee |
| PUT-5P | 5/16 OD PBT Push-to-Connect Tee |
| PUT-4MM-P | 4 mm OD PBT Push-to-Connect Tee |
| PUT-6MM-P | 6 mm OD PBT Push-to-Connect Tee |
| PUT-8MM-P | 8 mm OD PBT Push-to-Connect Tee |

PUM SERIES - STRAIGHT LINE PUSH-TO-CONNECT MANIFOLD



Straight line Manifold with equal or reducing push-to-connect ports. It is also available with male NPT threads on the in port.

| SKU | DESCRIPTION |
|---------------|--|
| PUM-14 | 1/4 In/Out and 3 1/4 Ports Manifold |
| PUM-14532 | 1/4 In/Out and 3 5/32 Ports Manifold |
| PUM-18 | 1/8 In/Out and 3 1/8 Ports Manifold |
| PUM-3814 | 3/8 In/Out and 3 1/4 Ports Manifold |
| PUM-38516 | 3/8 In/Out and 3 5/16 Ports Manifold |
| PUM-516 | 5/16 In/Out and 3 5/16 Ports Manifold |
| PUM-51614 | 5/16 In/Out and 3 1/4 Ports Manifold |
| PUM-516316 | 5/16 In/Out and 3 3/16 Ports Manifold |
| PUM-516532 | 5/16 In/Out and 3 5/32 Ports Manifold |
| PUM-532 | 5/32 In/Out and 3 5/32 Ports Manifold |
| PUM-532185 | 5/32 In/Out and 3 1/8 Ports Manifold |
| PUM-2M532 | 1/8 MNPT In 5/32 Out and 3 5/32 Ports Manifold |
| PUM-2M532-316 | 1/8 MNPT In 5/32 Out and 3 3/16 Ports Manifold |

| SKU | DESCRIPTION |
|---------------|--|
| PUM-4M316-516 | 1/4 MNPT In 5/16 Out and 3 5/16 Ports Manifold |
| PUM-4M516-38 | 1/4 MNPT In 5/16 Out and 3 3/8 Ports Manifold |
| PUM-4M532-14 | 1/4 MNPT In 5/32 Out and 3 1/4 Ports Manifold |
| PUM-4M532-316 | 1/4 MNPT in 5/32 Out and 3 3/16 PortsManifold |
| PUM-4M532-516 | 3/8 MNPT In 1/4 Out and 3 5/16 Ports Manifold |
| PUM-6M14-516 | 3/8 MNPT In 1/4 Out and 3 5/16 Ports Manifold |
| PUM-8M516-38 | 1/2 MNPT In 5/16 Out and 3 3/8 Ports Manifold |
| PUMR-14532 | 1/4 In/out with 3- 5/32 Ports Reducer Manifold |

PUE SERIES



Composite Union Elbow made of a PBT body and a Buna-N seal. The working pressure is 150 psi and a temperature range of 32° F to 140° F.

| SKU | DESCRIPTION |
|------------|--------------------------------|
| PUE-12P | 1/2 PBT Elbow Push-to-Connect |
| PUE-14P | 1/4 PBT Elbow Push-to-Connect |
| PUE-18P | 1/8 PBT Elbow Push-to-Connect |
| PUE-316P | 3/16 PBT Elbow Push-to-Connect |
| PUE-38P | 3/8 PBT Elbow Push-to-Connect |
| PUE-5/16-P | 5/16 PBT Elbow Push-to-Connect |
| PUE-532P | 5/32 PBT Elbow Push-to-Connect |
| PUE-4MM-P | 4 mm PBT Elbow Push-to-Connect |
| PUE-6MM-P | 6 mm PBT Elbow Push-to-Connect |



PUCX SERIES

Union Cross push-to-connect fitting with four opposing, equal-sized ports made of Polybutylene. This fitting is also available in metric sizes.

| SKU | DESCRIPTION |
|-------------|-----------------------------------|
| PUCX-12P | 1/2 OD Cross Polybutylene |
| PUCX-14P | 1/4 OD Cross Polybutylene |
| PUCX-18P | 1/8 OD Cross Polybutylene |
| PUCX-316P | 3/16 OD Cross Polybutylene |
| PUCX-38P | 3/8 OD Cross Polybutylene |
| PUCX-516P | 5/16 Cross Polybutylene |
| PUCX-532P | 5/32 Cross Polybutylene |
| PUCX-1238P | 3/8 by 1/2 OD Cross Polybutylene |
| PUCX-38516P | 5/16 by 3/8 OD Cross Polybutylene |



PUC COMPACT STRAIGHT PUSH-TO-CONNECT FITTING

Compact Straight Fitting with two push-to-connect ports in opposite directions. The body is PBT resin. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

| SKU | DESCRIPTION |
|------------|------------------------------------|
| PUC-12P | 1/2 OD PBT Push-to-Connect Union |
| PUC-14P | 1/4 OD PBT Push-to-Connect Union |
| PUC-18P | 1/8 OD PBT Push-to-Connect Union |
| PUC-316P | 3/16 OD PBT Push-to-Connect Union |
| PUC-38-P | 3/8 OD PBT Push-to-Connect Union |
| PUC-516-P | 5/16 OD PBT Push-to-Connect Union |
| PUC-532-P | 5/32 OD PBT Push-to-Connect Union |
| PUC-58P | 5/8 OD PBT Push-to-Connect Union |
| PUC-4MM-P | 4 mm OD PBT Push-to-Connect Union |
| PUC-6MM-P | 6 mm OD PBT Push-to-Connect Union |
| PUC-8MM-P | 8 mm OD PBT Push-to-Connect Union |
| PUC-10MM-P | 10 mm OD PBT Push-to-Connect Union |
| PUC-18BR | 1/8 OD Brass Push-to-Connect Union |



PSR SERIES

PBT Stem Reducer. Not for water applications, only air. The working pressure is 150 psi and the temperature range is 32° F to 140° F.

| SKU | DESCRIPTION |
|---------------|-------------------------------|
| PSR-12S-38P | 1/2 by 3/8 PBT Stem Reducer |
| PSR-12S-516P | 1/2 by 5/16 PBT Stem Reducer |
| PSR-14S-18P | 1/4 by 1/8 PBT Stem Reducer |
| PSR-14S-316P | 1/4 by 3/16 PBT Stem Reducer |
| PSR-14S-532P | 1/4 by 5/32 PBT Stem Reducer |
| PSR-316S-18P | 3/16 by 1/8 PBT Stem Reducer |
| PSR-316S-532P | 3/16 by 5/32 PBT Stem Reducer |
| PSR-38S-14P | 3/8 by 1/4 PBT Stem Reducer |
| PSR-38S-516P | 3/8 by 5/16 PBT Stem Reducer |
| PSR-516S-14P | 5/16 by 1/4 PBT Stem Reducer |
| PSR-532S-18P | 5/32 by 1/8 PBT Stem Reducer |



PSC SERIES

PPF SERIES



The PPF Series is a push-to-connect cap for use with all push-to-connect fittings to block a port. The body is PBT with a Buna-N O-Ring. This fitting is also available in metric sizes.

| SKU | | Description |
|---------|-----------|-------------------------|
| PPF-14 | 1/4 inch | PBT Push-to-Connect Cap |
| PPF-38 | 3/8 inch | PBT Push-to-Connect Cap |
| PPF-532 | 5/32 inch | PBT Push-to-Connect Cap |

PP SERIES



These PBT Plugs block off push-to-connect ports. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

| SKU | | DESCRPTON |
|--------|------------|----------------------|
| PP-12 | 1/2 PBT | Push-to-Connect Plug |
| PP-14 | 1/4 PBT | Push-to-Connect Plug |
| PP-316 | 3/16 PBT | Push-to-Connect Plug |
| PP-38 | 3/8 PBT | Push-to-Connect Plug |
| PP-516 | 5/16 Brass | Push-to-Connect Plug |
| PP-532 | 5/32 PBT | Push-to-Connect Plug |
| PP-6M | 6 mm PBT | Push-to-Connect Plug |

PEMT SERIES



Push-to-connect Male Branch Swivel Tee with male NPT and UNF threads. The working pressure is 150 psi, the temperature range is 32° F to 140° F. This series is made of PBT resin, Nickel Plated Brass with a Buna-N O-ring and a Stainless Steel grip ring. For use with compressed air and inert gases. This fitting is also available with metric sizes.

| SKU | DESCRIPTION |
|--------------|-----------------------------------|
| PEMT-10U14P | 10-32 Male UNF by 1/4 OD PBT Tee |
| PEMT-10U18P | 10-32 Male UNF by 1/8 OD PBT Tee |
| PEMT-10U316P | 10-32 Male UNF by 3/16 OD PBT Tee |
| PEMT-10U532P | 10-32 Male UNF by 5/32 OD PBT Tee |
| PEMT-1M14P | 1/16 MNPT by 1/4 OD PBT Tee |
| PEMT-1M18P | 1/16 MNPT by 1/8 OD PBT Tee |
| PEMT-1M532P | 1/16 MNPT by 5/32 OD PBT Tee |
| PEMT-2M14P | 1/8 MNPT by 1/4 OD PBT Tee |
| PEMT-2M18P | 1/8 MNPT by 1/8 OD PBT Tee |
| PEMT-2M316P | 1/8 MNPT by 3/16 OD PBT Tee |
| PEMT-2M38P | 1/8 MNPT by 3/8 OD PBT Tee |
| PEMT-2M516P | 1/8 MNPT by 5/16 OD PBT Tee |
| PEMT-2M532P | 1/8 MNPT by 5/32 OD PBT Tee |
| PEMT-4M12P | 1/4 MNPT by 1/2 OD PBT Tee |
| PEMT-4M14P | 1/4 MNPT by 1/4 OD PBT Tee |
| PEMT-4M18P | 1/4 MNPT by 1/8 OD PBT Tee |
| PEMT-4M12P | 1/4 MNPT by 1/2 OD PBT Tee |
| PEMT-4M14P | 1/4 MNPT by 1/4 OD PBT Tee |
| PEMT-4M18P | 1/4 MNPT by 1/8 OD PBT Tee |
| PEMT-4M316P | 1/4 MNPT by 3/16 OD PBT Tee |
| PEMT-4M38P | 1/4 MNPT by 3/8 OD PBT Tee |
| PEMT-4M516P | 1/4 MNPT by 5/16 OD PBT Tee |
| PEMT-4M532P | 1/4 MNPT by 5/32 OD PBT Tee |
| PEMT-4R-4MM | 1/4 R MNPT by 4 mm OD PBT Tee |
| PEMT-4R-6MM | 1/4 R MNPT by 6 mm OD PBT Tee |
| PEMT-4R-8MM | 1/4 R MNPT by 8 mm OD PBT Tee |
| PEMT-6M12P | 3/8 MNPT by 1/2 OD PBT Tee |
| PEMT-6M14P | 3/8 MNPT by 1/4 OD PBT Tee |
| PEMT-6M316P | 3/8 MNPT by 3/16 OD PBT Tee |
| PEMT-6M38P | 3/8 MNPT by 3/8 OD PBT Tee |
| PEMT-8M12P | 1/2 MNPT by 1/2 OD PBT Tee |
| PEMT-8M38P | 1/2 MNPT by 3/8 OD PBT Tee |
| PEMT-8R-8MM | 1/2 R MNPT by 8 mm OD PBT Tee |



PEMR SERIES

| SKU | DESCRIPTION |
|--------------|--|
| PEMR-10U18P | 10-32 Male UNF by 1/8 OD PBT Male Run Tee |
| PEMR-10U316P | 10-32 Male UNF by 3/16 OD PBT Male Run Tee |
| PEMR-10U14P | 10-32 Male UNF by 1/4 OD PBT Male Run Tee |
| PEMR-10U532P | 10-32 Male UNF by 5/32 OD PBT Male Run Tee |
| PEMR-1M18P | 1/16 MNPT by 1/8 OD PBT Male Run Tee |
| PEMR-1M14P | 1/16 MNPT by 1/4 OD PBT Male Run Tee |
| PEMR-1M532P | 1/16 MNPT by 5/32 OD PBT Male Run Tee |
| PEMR-2M18P | 1/8 MNPT by 1/8 OD PBT Male Run Tee |
| PEMR-2M316P | 1/8 MNPT by 3/16 OD PBT Male Run Tee |
| PEMR-2M14P | 1/8 MNPT by 1/4 OD PBT Male Run Tee |
| PEMR-2M532P | 1/8 MNPT by 5/32 OD PBT Male Run Tee |
| PEMR-2M5P | 1/8 MNPT by 5/16 OD PBT Male Run Tee |
| PEMR-2M38P | 1/8 MNPT by 3/8 OD PBT Male Run Tee |
| PEMR-2M12P | 1/8 MNPT by 1/2 OD PBT Male Run Tee |
| PEMR-4M18P | 1/4 MNPT by 1/8 OD PBT Male Run Tee |
| PEMR-4M316P | 1/4 MNPT by 3/16 OD PBT Male Run Tee |
| PPEMR-4M516P | 1/4 MNPT by 5/16 OD PBT Male Run Tee |
| PEMR-4M532P | 1/4 MNPT by 5/32 OD PBT Male Run Tee |
| PEMR-4M14P | 1/4 MNPT by 1/4 OD PBT Male Run Tee |
| PEMR-4M38P | 1/4 MNPT by 3/8 OD PBT Male Run Tee |
| PEMR-4M8P | 1/4 MNPT by 1/2 OD PBT Male Run Tee |
| PEMR-6M316P | 3/8 MNPT by 3/16 OD PBT Male Run Tee |
| PEMR-6M14P | 3/8 MNPT by 1/4 OD PBT Male Run Tee |
| PEMR-6M38P | 3/8 MNPT by 3/8 OD PBT Male Run Tee |
| PEMR-6M12P | 3/8 MNPT by 1/2 OD PBT Male Run Tee |
| PEMR-8M38P | 1/2 MNPT by 3/8 OD PBT Male Run Tee |
| PEMR-8M12P | 1/2 MNPT by 1/2 OD PBT Male Run Tee |



PEM45

Male push-to-connect fitting is configured with a 45° elbow. The working pressure is 150 psi and the temperature range is 32° F to 140° F. Metal body material is Nickel-plated Brass and the resin is PBT. For use with compressed air and inert gases.

| SKU | DESCRIPTION |
|---------------|---|
| PEM45-10U18P | PEM45 10-32 Male UNF by 1/8 OD PBT Elbow |
| PEM45-10U316P | PEM45 10-32 Male UNF by 3/16 OD PBT Elbow |
| PEM45-10U14P | PEM45 10-32 Male UNF by 1/4 OD PBT Elbow |
| PEM45-10U532P | PEM45 10-32 Male UNF by 5/32 OD PBT Elbow |
| PEM45-2M18P | PEM45 1/8 MNPT by 1/8 OD PBT Elbow |
| PEM45-2M316P | PEM45 1/8 MNPT by 3/16 OD PBT Elbow |
| PEM45-2M14P | PEM45 1/8 MNPT by 1/4 OD PBT Elbow |
| PEM45-2M516P | PEM45 1/8 MNPT by 5/16 OD PBT Elbow |
| PEM45-2M532P | PEM45 1/8 MNPT by 5/32 OD PBT Elbow |
| PEM45-2M38P | PEM45 1/8 MNPT by 3/8 OD PBT Elbow |
| PEM45-4M14P | PEM45 1/4 MNPT by 1/4 OD PBT Elbow |
| PEM45-4M516P | PEM45 1/4 MNPT by 5/16 OD PBT Elbow |
| PEM45-4M38P | PEM45 1/4 MNPT by 3/8 OD PBT Elbow |
| PEM45-4M12P | PEM45 1/4 MNPT by 1/2 OD PBT Elbow |
| PEM45-6M14P | PEM45 3/8 MNPT by 1/4 OD PBT Elbow |
| PEM45-6M516P | PEM45 3/8 MNPT by 5/16 OD PBT Elbow |
| PEM45-6M38P | PEM45 3/8 MNPT by 3/8 OD PBT Elbow |
| PEM45-6M12P | PEM45 3/8 MNPT by 1/2 OD PBT Elbow |
| PEM45-8M14P | PEM45 1/2 MNPT by 1/4 OD PBT Elbow |
| PEM45-8M38P | PEM45 1/2 MNPT by 3/8 OD PBT Elbow |
| PEM45-8M12P | PEM45 1/2 MNPT by 1/2 OD PBT Elbow |



PEM - PUSH-TO-CONNECT ELBOW WITH HEX

Push-to-connect fitting is a male compact Swivel Elbow with a hex configuration. Working pressure 150 psi, temperature range is 32° F to 140° F. Nickel Plated Brass, Buna-N O-ring and the grip ring is Stainless Steel. For use with compressed air and inert gases. Long stem version available. SAE and G threads have an O-ring below the hex.



PEFC FEMALE PUSH-TO-CONNECT ELBOW WITH EXTERNAL HEX

Push-to-connect Swivel Female Elbow is configured with a 90° body with an external hex for tightening. The working pressure is 150 psi and the temperature range is 32° F to 140° F. Metal body material is Nickel-Plated Brass and the resin is PBT. For use with compressed air and inert gases.

| SKU | DESCRIPTION |
|--------------|---|
| PEFC-10U14P | 10-32 Female UNF by 1/4 OD Push-to-Connect Elbow |
| PEFC-10U18P | 10-32 Female UNF by 1/8 OD Push-to-Connect Elbow |
| PEFC-10U316P | 10-32 Female UNF by 3/16 OD Push-to-Connect Elbow |
| PEFC-10U532P | 10-32 Female UNF by 5/32 OD Push-to-Connect Elbow |
| PEFC-2F18P | 1/8 FNPT by 1/8 OD Push-to-Connect Elbow |
| PEFC-2F316P | 1/8 FNPT by 3/16 OD Push-to-Connect Elbow |
| PEFC-2F14P | 1/8 FNPT by 1/4 OD Push-to-Connect Elbow |
| PEFC-2F38P | 1/8 FNPT by 3/8 OD Push-to-Connect Elbow |
| PEFC-2F4P | 1/8 FNPT by 1/4 OD Push-to-Connect Elbow |
| PEFC-2F516P | 1/8 FNPT by 5/16 OD Push-to-Connect Elbow |
| PEFC-2F532P | 1/8 FNPT by 5/32 OD Push-to-Connect Elbow |
| PEFC-4F18P | 1/4 FNPT by 1/8 OD Push-to-Connect Elbow |
| PEFC-4F316P | 1/4 FNPT by 3/16 OD Push-to-Connect Elbow |
| PEFC-4F14P | 1/4 FNPT by 1/4 OD Push-to-Connect Elbow |
| PEFC-4F516P | 1/4 FNPT by 5/16 OD Push-to-Connect Elbow |
| PEFC-4F532P | 1/4 FNPT by 5/32 OD Push-to-Connect Elbow |

| SKU | DESCRIPTION |
|-------------|---|
| PEFC-4F6P | 1/4 FNPT by 3/8 OD Push-to-Connect Elbow |
| PEFC-4F8P | 1/4 FNPT by 1/2 OD Push-to-Connect Elbow |
| PEFC-6F316P | 3/8 FNPT by 3/16 OD Push-to-Connect Elbow |
| PEFC-6F14P | 3/8 FNPT by 1/4 OD Push-to-Connect Elbow |
| PEFC-6F516P | 3/8 FNPT by 5/16 OD Push-to-Connect Elbow |
| PEFC-6F38P | 3/8 FNPT by 3/8 OD Push-to-Connect Elbow |
| PEFC-6F12P | 3/8 FNPT by 1/2 OD Push-to-Connect Elbow |
| PEFC-8F38P | 1/2 FNPT by 3/8 OD Push-to-Connect Elbow |
| PEFC-8F12P | 1/2 FNPT by 1/2 OD Push-to-Connect Elbow |



PEA SERIES

Push-to-connect adjustable male swivel 90° Elbow with NPT and UNF threads. The working pressure is 150 psi, the temperature range is 32° F to 140° F. This series is made of PBT resin, Nickel Plated Brass with a Buna-N O-ring and a Stainless Steel grip ring. For use with compressed air and inert gases. This fitting is also available with metric sizes. These fittings can swivel a full 360°.

| SKU | DESCRIPTION |
|-------------|--|
| PEA-10U14P | 10-32 Male UNF by 1/4 OD PBT Adjustable Elbow |
| PEA-10U18P | 10-32 Male UNF by 1/8 OD PBT Adjustable Elbow |
| PEA-10U316P | 10-32 Male UNF by 3/16 OD PBT Adjustable Elbow |
| PEA-10U532P | 10-32 Male UNF by 5/32 OD PBT Adjustable Elbow |
| PEA-2M14P | 1/8 MNPT by 1/4 OD PBT Adjustable Elbow |
| PEA-2M18P | 1/8 MNPT by 1/8 OD PBT Adjustable Elbow |
| PEA-2M316P | 1/8 MNPT by 3/16 OD PBT Adjustable Elbow |
| PEA-2M516P | 1/8 MNPT by 5/16 OD PBT Adjustable Elbow |
| PEA-2M532P | 1/8 MNPT by 5/32 OD PBT Adjustable Elbow |
| PEA-4M14P | 1/4 MNPT by 1/4 OD PBT Adjustable Elbow |
| PEA-4M316P | 1/4 MNPT by 3/16 OD PBT Adjustable Elbow |
| PEA-4M516P | 1/4 MNPT by 5/16 OD PBT Adjustable Elbow |
| PEA-6M12P | 3/8 MNPT by 1/2 OD PBT Adjustable Elbow |
| PEA-6M14P | 3/8 MNPT by 1/4 OD PBT Adjustable Elbow |
| PEA-6M316P | 3/8 MNPT by 3/16 OD PBT Adjustable Elbow |
| PEA-6M38P | 3/8 MNPT by 3/8 OD PBT Adjustable Elbow |
| PEA-6M516P | 3/8 MNPT by 5/16 OD PBT Adjustable Elbow |
| PEA-8M12P | 1/2 MNPT by 1/2 OD PBT Adjustable Elbow |
| PEA-8M38P | 1/2 MNPT by 3/8 OD PBT Adjustable Elbow |



PBFC PUSH-TO-CONNECT FEMALE UNION BULKHEAD FITTING

Push-to-connect female Bulkhead Union fitting with female NPT and BSPT threads. It is made of nickel-plated brass with PBT resin. The working pressure is 150 psi and the temperature range is 32° F to 140° F. It can be used with compressed air and inert gases.

| SKU | DESCRIPTION |
|--------------|---|
| PBFC-2F-14P | 1/8 FNPT by 1/4 PBT Push-to-Connect Bulkhead |
| PBFC-2F-316P | 1/8 FNPT by 3/16 PBT Push-to-Connect Bulkhead |
| PBFC-2F-516P | 1/8 FNPT by 5/16 PBT Push-to-Connect Bulkhead |
| PBFC-2F-532P | 1/8 FNPT by 5/32 PBT Push-to-Connect Bulkhead |
| PBFC-4F-14P | 1/4 FNPT by 1/4 PBT Push-to-Connect Bulkhead |
| PBFC-4F-316P | 1/4 FNPT by 3/16 PBT Push-to-Connect Bulkhead |
| PBFC-4F-38P | 1/4 FNPT by 3/8 PBT Push-to-Connect Bulkhead |
| PBFC-4F-516P | 1/4 FNPT by 5/16 PBT Push-to-Connect Bulkhead |
| PBFC-4G6MM-P | 1/4 Female BSPT by 6mm PBT Push-to-Connect Bulkhead |
| PBFC-4G8MM-P | 1/4 Female BSPT by 8mm PBT Push-to-Connect Bulkhead |
| PBFC-4R6MM-P | 1/4 Female BSPT by 6mm PBT Push-to-Connect Bulkhead |
| PBFC-4R8MM-P | 1/4 Female BSPT by 8mm PBT Push-to-Connect Bulkhead |
| PBFC-6F-516P | 3/8 FNPT by 5/16 PBT Push-to-Connect Bulkhead |
| PBFC-6F-6P | 3/8 FNPT by 3/8 PBT Push-to-Connect Bulkhead |
| PBFC-6F-8P | 3/8 FNPT by 1/2 PBT Push-to-Connect Bulkhead |
| PBFC-6G6MM-P | 3/8 Female BSPT by 6mm PBT Push-to-Connect Bulkhead |



DEFV SERIES PUSH-TO-CONNECT FLOW CONTROL VALVE

Push-to-Connect Flow Control Valve Elbow made with nickel-plated threads and stem with a PBT body. Standard controls flow out but checks the flow back. These valves needle the flow in from the tube and check the flow back through the tubing line. They are equipped with a single push-to-connect port at a 90° angle to the male thread. Thread sizes are 10-32, 1/8", 1/4", 3/8" and 1/2".

| SKU | DESCRIPTION |
|--------------|--|
| DEFV-10U18P | 10-32 by 1/8 OD Push-to-Connect Elbow Flow Control |
| DEFV-10U532P | 10-32 by 5/32 OD Push-to-Connect Elbow Flow Control |
| DEFV-10U316P | 10-32 by 3/16 OD Push-to-Connect Elbow Flow Control |
| DEFV-10U14P | 10-32 by 1/4 OD Push-to-Connect Elbow Flow Control |
| DEFV-10U516P | 10-32 by 5/16 OD Push-to-Connect Elbow Flow Control |
| DEFV-2M18P | 1/8 MNPT by 1/8 OD Push-to-Connect Elbow Flow Control |
| DEFV-2M532P | 1/8 MNPT by 5/32 OD Push-to-Connect Elbow Flow Control |
| DEFV-2M316P | 1/8 MNPT by 3/16 OD Push-to-Connect Elbow Flow Control |
| DEFV-2M14P | 1/8 MNPT by 1/4 OD Push-to-Connect Elbow Flow Control |
| DEFV-2M516P | 1/8 MNPT by 5/16 OD Push-to-Connect Elbow Flow Control |
| DEFV-4M532P | 1/4 MNPT by 5/32 OD Push-to-Connect Elbow Flow Control |
| DEFV-4M316P | 1/4 MNPT by 3/16 OD Push-to-Connect Elbow Flow Control |
| DEFV-4M14P | 1/4 MNPT by 1/4 OD Push-to-Connect Elbow Flow Control |
| DEFV-4M516P | 1/4 MNPT by 5/16 OD Push-to-Connect Elbow Flow Control |
| DEFV-4M38P | 1/4 MNPT by 3/8 OD Push-to-Connect Elbow Flow Control |
| DEFV-4M12P | DEFV-4M12P 1/4 MNPT by 1/2 OD Push-to-Connect Elbow Flow Control |
| DEFV-6M316P | DEFV-6M316P 3/8 MNPT by 3/16 OD Push-to-Connect Elbow Flow Control |
| DEFV-6M14P | DEFV-6M14P 3/8 MNPT by 1/4 OD Push-to-Connect Elbow Flow Control |
| DEFV-6M516P | 3/8 MNPT by 5/16 OD Push-to-Connect Elbow Flow Control |
| DEFV-6M38P | 3/8 MNPT by 3/8 OD Push-to-Connect Elbow Flow Control |
| DEFV-6M12P | 3/8 MNPT by 1/2 OD Push-to-Connect Elbow Flow Control |
| DEFV-8M516P | 1/2 MNPT by 5/16 OD Push-to-Connect Elbow Flow Control |
| DEFV-8M38P | 1/2 MNPT by 3/8 OD Push-to-Connect Elbow Flow Control |

INDEX

D

DEFV Series Push-to-Connect Flow Control Valve 15

P

PBFC PUSH-TO-CONNECT FEMALE UNION BULKHEAD FITTING 14

PEA SERIES 13

PEFC FEMALE PUSH-TO-CONNECT ELBOW WITH EXTERNAL HEX 12

PEM - Push-to-Connect Elbow with hex 12

PEM45 11

PEMR SERIES 10

PEMT SERIES 9

PP Series 8

PPF Series 8

PSC SERIES 7

PSR SERIES 7

PUC COMPACT STRAIGHT PUSH-TO-CONNECT FITTING 6

PUCX SERIES 6

PUE SERIES 5

PUM Series - Straight Line Push-to-Connect Manifold 4

PUT EQUAL PUSH-TO-CONNECT UNION TEE 4

PUTR PUSH-TO-CONNECT REDUCER TEE 3

PUY - PBT Three Port WYE Push-to-Connect 3

PUYR - PBT Straight Compact WYE Reducer Push-to-Connect Reducer 2