



PBT PUSH-TO-CONNECTS

PBT PUSH TO CONNECTS

Our PBT push-to-connect fittings are available in a variety of sizes and orientations, including Ts, elbows, straights, and wyes.



PP SERIES

These PBT Plugs block off push-to-connect ports. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

SKU	DESCRIPTION
PP-12	1/2 PBT Push-to-Connect Plug
PP-14	1/4 PBT Push-to-Connect Plug
PP-316	3/16 PBT Push-to-Connect Plug
PP-38	3/8 PBT Push-to-Connect Plug
PP-516	5/16 Brass Push-to-Connect Plug
PP-532	5/32 PBT Push-to-Connect Plug
PP-6M	6 mm PBT Push-to-Connect Plug

PUM SERIES



The PUM Series is a straight line Manifold with equal or reducing push-to-connect ports. It is also available with male NPT threads on the in-port.

SKU	DESCRIPTION
PUM-14	1/4 In/Out and 3 1/4 Ports Manifold
PUM-14532	1/4 In/Out and 3 5/32 Ports Manifold
PUM-18	1/8 In/Out and 3 1/8 Ports Manifold
PUM-3814	3/8 In/Out and 3 1/4 Ports Manifold
PUM-38516	3/8 In/Out and 3 5/16 Ports Manifold
PUM-516	5/16 In/Out and 3 5/16 Ports Manifold
PUM-51614	5/16 In/Out and 3 1/4 Ports Manifold
PUM-516316	5/16 In/Out and 3 3/16 Ports Manifold
PUM-516532	5/16 In/Out and 3 5/32 Ports Manifold
PUM-532	5/32 In/Out and 3 5/32 Ports Manifold
PUM-532185	5/32 In/Out and 3 1/8 Ports Manifold
PUM-2M532	1/8 MNPT In 5/32 Out and 3 5/32 Ports Manifold

SKU	DESCRIPTION
PUM-2M532-316	1/8 MNPT In 5/32 Out and 3 3/16 Ports Manifold
PUM-4M316-516	1/4 MNPT In 5/16 Out and 3 5/16 Ports Manifold
PUM-4M516-38	1/4 MNPT In 5/16 Out and 3 3/8 Ports Manifold
PUM-4M532-14	1/4 MNPT In 5/32 Out and 3 1/4 Ports Manifold
PUM-4M532-316	1/4 MNPT in 5/32 Out and 3 3/16 PortsManifold
PUM-4M532-516	3/8 MNPT In 1/4 Out and 3 5/16 Ports Manifold
PUM-6M14-516	3/8 MNPT In 1/4 Out and 3 5/16 Ports Manifold
PUM-8M516-38	1/2 MNPT In 5/16 Out and 3 3/8 Ports Manifold
PUMR-14532	1/4 In/out with 3- 5/32 Ports Reducer Manifold



DEFV SERIES

DEFV series is a Push-to-Connect Flow Control Valve Elbow made with nickel-plated threads and a stem with a PBT body. Standard controls flow out but checks the flow back. Also, these valves needle the flow from the tube and check the flow back through the tubing line. They are equipped with a single push-to-connect port at a 90° angle to the male thread. Furthermore, thread sizes are 10-32, 1/8", 1/4", 3/8" and 1/2".

SKU	DESCRIPTION
DEFV-10U18P	10-32 by 1/8 OD Push-to-Connect Elbow Flow Control
DEFV-10U532P	10-32 by 5/32 OD Push-to-Connect Elbow Flow Control
DEFV-10U316P	10-32 by 3/16 OD Push-to-Connect Elbow Flow Control
DEFV-10U14P	10-32 by 1/4 OD Push-to-Connect Elbow Flow Control
DEFV-10U516P	10-32 by 5/16 OD Push-to-Connect Elbow Flow Control
DEFV-2M18P	1/8 MNPT by 1/8 OD Push-to-Connect Elbow Flow Control
DEFV-2M532P	1/8 MNPT by 5/32 OD Push-to-Connect Elbow Flow Control
DEFV-2M316P	1/8 MNPT by 3/16 OD Push-to-Connect Elbow Flow Control
DEFV-2M14P	1/8 MNPT by 1/4 OD Push-to-Connect Elbow Flow Control
DEFV-2M516P	1/8 MNPT by 5/16 OD Push-to-Connect Elbow Flow Control
DEFV-4M532P	1/4 MNPT by 5/32 OD Push-to-Connect Elbow Flow Control
DEFV-4M316P	1/4 MNPT by 3/16 OD Push-to-Connect Elbow Flow Control
DEFV-4M14P	1/4 MNPT by 1/4 OD Push-to-Connect Elbow Flow Control
DEFV-4M516P	1/4 MNPT by 5/16 OD Push-to-Connect Elbow Flow Control
DEFV-4M38P	1/4 MNPT by 3/8 OD Push-to-Connect Elbow Flow Control
DEFV-4M12P	DEFV-4M12P 1/4 MNPT by 1/2 OD Push-to-Connect Elbow Flow Control

SKU	DESCRIPTION
DEFV-6M316P	DEFV-6M316P 3/8 MNPT by 3/16 OD Push-to-Connect Elbow Flow Control
DEFV-6M14P	DEFV-6M14P 3/8 MNPT by 1/4 OD Push-to-Connect Elbow Flow Control
DEFV-6M516P	3/8 MNPT by 5/16 OD Push-to-Connect Elbow Flow Control
DEFV-6M38P	3/8 MNPT by 3/8 OD Push-to-Connect Elbow Flow Control
DEFV-6M12P	3/8 MNPT by 1/2 OD Push-to-Connect Elbow Flow Control
DEFV-8M516P	1/2 MNPT by 5/16 OD Push-to-Connect Elbow Flow Control
DEFV-8M38P	1/2 MNPT by 3/8 OD Push-to-Connect Elbow Flow Control



PUYR SERIES- PBT REDUCER

The PUYR Series is a compact Straight Wye Reducer fitting that has three push-to-connect ports in a wye pattern with two smaller ports side by side opposite the third larger port. Also, the body is PBT resin with Nickel-plated Brass threads. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

PUC SERIES



Compact Straight Fitting with two push-to-connect ports in opposite directions. The body is PBT resin. The working pressure is 150 psi and the temperature range is 32° F to 140° F. Suitable for applications involving compressed air and inert gases.

SKU	DESCRIPTION
PUC-12P	1/2 OD PBT Push-to-Connect Union
PUC-14P	1/4 OD PBT Push-to-Connect Union
PUC-18P	1/8 OD PBT Push-to-Connect Union
PUC-316P	3/16 OD PBT Push-to-Connect Union
PUC-38-P	3/8 OD PBT Push-to-Connect Union
PUC-516-P	5/16 OD PBT Push-to-Connect Union
PUC-532-P	5/32 OD PBT Push-to-Connect Union
PUC-58P	5/8 OD PBT Push-to-Connect Union
PUC-4MM-P	4 mm OD PBT Push-to-Connect Union
PUC-6MM-P	6 mm OD PBT Push-to-Connect Union
PUC-8MM-P	8 mm OD PBT Push-to-Connect Union
PUC-10MM-P	10 mm OD PBT Push-to-Connect Union
PUC-18BR	1/8 OD Brass Push-to-Connect Union

PUT SERIES- EQUAL PUSH-TO-CONNECTS



The PUT Series is a Union Tee Fitting that has 3 push-to-connect ports of equal sizes. The body is PBT resin. In addition, the working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

SKU	DESCRIPTION
PUT-12N	1/2 OD Push-to-Connect Tee Nylon
PUT-14P	1/4 OD PBT Push-to-Connect Tee
PUT-18P	1/8 OD PBT Push-to-Connect Tee
PUT-316P	3/16 OD PBT Push-to-Connect Tee
PUT-38-P	3/8 OD PBT Push-to-Connect Tee
PUT-532-P	5/32 OD PBT Push-to-Connect Tee

SKU	DESCRIPTION
PUT-5P	5/16 OD PBT Push-to-Connect Tee
PUT-4MM-P	4 mm OD PBT Push-to-Connect Tee
PUT-6MM-P	6 mm OD PBT Push-to-Connect Tee
PUT-8MM-P	8 mm OD PBT Push-to-Connect Tee



PUTR SERIES

Union Tee fitting with 2 push-to-connect ports of equal sizes and 1 push-to-connect port that is a reducer located 90° apart. The body is PBT resin. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

SKU	DESCRIPTION
PUTR-12-38P	1/2 OD by 3/8 OD PBT Reducing Tee
PUTR-12-516P	1/2 OD by 5/16 OD PBT Reducing Tee
PUTR-14-18P	1/4 OD by 1/8 OD PBT Reducing Tee
PUTR-14-316P	1/4 OD by 3/16 OD PBT Reducing Tee
PUTR-316-532P	3/16 OD by 5/32 OD PBT Reducing Tee
PUTR-38-14P	1/4 OD by 3/8 OD PBT Reducing Tee
PUTR-38-516P	3/8 OD by 5/16 OD PBT Reducing Tee
PUTR-4532P	1/4 OD by 5/32 OD PBT Reducing Tee
PUTR-516-14P	5/16 OD by 1/4 OD PBT Reducing Tee
PUTR-516-532P	5/16 OD by 5/32 OD PBT Reducing Tee

PUE SERIES



The PUE Series is a composite Union Elbow made of a PBT body and a Buna-N seal. The working pressure is 150 psi and a temperature range of 32° F to 140° F.

SKU	DESCRIPTION
PUE-12P	1/2 PBT Elbow Push-to-Connect
PUE-14P	1/4 PBT Elbow Push-to-Connect
PUE-18P	1/8 PBT Elbow Push-to-Connect
PUE-316P	3/16 PBT Elbow Push-to-Connect
PUE-38P	3/8 PBT Elbow Push-to-Connect
PUE-5/16-P	5/16 PBT Elbow Push-to-Connect
PUE-532P	5/32 PBT Elbow Push-to-Connect
PUE-4MM-P	4 mm PBT Elbow Push-to-Connect
PUE-6MM-P	6 mm PBT Elbow Push-to-Connect

PEA SERIES



Push-to-connect adjustable male swivel 90° Elbow with NPT and UNF threads. The working pressure is 150 psi, and the temperature range is 32° F to 140° F. This series is made of PBT resin, nickel-plated brass with a Buna-N O-ring, and a Stainless Steel grip ring. For use with compressed air and inert gases. This fitting is also available in metric sizes. In fact, these fittings can swivel a full 360°.

SKU	DESCRIPTION
PEA-10U14P	10-32 Male UNF by 1/4 OD PBT Adjustable Elbow
PEA-10U18P	10-32 Male UNF by 1/8 OD PBT Adjustable Elbow
PEA-10U316P	10-32 Male UNF by 3/16 OD PBT Adjustable Elbow
PEA-10U532P	10-32 Male UNF by 5/32 OD PBT Adjustable Elbow
PEA-2M14P	1/8 MNPT by 1/4 OD PBT Adjustable Elbow
PEA-2M18P	1/8 MNPT by 1/8 OD PBT Adjustable Elbow
PEA-2M316P	1/8 MNPT by 3/16 OD PBT Adjustable Elbow
PEA-2M516P	1/8 MNPT by 5/16 OD PBT Adjustable Elbow
PEA-2M532P	1/8 MNPT by 5/32 OD PBT Adjustable Elbow

SKU	DESCRIPTION
PEA-4M14P	1/4 MNPT by 1/4 OD PBT Adjustable Elbow
PEA-4M316P	1/4 MNPT by 3/16 OD PBT Adjustable Elbow
PEA-4M516P	1/4 MNPT by 5/16 OD PBT Adjustable Elbow
PEA-6M12P	3/8 MNPT by 1/2 OD PBT Adjustable Elbow
PEA-6M14P	3/8 MNPT by 1/4 OD PBT Adjustable Elbow
PEA-6M316P	3/8 MNPT by 3/16 OD PBT Adjustable Elbow
PEA-6M38P	3/8 MNPT by 3/8 OD PBT Adjustable Elbow
PEA-6M516P	3/8 MNPT by 5/16 OD PBT Adjustable Elbow
PEA-8M12P	1/2 MNPT by 1/2 OD PBT Adjustable Elbow
PEA-8M38P	1/2 MNPT by 3/8 OD PBT Adjustable Elbow



PEM SERIES

Push-to-connect fitting is a male compact Swivel Elbow with a hex configuration. Working pressure 150 psi, the temperature range is 32° F to 140° F. Nickel Plated Brass, Buna-N O-ring, and the grip ring is Stainless Steel. For use with compressed air and inert gases. Long stem version available. SAE and G threads have an O-ring below the hex.



PEMR SERIES

The PEMR Series is a Tee Push-to-Connect with a Metal Hex, see available options below.

SKU	DESCRIPTION
PEMR-10U18P	10-32 Male UNF by 1/8 OD PBT Male Run Tee
PEMR-10U316P	10-32 Male UNF by 3/16 OD PBT Male Run Tee
PEMR-10U14P	10-32 Male UNF by 1/4 OD PBT Male Run Tee
PEMR-10U532P	10-32 Male UNF by 5/32 OD PBT Male Run Tee
PEMR-1M18P	1/16 MNPT by 1/8 OD PBT Male Run Tee
PEMR-1M14P	1/16 MNPT by 1/4 OD PBT Male Run Tee
PEMR-1M532P	1/16 MNPT by 5/32 OD PBT Male Run Tee
PEMR-2M18P	1/8 MNPT by 1/8 OD PBT Male Run Tee
PEMR-2M316P	1/8 MNPT by 3/16 OD PBT Male Run Tee
PEMR-2M14P	1/8 MNPT by 1/4 OD PBT Male Run Tee
PEMR-2M532P	1/8 MNPT by 5/32 OD PBT Male Run Tee
PEMR-2M5P	1/8 MNPT by 5/16 OD PBT Male Run Tee
PEMR-2M38P	1/8 MNPT by 3/8 OD PBT Male Run Tee
PEMR-2M12P	1/8 MNPT by 1/2 OD PBT Male Run Tee
PEMR-4M18P	1/4 MNPT by 1/8 OD PBT Male Run Tee
PEMR-4M316P	1/4 MNPT by 3/16 OD PBT Male Run Tee
PPEMR-4M516P	1/4 MNPT by 5/16 OD PBT Male Run Tee
PEMR-4M532P	1/4 MNPT by 5/32 OD PBT Male Run Tee
PEMR-4M14P	1/4 MNPT by 1/4 OD PBT Male Run Tee
PEMR-4M38P	1/4 MNPT by 3/8 OD PBT Male Run Tee
PEMR-4M8P	1/4 MNPT by 1/2 OD PBT Male Run Tee
PEMR-6M316P	3/8 MNPT by 3/16 OD PBT Male Run Tee
PEMR-6M14P	3/8 MNPT by 1/4 OD PBT Male Run Tee
PEMR-6M38P	3/8 MNPT by 3/8 OD PBT Male Run Tee
PEMR-6M12P	3/8 MNPT by 1/2 OD PBT Male Run Tee
PEMR-8M38P	1/2 MNPT by 3/8 OD PBT Male Run Tee
PEMR-8M12P	1/2 MNPT by 1/2 OD PBT Male Run Tee



PBFC BULKHEAD SERIES

Push-to-connect female Bulkhead Union fitting with female NPT and BSPT threads. It is made of nickel-plated brass with PBT resin. The working pressure is 150 psi and the temperature range is 32° F to 140° F. It can be used with compressed air and inert gases.

SKU	DESCRIPTION
PBFC-2F-14P	1/8 FNPT by 1/4 PBT Push-to-Connect Bulkhead
PBFC-2F-316P	1/8 FNPT by 3/16 PBT Push-to-Connect Bulkhead
PBFC-2F-516P	1/8 FNPT by 5/16 PBT Push-to-Connect Bulkhead
PBFC-2F-532P	1/8 FNPT by 5/32 PBT Push-to-Connect Bulkhead
PBFC-4F-14P	1/4 FNPT by 1/4 PBT Push-to-Connect Bulkhead
PBFC-4F-316P	1/4 FNPT by 3/16 PBT Push-to-Connect Bulkhead
PBFC-4F-38P	1/4 FNPT by 3/8 PBT Push-to-Connect Bulkhead
PBFC-4F-516P	1/4 FNPT by 5/16 PBT Push-to-Connect Bulkhead
PBFC-4G6MM-P	1/4 Female BSPT by 6mm PBT Push-to-Connect Bulkhead
PBFC-4G8MM-P	1/4 Female BSPT by 8mm PBT Push-to-Connect Bulkhead
PBFC-4R6MM-P	1/4 Female BSPT by 6mm PBT Push-to-Connect Bulkhead
PBFC-4R8MM-P	1/4 Female BSPT by 8mm PBT Push-to-Connect Bulkhead
PBFC-6F-516P	3/8 FNPT by 5/16 PBT Push-to-Connect Bulkhead
PBFC-6F-6P	3/8 FNPT by 3/8 PBT Push-to-Connect Bulkhead
PBFC-6F-8P	3/8 FNPT by 1/2 PBT Push-to-Connect Bulkhead
PBFC-6G6MM-P	3/8 Female BSPT by 6mm PBT Push-to-Connect Bulkhead

PEMT SERIES



Push-to-connect Male Branch Swivel Tee with male NPT and UNF threads. The working pressure is 150 psi, and the temperature range is 32° F to 140° F. Also, this series is made of PBT resin, Nickel nickel-plated brass with a Buna-N O-ring, and a Stainless Steel grip ring. For use with compressed air and inert gases. This fitting is also available in metric sizes.

SKU	DESCRIPTION
PEMT-10U14P	10-32 Male UNF by 1/4 OD PBT Tee
PEMT-10U18P	10-32 Male UNF by 1/8 OD PBT Tee
PEMT-10U316P	10-32 Male UNF by 3/16 OD PBT Tee
PEMT-10U532P	10-32 Male UNF by 5/32 OD PBT Tee
PEMT-1M14P	1/16 MNPT by 1/4 OD PBT Tee
PEMT-1M18P	1/16 MNPT by 1/8 OD PBT Tee
PEMT-1M532P	1/16 MNPT by 5/32 OD PBT Tee
PEMT-2M14P	1/8 MNPT by 1/4 OD PBT Tee
PEMT-2M18P	1/8 MNPT by 1/8 OD PBT Tee
PEMT-2M316P	1/8 MNPT by 3/16 OD PBT Tee
PEMT-2M38P	1/8 MNPT by 3/8 OD PBT Tee
PEMT-2M516P	1/8 MNPT by 5/16 OD PBT Tee
PEMT-2M532P	1/8 MNPT by 5/32 OD PBT Tee
PEMT-4M12P	1/4 MNPT by 1/2 OD PBT Tee
PEMT-4M14P	1/4 MNPT by 1/4 OD PBT Tee
PEMT-4M18P	1/4 MNPT by 1/8 OD PBT Tee
PEMT-4M12P	1/4 MNPT by 1/2 OD PBT Tee
PEMT-4M14P	1/4 MNPT by 1/4 OD PBT Tee
PEMT-4M18P	1/4 MNPT by 1/8 OD PBT Tee
PEMT-4M316P	1/4 MNPT by 3/16 OD PBT Tee
PEMT-4M38P	1/4 MNPT by 3/8 OD PBT Tee
PEMT-4M516P	1/4 MNPT by 5/16 OD PBT Tee
PEMT-4M532P	1/4 MNPT by 5/32 OD PBT Tee
PEMT-4R-4MM	1/4 R MNPT by 4 mm OD PBT Tee
PEMT-4R-6MM	1/4 R MNPT by 6 mm OD PBT Tee
PEMT-4R-8MM	1/4 R MNPT by 8 mm OD PBT Tee
PEMT-6M12P	3/8 MNPT by 1/2 OD PBT Tee
PEMT-6M14P	3/8 MNPT by 1/4 OD PBT Tee
PEMT-6M316P	3/8 MNPT by 3/16 OD PBT Tee
PEMT-6M38P	3/8 MNPT by 3/8 OD PBT Tee
PEMT-8M12P	1/2 MNPT by 1/2 OD PBT Tee

SKU	DESCRIPTION
PEMT-8M38P	1/2 MNPT by 3/8 OD PBT Tee
PEMT-8R-8MM	1/2 R MNPT by 8 mm OD PBT Tee



PSR SERIES

The PSR Series is a PBT Stem Reducer. Not for water applications, only air. The working pressure is 150 psi and the temperature range is 32° F to 140° F.

SKU	DESCRIPTION
PSR-12S-38P	1/2 by 3/8 PBT Stem Reducer
PSR-12S-516P	1/2 by 5/16 PBT Stem Reducer
PSR-14S-18P	1/4 by 1/8 PBT Stem Reducer
PSR-14S-316P	1/4 by 3/16 PBT Stem Reducer
PSR-14S-532P	1/4 by 5/32 PBT Stem Reducer
PSR-316S-18P	3/16 by 1/8 PBT Stem Reducer
PSR-316S-532P	3/16 by 5/32 PBT Stem Reducer
PSR-38S-14P	3/8 by 1/4 PBT Stem Reducer
PSR-38S-516P	3/8 by 5/16 PBT Stem Reducer
PSR-516S-14P	5/16 by 1/4 PBT Stem Reducer
PSR-532S-18P	5/32 by 1/8 PBT Stem Reducer

PSC SERIES



PEM45 SERIES- PUSH-TO-CONNECT



The PEM45 Series is a male push-to-connect fitting configured with a 45° elbow. The working pressure is 150 psi and the temperature range is 32° F to 140° F. Also, the metal body material is Nickel-plated Brass and the resin is PBT. This product is intended for use with compressed air and inert gases.

SKU	DESCRIPTION
PEM45-10U18P	PEM45 10-32 Male UNF by 1/8 OD PBT Elbow
PEM45-10U316P	PEM45 10-32 Male UNF by 3/16 OD PBT Elbow
PEM45-10U14P	PEM45 10-32 Male UNF by 1/4 OD PBT Elbow
PEM45-10U532P	PEM45 10-32 Male UNF by 5/32 OD PBT Elbow
PEM45-2M18P	PEM45 1/8 MNPT by 1/8 OD PBT Elbow
PEM45-2M316P	PEM45 1/8 MNPT by 3/16 OD PBT Elbow
PEM45-2M14P	PEM45 1/8 MNPT by 1/4 OD PBT Elbow
PEM45-2M516P	PEM45 1/8 MNPT by 5/16 OD PBT Elbow
PEM45-2M532P	PEM45 1/8 MNPT by 5/32 OD PBT Elbow
PEM45-2M38P	PEM45 1/8 MNPT by 3/8 OD PBT Elbow
PEM45-4M14P	PEM45 1/4 MNPT by 1/4 OD PBT Elbow
PEM45-4M516P	PEM45 1/4 MNPT by 5/16 OD PBT Elbow
PEM45-4M38P	PEM45 1/4 MNPT by 3/8 OD PBT Elbow
PEM45-4M12P	PEM45 1/4 MNPT by 1/2 OD PBT Elbow
PEM45-6M14P	PEM45 3/8 MNPT by 1/4 OD PBT Elbow

SKU	DESCRIPTION
PEM45-6M516P	PEM45 3/8 MNPT by 5/16 OD PBT Elbow
PEM45-6M38P	PEM45 3/8 MNPT by 3/8 OD PBT Elbow
PEM45-6M12P	PEM45 3/8 MNPT by 1/2 OD PBT Elbow
PEM45-8M14P	PEM45 1/2 MNPT by 1/4 OD PBT Elbow
PEM45-8M38P	PEM45 1/2 MNPT by 3/8 OD PBT Elbow
PEM45-8M12P	PEM45 1/2 MNPT by 1/2 OD PBT Elbow



PUCX SERIES

PUCX Series is a union Cross push-to-connect fitting with four opposing, equal-sized ports made of Polybutylene. This fitting is also available in metric sizes.

SKU	DESCRIPTION
PUCX-12P	1/2 OD Cross Polybutylene
PUCX-14P	1/4 OD Cross Polybutylene
PUCX-18P	1/8 OD Cross Polybutylene
PUCX-316P	3/16 OD Cross Polybutylene
PUCX-38P	3/8 OD Cross Polybutylene
PUCX-516P	5/16 Cross Polybutylene
PUCX-532P	5/32 Cross Polybutylene
PUCX-1238P	3/8 by 1/2 OD Cross Polybutylene
PUCX-38516P	5/16 by 3/8 OD Cross Polybutylene



PUY SERIES- PUSH-TO-CONNECT

Compact straight fitting with three push-to-connect ports in a Wye pattern with two ports side by side opposite the third port. The body is PBT resin with Nickel-Plated Brass threads. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

SKU	DESCRIPTION
PUY-12P	1/2 OD Parallel PBT Wye
PUY-14P	1/4 OD Parallel PBT Wye
PUY-18P	1/8 OD Parallel PBT Wye
PUY-316P	3/16 OD Parallel PBT Wye
PUY-38P	3/8 OD Parallel PBT Wye
PUY-516P	5/16 OD Parallel PBT Wye
PUY-532P	5/32 OD Parallel PBT Wye



PEFC SERIES

The PEFC Series is a push-to-connect Swivel Female Elbow that is configured with a 90° body **with an external hex for tightening**. The working pressure is 150 psi and the temperature range is 32° F to 140° F. Metal body material is Nickel-Plated Brass and the resin is PBT. For use with compressed air and inert gases.

SKU	DESCRIPTION
PEFC-10U14P	10-32 Female UNF by 1/4 OD Push-to-Connect Elbow
PEFC-10U18P	10-32 Female UNF by 1/8 OD Push-to-Connect Elbow
PEFC-10U316P	10-32 Female UNF by 3/16 OD Push-to-Connect Elbow
PEFC-10U532P	10-32 Female UNF by 5/32 OD Push-to-Connect Elbow
PEFC-2F18P	1/8 FNPT by 1/8 OD Push-to-Connect Elbow
PEFC-2F316P	1/8 FNPT by 3/16 OD Push-to-Connect Elbow
PEFC-2F14P	1/8 FNPT by 1/4 OD Push-to-Connect Elbow
PEFC-2F38P	1/8 FNPT by 3/8 OD Push-to-Connect Elbow
PEFC-2F4P	1/8 FNPT by 1/4 OD Push-to-Connect Elbow

SKU	DESCRIPTION
PEFC-2F516P	1/8 FNPT by 5/16 OD Push-to-Connect Elbow
PEFC-2F532P	1/8 FNPT by 5/32 OD Push-to-Connect Elbow
PEFC-4F18P	1/4 FNPT by 1/8 OD Push-to-Connect Elbow
PEFC-4F316P	1/4 FNPT by 3/16 OD Push-to-Connect Elbow
PEFC-4F14P	1/4 FNPT by 1/4 OD Push-to-Connect Elbow
PEFC-4F516P	1/4 FNPT by 5/16 OD Push-to-Connect Elbow
PEFC-4F532P	1/4 FNPT by 5/32 OD Push-to-Connect Elbow
PEFC-4F6P	1/4 FNPT by 3/8 OD Push-to-Connect Elbow
PEFC-4F8P	1/4 FNPT by 1/2 OD Push-to-Connect Elbow
PEFC-6F316P	3/8 FNPT by 3/16 OD Push-to-Connect Elbow
PEFC-6F14P	3/8 FNPT by 1/4 OD Push-to-Connect Elbow
PEFC-6F516P	3/8 FNPT by 5/16 OD Push-to-Connect Elbow
PEFC-6F38P	3/8 FNPT by 3/8 OD Push-to-Connect Elbow
PEFC-6F12P	3/8 FNPT by 1/2 OD Push-to-Connect Elbow
PEFC-8F38P	1/2 FNPT by 3/8 OD Push-to-Connect Elbow
PEFC-8F12P	1/2 FNPT by 1/2 OD Push-to-Connect Elbow

PPF SERIES



The PPF Series is a push-to-connect cap for use with all push-to-connect fittings to block a port. The body is PBT with a Buna-N O-Ring. This fitting is also available in metric sizes.

SKU	Description
PPF-14	1/4 inch PBT Push-to-Connect Cap
PPF-38	3/8 inch PBT Push-to-Connect Cap
PPF-532	5/32 inch PBT Push-to-Connect Cap