



## **PLASTIC BALL VALVES**

Plastic Ball Valves, commonly used in landscaping, are essential when trying to control the flow of liquid. We offer 2-way and 3-way valves in a variety of sizes and materials.



## 2-WAY PLASTIC BALL VALVES

2-Way Plastic Ball Valves are a simple solution when you need a simple flow restriction device. Pneuline offers several different ball valve variations.

### PKV SERIES



The PKV Series is a Polypropylene Ball Valve with Push-to-Connect connections and EPDM seals. Not suitable for vacuum, air, or inert gases.

SKU	Description
PKV-14	1/4 inch OD Push-in Shut-off Ball Valve
PKV-38	3/8 inch OD Push-in Shut-off Ball Valve
PKV-4M14	1/4 inch Male NPT by 1/4 inch OD Ball Valve
PKV-4F14E	1/4 inch Female NPT by 1/4 inch OD Elbow Ball Valve
PKV-4F38E	1/4 inch Female NPT by 3/8 OD Elbow Ball Valve

## PJV SERIES



The PJV Series Micro Ball Valves are of Polypropylene and reinforced fiberglass with a 90 degree rotating handle and FKM O-rings. Standard pressure is 150 psi with maximum temperature of 150° with a maximum pressure of 300 psi at 70° F.

SKU	Description
PJV-38B	3/8 inch Barbed Glass-Filled Polypropylene Micro Ball Valve with FKM Seals
PJV-38F	3/8 inch Female Glass-Filled Polypropylene Micro Ball Valve with FKM Seals
PJV-4F4M	1/4 inch Female by 1/4 inch Male
PJV-4B	1/4 inch Barbed Polypropylene Micro Ball Valve
PJV-6F6M	3/8 inch Female by 3/8 inch Male Polypropylene Micro Ball Valve
PJV-6B	3/8 inch Barbed Polypropylene Micro Ball Valve
PJV-8F8M	1/2 inch Female by 1/2 inch Male Polypropylene Micro Ball Valve
PJV-8B	1/2 inch Barbed Polypropylene Micro Ball Valve
PJV-12B	1/2 inch Barbed Polypropylene Micro Ball Valve

## PBV6 SERIES



The PBV6 Series is a Three-way two directional 3/8 inch Flow Panel Mount Ball Valve made of NSF approved PVC, Polypropylene, or Nylon. Designed to promote multiple configurations. Used for air, water, beverage, and chemical application.

SKU	Definition
PBV6-4F	3/8 Flow 1/4 FNPT PVC Ball Valve
PBV6-6F	3/8 Flow 3/8 FNPT PVC Ball Valve
PBV6-8F	3/8 Flow 1/2 FNPT PVC Ball Valve
PBV6-2M	3/8 Flow 1/8 MNPT PVC Ball Valve
PBV6-4M	3/8 Flow 1/4 MNPT PVC Ball Valve
PBV6-6M	3/8 Flow 3/8 MNPT PVC Ball Valve
PBV6-8M	3/8 Flow 1/2 MNPT PVC Ball Valve
PBV6-2B	3/8 Flow 1/8 Barb PVC Ball Valve
PBV6-4B	3/8 Flow 1/4 Barb PVC Ball Valve
PBV6-6B	3/8 Flow 3/8 Barb PVC Ball Valve
PBV6-8B	3/8 Flow 1/2 Barb PVC Ball Valve
PBV6-4PI	3/8 Flow 1/4 Push-to-Connect PVC Ball Valve
PBV6-6PI	3/8 Flow 3/8 Push-to-Connect PVC Ball Valve
PBV6-8PI	3/8 Flow 1/2 Push-to-Connect PVC Ball Valve
PBV6-4C	3/8 Flow 1/4 Compression PVC Ball Valve

## PBV5 SERIES



The PBV5 Series is a Two-way Ball Valve available with an operating pressure of 125 psi, 140° F, with .312 thru hole in multiple configurations of Barb, Push-in, or Thread. PVC and White Filled Polypropylene materials which are used for chemical resistance applications and are NSF Standard 42 Certified. MakroBlend® (*a Polycarbonate and PBT blend*) is an NSF Standard 51 certified material. An optional Panel Mount is available for a .750 thru hole and comes with a Brass knurled nut or Electroless Nickel-plated Hex mount nut. The Flag Handle comes standard with an optional round Knurled Handle. The maximum panel is .125

SKU	Description
PBV5-3W-4C	5/16 Flow 1/4 Compression PVC 3-Way Ball Valve
PBV5-3W-4F	5/16 Flow 1/4 FNPT PVC 3-Way Ball Valve
PBV5-3W-4F-PVCE	5/16 Flow 1/4 FNPT PVC EPDM 3-Way Ball Valve
PBV5-3W-4F-PVCV	5/16 Flow 1/4 FNPT PVC EPDM 3-Way Ball Valve
PBV5-3W-4M	5/16 Flow 1/4 MNPT PVC 3-Way Ball Valve
PBV5-3W-4PE-PM JG	5/16 Flow 1/4 Barb EPDM PM JG 3-Way Ball Valve
PBV5-3W-5B	5/16 Flow 5/16 Barb PVC 3-Way Ball Valve
PBV5-3W-4PI	5/16 Flow 1/4 Push-to-Connect PVC 3-Way Ball Valve
PBV5-3W-5F	5/16 Flow 5/16 FNPT PVC 3-Way Ball Valve
PBV5-3W-5M	5/16 Flow 5/16 MNPT PVC 3-Way Ball Valve
PBV5-3W-5PI	5/16 Flow 5/16 Push-to-Connect PVC 3-Way Ball Valve
PBV5-3W-6B	5/16 Flow 3/8 Barb PVC 3-Way Ball Valve
PBV5-3W-6F	5/16 Flow 3/8 FNPT PVC 3-Way Ball Valve
PBV5-3W-6M	5/16 Flow 3/8 MNPT PVC 3-Way Ball Valve
PBV5-3W-6PI	5/16 Flow 3/8 Push-to-Connect PVC 3-Way Ball Valve
PBV5-3W-8B	5/16 Flow 1/2 Barb PVC 3-Way Ball Valve
PBV5-3W-8F	5/16 Flow 1/2 FNPT PVC 3-Way Ball Valve
PBV5-3W-8M	5/16 Flow 1/2 MNPT PVC 3-Way Ball Valve
PBV5-3W-4B	5/16 Flow 1/4 Barb PVC 3-Way Ball Valve
PBV5-3W-2M	5/16 Flow 1/8 MNPT PVC 3-Way Ball Valve
PBV5-3W-2F	5/16 Flow 1/8 FNPT PVC 3-Way Ball Valve
PBV5-3W-2C	5/16 Flow 1/8 Compression PVC 3-Way Ball Valve
PBV5-3W-2B	5/16 Flow 1/8 Barb PVC 3-Way Ball Valve

LRH SERIES



The LRH Series Two-Way Ball Valves are made from PVC or ABS plastic with a 7 CV Flow and 125 psi with Buna seals standard. (one-way valve is optional)

SKU	Description
LRH-MGH8M	3/4 inch Male GHT by 1/2 inch NPT Ball Valve
LRH-MGMG	3/4 inch MGHT by Male GHT Ball Valve
LRH-8F8M	1/2 inch Female NPT by 1/2 inch Male NPT Ball Valve
LRH-12F12M	3/4 inch Female NPT by 3/4 inch Male NPT Ball Valve
LRH-8SMG	1/2 inch Socket by MGH Ball Valve
LRH-12SMG	3/4 inch Socket by MGH Ball Valve

LGH SERIES



The LGH Series is a Two-way Ball Valve. It has an operating pressure of 150 psi, and a working temperature of up to 140° F. Available in variations of Female and Male GHT, and Female and Male NPT with combinations of these sizes: 3/8 inch, 1/2 inch, and 3/4 inch; all with a .625 through hole. Materials available are Gray PVC and Polypropylene. The PVC and Polypropylene materials are used for chemical resistance applications and are NSF Standard 61 Certified. PVC with EPDM seals are standard. Other seal options are Buna-N and Viton®. Panel Mounts are not available.

SKU	Description
LGH-34F12M	3/4 FNPT by 1/2 MNPT Ball Valve
LGH-34F34MGH	3/4 FNPT by 3/4 MGH Ball Valve
LGH-34F6B	3/4 FNPT by 3/8 Barb Ball Valve
LGH-34F-B	3/4 FNPT by 3/4 FNPT PVC/Buna Ball Valve
LGH-34FF	3/4 FNPT by 3/4 FNPT Ball Valve
LGH-34FGH34F	3/4 FGH by 3/4 FNPT Ball Valve
LGH-34FGH34M	3/4 FGH by 3/4 MNPT Ball Valve
LGH-34FGH6B	3/4 FGH by 3/8 Barb Ball Valve
LGH-34FGH8M	3/4 FGH by 1/2 MNPT Ball Valve
LGH-34FGHMGH	3/4 FGH by 3/4 MGH Ball Valve
LGH-34FM	3/4 FNPT by 3/4 MNPT Ball Valve

SKU	Description
LGH-34FM-E	3/4 FNPT to 3/4 MNPT PVC/EPDM Ball Valve
LGH-34FM-PP-E	3/4 FNPT to 3/4 MNPT Bk Polypropylene/EPDM Ball Valve

HV PBT HAND VALVES



These Hand Valves are made with a PBT body, nickel-plated threads, and Buna-N O-rings. The valves can stop or reduce flow. The working pressure is 150 psi and the temperature range is 32° F to 140° F. They can be used for compressed air or inert gases.

SKU	DESCRIPTION
HV-2M4P	1/8 MNPT by 1/4 PBT
HV-2M5P	1/8 MNPT by 5/16 PBT
HV-4M4P	1/4 MNPT by 1/4 PBT
HV-4M5P	1/4 MNPT by 5/16 PBT
HV-6M4P	3/8 MNPT by 1/4 PBT
HV-6M5P	3/8 MNPT by 5/16 PBT
HV-2M	1/8 MNPT
HV-4M2M	1/4 MNPT by 1/8 MNPT
HV-4M	1/4 MNPT
HV-4M6M	1/4 MNPT by 3/8 MNPT
HV-6M	3/8 MNPT
HV-8M	1/2 MNPT
HV-8M6M	1/2 MNPT by 3/8 MNPT
HV-4P	1/4 PBT
HV-5P	5/16 PBT
HV-5P4P	5/16 PBT by 1/4 PBT

EBVA SERIES



The EBV Series One-Way single-direction Flow Ball Valve is made of PVC with standard Buna seals. Maximum pressure 125 psi and 140 degrees F and a thru-hole of .437 used for air, water, gas, oxygen, and refrigeration applications. (not for vacuum)

SKU		Description
EBVA-4B	1/4 Barb Ball Valve	
EBVA-6B	3/8 Barb Ball Valve	
EBVA-8B	1/2 Barb Ball Valve	
EBVA-4F	1/4 MNPT Ball Valve	
EBVA-6F	3/8 FNPT Ball Valve	
EBVA-8F	1/2 FNPT Ball Valve	
EBVA-4F-4B	1/4 FNPT by 1/4 Barb Ball Valve	
EBVA-6F-6B	3/8 FNPT by 3/8 Barb Ball Valve	
EBVA-8F-8B	1/2 FNPT by 1/2 Barb Ball Valve	
EBVA-4M	1/4 MNPT Ball Valve	
EBVA-6M	3/8 MNPT Ball Valve	
EBVA-8M	1/2 MNPT Ball Valve	
EBVA-4M-4B	1/4 MNPT by 1/4 Barb Ball Valve	
EBVA-6M-6B	3/8 MNPT by 3/8 Barb Ball Valve	
EBVA-8M-8B	1/2 MNPT by 1/2 Barb Ball Valve	
EBVA-4P-4B	1/4 Push-to-Connect by 1/4 Barb Ball Valve	
EBVA-6P-6B	3/8 Push-to-Connect by 3/8 Barb Ball Valve	
EBVA-8P-8B	1/2 Push-to-Connect by 1/2 Barb Ball Valve	
EBVA-4C-4B	1/4 Compression by 1/4 Barb Ball Valve	
EBVA-6C-6B	3/8 Compression by 3/8 Barb Ball Valve	
EBVA-8C-8B	1/2 Compression by 1/2 Barb Ball Valve	

EBV SERIES



The EBV Series One-Way single-direction Flow 90-degree Ball Valve is made of PVC with standard Buna seals. Maximum pressure 125 psi and 140 degrees F and a thru-hole of .437 used for air, water, gas, oxygen, and refrigeration applications. (not for vacuum)

SKU		Description
EBV-4B	1/4 Barb Ball Valve	
EBV-6B	3/8 Barb Ball Valve	
EBV-8B	1/2 Barb Ball Valve	
EBV-4F	1/4 FNPT Ball Valve	
EBV-6F	3/8 FNPT Ball Valve	
EBV-8F	1/2 FNPT Ball Valve	
EBV-4F-4B	1/4 FNPT by 1/4 Barb Ball Valve	
EBV-6F-6B	3/8 FNPT by 3/8 Barb Ball Valve	
EBV-8F-8B	1/2 FNPT by 1/2 Barb Ball Valve	
EBV-4M	1/4 MNPT Ball Valve	
EBV-6M	3/8 MNPT Ball Valve	
EBV-8M	1/2 MNPT Ball Valve	
EBV-4M-4B	1/4 MNPT by 1/4 Barb Ball Valve	
EBV-6M-6B	3/8 MNPT by 3/8 Barb Ball Valve	
EBV-8M-8B	1/2 MNPT by 1/2 Barb Ball Valve	
EBV-4P-4B	1/4 Push-to-Connect by 1/4 Barb Ball Valve	
EBV-6P-6B	3/8 Push-to-Connect by 3/8 Barb Ball Valve	
EBV-8P-8B	1/2 Push-to-Connect by 1/2 Barb Ball Valve	
EBV-4C-4B	1/4 Comp by 1/4 Barb Ball Valve	
EBV-6C-6B	3/8 Comp by 3/8 Barb Ball Valve	
EBV-8C-8B	1/2 Comp by 1/2 Barb Ball Valve	

BRS SERIES



The BRS Series compact PVC quarter-turn shut-off Ball Valves with PTFE sets and EPDM O-ring seals are used in industrial and plumbing applications. Available in schedule 80 (gray) and schedule 40 (white). Sizes range from ½ inch to 2 inches.

SKU		Description
BRS-12F	1/2 inch Female PVC Ball Valve	
BRS-34F	3/4 inch Female PVC Ball Valve	
BRS-1F	1 inch Female PVC Ball Valve	
BRS-114F	1-1/4 inch Female PVC Ball Valve	
BRS-112F	1-1/2 inch Female PVC Ball Valve	
BRS-2F	2 inch Female PVC Ball Valve	

2-WAY SERIES



This Ball Valve is made of white Polypropylene with EPDM O-rings. It is a 1/4 turn from open to closed. The maximum pressure is 150 psi and the temperature range is 33 F to 140 F. To be used with potable water, it is not suitable for inert gases or air. One end is male NPT threaded and the other end is a socket fitting.

## **INDEX**

### **2**

2-Way Series 9

### **B**

BRS Series 9

### **E**

EBV Series 8

EBVA Series 7

### **H**

HV PBT HAND VALVES 6

### **L**

LGH Series 5

LRH Series 5

### **P**

PBV5 Series 4

PBV6 Series 3

PJV Series 3

PKV Series 2