### **AIR**



# PSSV SERIES | SELF-CLOSING CHECK VALVES

Our **PSSV Series, Self-sealing Check Valves,** are made from either Polycarbonate or Polypropylene with Barb connector sizes of 3/16 inch or 5/16 inch. Product is made in a class 8 clean-room. The seal is a retractable silicone disk that prevents backflow in a number of air and liquid applications making it an ideal option for the Medical Industry. Open pressure is approximately .20 PSI

SKU	Description
PSSV-3B-PP	3/16 inch by 3/16 inch Polypropylene Barbed Self-Sealing Check Valve
PSSV-3B-PC	3/16 inch by 3/16 inch Polycarbonate Barbed Self-Sealing Check Valve
PSSV-5B-PP	5/16 inch by 5/16 inch Polypropylene Barbed Self-Sealing Check Valve
PSSV-5B-PC	5/16 inch by 5/16 inch Polycarbonate Barbed Self-Sealing Check Valve
PSSV-5B3B-PP	5/16 inch by 3/16 inch Polypropylene Barbed Self-Sealing Check Valve
PSSV-5B3B-PC	5/16 inch by 3/16 inch Polycarbonate Barbed Self-Sealing Check Valve

#### **PBV6 SERIES**



The PBV6 Series is a Three-way two directional 3/8 inch Flow Panel Mount Ball Valve made of NSF approved PVC, Polypropylene, or Nylon. Designed to promote multiple configurations. Used for air, water, beverage, and chemical application.

SKU		Definition
PBV6-4F	3/8 Flow 1/4 FNPT PVC Ball Valve	
PBV6-6F	3/8 Flow 3/8 FNPT PVC Ball Valve	
PBV6-8F	3/8 Flow 1/2 FNPT PVC Ball Valve	
PBV6-2M	3/8 Flow 1/8 MNPT PVC Ball Valve	<u> </u>
PBV6-4M	3/8 Flow 1/4 MNPT PVC Ball Valve	<u> </u>
PBV6-6M	3/8 Flow 3/8 MNPT PVC Ball Valve	<u>۽</u>
PBV6-8M	3/8 Flow 1/2 MNPT PVC Ball Valve	<u>۽</u>
PBV6-2B	3/8 Flow 1/8 Barb PVC Ball Valve	
PBV6-4B	3/8 Flow 1/4 Barb PVC Ball Valve	
PBV6-6B	3/8 Flow 3/8 Barb PVC Ball Valve	
PBV6-8B	3/8 Flow 1/2 Barb PVC Ball Valve	
PBV6-4PI	3/8 Flow 1/4 Push-to-Connect PV	C Ball Valve

SKU	Definition
PBV6-6PI	3/8 Flow 3/8 Push-to-Connect PVC Ball Valve
PBV6-8PI	3/8 Flow 1/2 Push-to-Connect PVC Ball Valve
PBV6-4C	3/8 Flow 1/4 Compression PVC Ball Valve



### PBV6 (3-WAY) SERIES

The PBV6 Series is a Three-way two directional 3/8 inch Flow Panel Mount Ball Valve made of NSF approved PVC, Polypropylene, or Nylon. Designed to promote multiple configurations. Used for air, water, beverage, and chemical application.

SKU		Definition
PBV6-4F	3/8 Flow 1/4 FNPT PVC Ball Valve	
PBV6-6F	3/8 Flow 3/8 FNPT PVC Ball Valve	
PBV6-8F	3/8 Flow 1/2 FNPT PVC Ball Valve	
PBV6-2M	3/8 Flow 1/8 MNPT PVC Ball Valve	è
PBV6-4M	3/8 Flow 1/4 MNPT PVC Ball Valve	è
PBV6-6M	3/8 Flow 3/8 MNPT PVC Ball Valve	غ
PBV6-8M	3/8 Flow 1/2 MNPT PVC Ball Valve	غ
PBV6-2B	3/8 Flow 1/8 Barb PVC Ball Valve	
PBV6-4B	3/8 Flow 1/4 Barb PVC Ball Valve	
PBV6-6B	3/8 Flow 3/8 Barb PVC Ball Valve	
PBV6-8B	3/8 Flow 1/2 Barb PVC Ball Valve	
PBV6-4PI	3/8 Flow 1/4 Push-to-Connect PV	C Ball Valve
PBV6-6PI	3/8 Flow 3/8 Push-to-Connect PV	C Ball Valve
PBV6-8PI	3/8 Flow 1/2 Push-to-Connect PV	C Ball Valve
PBV6-4C	3/8 Flow 1/4 Compression PVC Ba	II Valve

### LD SERIES | LAB DISCONNECTS



Pneuline Supply, Inc. manufactures these low pressure Lab Disconnects made from either Polyethylene or Polypropylene which are used in laboratories for vacuum application, low pressure lines, water lines, and inert gases. They connect various tubing sizes from 1/8 inch, 7/32 inch, 1/4 inch, and .170 ID tube lines. They can be purchased with a Viton® or EPDM disc Check Valve, or with a porous Polyethylene filter. A unique pick-up tube line assembly for use in drawing air or water from containers is also available.

SKU	Description
LD-F-LDPE	Female LDPE Lab Disconnect
LD-F-PP	Female Polypropylene Lab Disconnect
LD-F-LDPE	Male/Female LDPE Complete Lab Disconnect
LD-M-LDPE	Male LDPE Lab Disconnect
LD-M-NB-PP	Male No-Barb Polypropylene Lab Disconnect

#### **EBVA SERIES**



The EBV Series One-Way single direction Flow Ball Valve is made of PVC with standard Buna seals. Maximum pressure 125 psi and 140 degrees F and a thru hole of .437 used for air, water, gas, oxygen, and refrigeration applications. (not for vacuum)

SKU	Description
EBVA-4B	1/4 Barb Ball Valve
EBVA-6B	3/8 Barb Ball Valve
EBVA-8B	1/2 Barb Ball Valve
EBVA-4F	1/4 MNPT Ball Valve
EBVA-6F	3/8 FNPT Ball Valve
EBVA-8F	1/2 FNPT Ball Valve
EBVA-4F-4B	1/4 FNPT by 1/4 Barb Ball Valve
EBVA-6F-6B	3/8 FNPT by 3/8 Barb Ball Valve
EBVA-8F-8B	1/2 FNPT by 1/2 Barb Ball Valve
EBVA-4M	1/4 MNPT Ball Valve
EBVA-6M	3/8 MNPT Ball Valve
EBVA-8M	1/2 MNPT Ball Valve
EBVA-4M-4B	1/4 MNPT by 1/4 Barb Ball Valve
EBVA-6M-6B	3/8 MNPT by 3/8 Barb Ball Valve
EBVA-8M-8B	1/2 MNPT by 1/2 Barb Ball Valve
EBVA-4P-4B	1/4 Push-to-Connect by 1/4 Barb Ball Valve
EBVA-6P-6B	3/8 Push-to-Connect by 3/8 Barb Ball Valve

SKU	Description
EBVA-8P-8B	1/2 Push-to-Connect by 1/2 Barb Ball Valve
EBVA-4C-4B	1/4 Compression by 1/4 Barb Ball Valve
EBVA-6C-6B	3/8 Compression by 3/8 Barb Ball Valve
EBVA-8C-8B	1/2 Compression by 1/2 Barb Ball Valve

#### **EBV SERIES**



The EBV Series One-Way single direction Flow 90 degree Ball Valve is made of PVC with standard Buna seals. Maximum pressure 125 psi and 140 degrees F and a thru hole of .437 used for air, water, gas, oxygen, and refrigeration applications. (not for vacuum)

SKU	Description
EBV-4B	1/4 Barb Ball Valve
EBV-6B	3/8 Barb Ball Valve
EBV-8B	1/2 Barb Ball Valve
EBV-4F	1/4 FNPT Ball Valve
EBV-6F	3/8 FNPT Ball Valve
EBV-8F	1/2 FNPT Ball Valve
EBV-4F-4B	1/4 FNPT by 1/4 Barb Ball Valve
EBV-6F-6B	3/8 FNPT by 3/8 Barb Ball Valve
EBV-8F-8B	1/2 FNPT by 1/2 Barb Ball Valve
EBV-4M	1/4 MNPT Ball Valve
EBV-6M	3/8 MNPT Ball Valve
EBV-8M	1/2 MNPT Ball Valve
EBV-4M-4B	1/4 MNPT by 1/4 Barb Ball Valve
EBV-6M-6B	3/8 MNPT by 3/8 Barb Ball Valve
EBV-8M-8B	1/2 MNPT by 1/2 Barb Ball Valve
EBV-4P-4B	1/4 Push-to-Connect by 1/4 Barb Ball Valve
EBV-6P-6B	3/8 Push-to-Connect by 3/8 Barb Ball Valve
EBV-8P-8B	1/2 Push-to-Connect by 1/2 Barb Ball Valve
EBV-4C-4B	1/4 Comp by 1/4 Barb Ball Valve
EBV-6C-6B	3/8 Comp by 3/8 Barb Ball Valve
EBV-8C-8B	1/2 Comp by 1/2 Barb Ball Valve



#### 2-WAY SERIES

This Ball Valve is made of white polypropylene with EPDM O-rings. It is a 1/4 turn from open to closed. The maximum pressure is 150 psi and the temperature range is 33 F to 140 F. To be used with potable water, it is not suitable for inert gases or air. One end is male NPT threaded and the other end is a socket fitting.

### **INDEX**

2	
2-Way Series 5	
E	
EBV Series 4	
EBVA Series 3	
L	
LD Series   Lab Disconnects 3	
P	
PBV6 (3-Way) Series 2	
PBV6 Series 1	
PSSV Series   Self-Closing Check Valves	1