

FDA APPROVED

SPE - PUSH-TO-CONNECT ELBOW STEM CONNECTOR



Push-to-Connect Elbow to Stem Swivel connectors available in Acetal, Polypropylene, and Kynar® can be added to any push-in connector to create a 90 degree connection. Stem sizes range from 1/2 inch to 5/32 inch OD. Push-in sizes of 1/2 inch to 5/32 inch. Use with Polyethylene, Brass, or Copper tubing. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|---------|--------------------------------|
| SPE-3 | 3/16 Stem by 3/16 OD Elbow PBT |
| SPE-4 | 1/4 Stem by 1/4 OD Elbow PBT |
| SPE-4-6 | 1/4 Stem by 3/16 OD Elbow PBT |
| SPE-5 | 5/16 Stem by 5/16 OD Elbow PBT |
| SPE-532 | 5/32 Stem by 5/32 OD Elbow PBT |
| SPE-6 | 3/8 Stem by 3/8 OD Elbow PBT |
| SPE-6-3 | 3/8 Stem by 3/16 OD Elbow PBT |
| SPE-6-4 | 3/8 Stem by 1/4 OD Elbow PBT |
| SPE-6-5 | 3/8 Stem by 5/16 OD Elbow PBT |
| SPE-8 | 1/2 Stem by 1/2 OD Elbow PBT |

PT SERIES



Push-to-Connect Tee connectors available in Acetal, Polypropylene, and Kynar® used to join tubing of Polyethylene. Sizes range from 1/2 inch OD to 5/32 inch OD including reducing sizes. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | DESCRIPTION |
|----------|--|
| PT-3 | 3/16 OD Push-to-Connect Union Tee |
| PT-4 | 1/4 OD Push-to-Connect Union Tee |
| PT-532 | 5/32 OD Push-to-Connect Union Tee |
| PT-5 | 5/16 OD Push-to-Connect Union Tee |
| PT-6-4-6 | 3/8 OD by 1/4 OD Run by 3/8 OD Push-to-Connect Union Tee |
| PT-6-4 | 3/8 OD by 1/4 OD Reducing Push-to-Connect Union Tee |
| PT-6 | 3/8 OD Push-to-Connect Union Tee |
| PT-8-6 | 1/2 OD by 3/8 OD Reducing Push-to-Connect Union Tee |
| PT-8 | 1/2 OD Push-to-Connect Union Tee |

PSP SERIES



Push-to-Connect to Stem available in Acetal, Polypropylene (select sizes only), and Kynar® can be added to a push-in connector to reduce the tubing size of Polyethylene, Brass, or Copper tubing. Stem sizes range from 1/2 inch to 3/16 inch reducing to as small as 5/32 inch OD. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|-----------|--|
| PSP-3-532 | 3/16 Stem by 5/32 OD Push-to-Connect Reducer |
| PSP-5-3 | 5/16 Stem to 3/16 OD Push-to-Connect Reducer |
| PSP-5-4 | 5/16 Stem to 1/4 OD Push-to-Connect Reducer |
| PSP-6-3 | 3/8 Stem to 3/16 OD Push-to-Connect Reducer |
| PSP-6-4 | 3/8 Stem to 1/4 OD Push-to-Connect Reducer |
| PSP-6-5 | 3/8 Stem to 5/16 OD Push-to-Connect Reducer |
| PSP-8-4 | 1/2 Stem to 1/4 OD Push-to-Connect Reducer |
| PSP-8-5 | 1/2 Stem to 5/16 OD Push-to-Connect Reducer |
| PSP-8-6 | 1/2 Stem to 3/8 OD Push-to-Connect Reducer |



PSM THREAD TO MALE PIPE CONNECTOR
PUSH TO CONNECT

Stem connector to Male Pipe Thread Fittings can be added to a Female Pipe Thread port. The stem allows for adding a Push-to-Connect connector to create Tees, Elbows, Wyes, and Crosses. Can also be used to create Male to Male Pipe or Male to Female Pipe connections. These units allow the connection to Swivel. Acetal, Polypropylene, and Kynar® can be added to a Push-to-Connect connector to terminate in a barbed connection for use with Polyethylene, Vinyl, or braided Vinyl tubing. Stem sizes range from 1/2 inch to 5/32 inch with Pipe Threads ranging from 1/2 inch NPT to 1/8 inch NPT (See PMES, PMT and PMR Series for examples.). Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|--------------|--|
| PSM-2M3-GA | 1/8 MNPT by 3/16 OD Push-to-Connect Stem |
| PSM-2M4-GA | 1/8 MNPT by 1/4 OD Push-to-Connect Stem |
| PSM-2M532-GA | 1/8 MNPT by 5/32 OD Push-to-Connect Stem |
| PSM-2M5-GA | 1/8 MNPT by 5/16 OD Push-to-Connect Stem |
| PSM-4M4-GA | 1/4 MNPT by 1/4 OD Push-to-Connect Stem |
| PSM-4M532-GA | 1/4 MNPT by 5/32 OD Push-to-Connect Stem |
| PSM-4M5-GA | 1/4 MNPT by 5/16 OD Push-to-Connect Stem |
| PSM-4M6-GA | 1/4 MNPT by 3/8 OD Push-to-Connect Stem |
| PSM-4M8-GA | 1/4 MNPT by 1/2 OD Push-to-Connect Stem |
| PSM-6M4-GA | 3/8 MNPT by 1/4 OD Push-to-Connect Stem |
| PSM-6M5-GA | 3/8 MNPT by 5/16 OD Push-to-Connect Stem |
| PSM-6M6-GA | 3/8 MNPT by 3/8 OD Push-to-Connect Stem |



PSB SERIES

Stem connector to Barbed Fittings Acetal, Polypropylene, and Kynar® can be added to a Push-to-Connect connector to terminate in a barbed connection for use with Polyethylene, Vinyl, or braided Vinyl tubing. Stem sizes range from 1/2 inch to 1/4 inch reducing to a 1/4 inch Barbed Fitting. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|------------|--|
| PSB-4-GA | 1/4 inch Stem by 1/4 inch Barb Gray Acetal Push-in |
| PSB-4-K | 1/4 inch Stem by 1/4 inch Barb PVDF Push-in |
| PSB-4S3-GA | 1/4 inch Stem by 3/16 Barb Gray Acetal Push-in |
| PSB-4S4-K | 1/4 inch Stem by 1/4 inch Barb PVDF Push-in |
| PSB-4S5-GA | 1/4 inch Stem by 5/16 inch Barb Gray Acetal Push-in |
| PSB-4-WP | 1/4 inch Stem by 1/4 inch Barb White Polypropylene Push-in |
| PSB-5-GA | 5/16 inch Stem by 5/16 inch Barb Gray Acetal Push-in |
| PSB-5S3-GA | 5/16 inch Stem by 3/16 Barb Gray Acetal Push-in |
| PSB-5S4-GA | 5/16 inch Stem by 1/4 inch Barb Gray Acetal Push-in |
| PSB-5S6-GA | 5/16 inch Stem by 3/8 inch Barb Gray Acetal Push-in |
| PSB-6-GA | 3/8 inch Stem by 3/8 inch Barb Gray Acetal Push-in |
| PSB-6-K | 3/8 inch Stem by 3/8 inch Barb PVDF Push-in |
| PSB-6S4-GA | 3/8 inch Stem by 1/4 inch Barb Gray Acetal Push-in |
| PSB-6S4-K | 3/8 inch Stem by 1/4 inch Barb PVDF Push-in |
| PSB-6S5-GA | 3/8 inch Stem by 5/16 inch Barb Gray Acetal Push-in |
| PSB-6S8-GA | 3/8 inch Stem by 1/2 inch Barb Gray Acetal Push-in |
| PSB-6S8-WP | 3/8 inch Stem by 1/2 inch Barb White Polypropylene Push-in |
| PSB-6-WP | 3/8 inch Stem by 3/8 inch Barb White Polypropylene Push-in |
| PSB-8-GA | 1/2 inch Stem by 1/2 inch Barb Gray Acetal Push-in |
| PSB-8S6-GA | 1/2 inch Stem by 3/8 inch Barb Gray Acetal Push-in |
| PSB-8S6-WP | 1/2 inch Stem by 3/8 inch Barb White Polypropylene Push-in |
| PSB-8-WP | 1/2 inch Stem by 1/2 inch Barb White Polypropylene Push-in |

PMT SERIES



PMT Series Push-to-Connect Tee to Male NPT connectors available in Acetal and select sizes in Polypropylene, and Kynar®. Push-to-Connect sizes range from 5/32 inch to 1/2 inch and Threads ranging from 1/2 inch MNPT to 1/8 inch MNPT. This is a swivel tee configuration using the [PT Series](#) and the [PSM Series](#) fittings. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|--------------|---|
| PMT-2M3-GA | 1/8 inch Male NPT by 3/16 inch OD Gray Acetal Tee Push-in |
| PMT-2M3-WA | 1/8 inch Male NPT by 3/16 inch OD White Acetal Tee Push-in |
| PMT-2M4-GA | 1/8 inch Male NPT by 1/4 inch OD Gray Acetal Tee Push-in |
| PMT-2M4-K | 1/8 inch Male NPT by 1/4 inch OD PVDF Tee Push-in |
| PMT-2M4-WA | 1/8 inch Male NPT by 1/4 inch OD White Acetal Tee Push-in |
| PMT-2M532-GA | 1/8 inch Male NPT by 5/32 inch OD Gray Acetal Tee Push-in |
| PMT-2M532-WA | 1/8 inch Male NPT by 5/32 inch OD White Acetal Tee Push-in |
| PMT-2M5-GA | 1/8 inch Male NPT by 5/16 inch OD Gray Acetal Tee Push-in |
| PMT-2M5-WA | 1/8 inch Male NPT by 5/16 inch OD White Acetal Tee Push-in |
| PMT-2M6-GA | 1/8 inch Male NPT by 3/8 inch OD Gray Acetal Tee Push-in |
| PMT-2M6-K | 1/8 inch Male NPT by 3/8 inch OD PVDF Tee Push-in |
| PMT-2M6-WA | 1/8 inch Male NPT by 3/8 inch OD White Acetal Tee Push-in |
| PMT-4M4-GA | 1/4 inch Male NPT by 1/4 inch OD Gray Acetal Tee Push-in |
| PMT-4M4-K | 1/4 inch Male NPT by 1/4 inch OD PVDF Tee Push-in |
| PMT-4M4-WA | 1/4 inch Male NPT by 1/4 inch OD White Acetal Tee Push-in |
| PMT-4M532-GA | 1/4 inch Male NPT by 5/32 inch OD Gray Acetal Tee Push-in |
| PMT-4M532-WA | 1/4 inch Male NPT by 5/32 inch OD White Acetal Tee Push-in |
| PMT-4M5-GA | 1/4 inch Male NPT by 5/16 inch OD Gray Acetal Tee Push-in |
| PMT-4M5-WA | 1/4 inch Male NPT by 5/16 inch OD White Acetal Tee Push-in |
| PMT-4M6-GA | 1/4 inch Male NPT by 3/8 inch OD Gray Acetal Tee Push-in |
| PMT-4M6-K | 1/4 inch Male NPT by 3/8 inch OD PVDF Tee Push-in |
| PMT-4M6-PP | 1/4 inch Male NPT by 3/8 inch OD Polypropylene Tee Push-in |
| PMT-4M6-WA | 1/4 inch Male NPT by 3/8 inch OD White Acetal Tee Push-in |
| PMT-4M8-GA | 1/4 inch Male NPT by 1/2 inch OD Gray Acetal Tee Push-in |
| PMT-4M8-PP | 1/4 inch Male NPT by 1/2 inch OD Polypropylene Tee Push-in |
| PMT-4M8-WA | 1/4 inch Male NPT by 1/2 inch OD White Acetal Tee Push-in |
| PMT-6M5-GA | 3/8 inch Male NPT by 5/16 inch OD Gray Acetal Tee Push-in |
| PMT-6M5-PP | 3/8 inch Male NPT by 5/16 inch OD Polypropylene Tee Push-in |
| PMT-6M5-WA | 3/8 inch Male NPT by 5/16 inch OD White Acetal Tee Push-in |
| PMT-6M6-GA | 3/8 inch Male NPT by 3/8 inch OD Gray Acetal Tee Push-in |
| PMT-6M6-K | 3/8 inch Male NPT by 3/8 inch OD PVDF Tee Push-in |

| SKU | Description |
|------------|--|
| PMT-6M6-PP | 3/8 inch Male NPT by 3/8 inch OD Polypropylene Tee Push-in |
| PMT-6M6-WA | 3/8 inch Male NPT by 3/8 inch OD White Acetal Tee Push-in |
| PMT-6M8-GA | 3/8 inch Male NPT by 1/2 inch OD Gray Acetal Tee Push-in |
| PMT-6M8-WA | 3/8 inch Male NPT by 1/2 inch OD White Acetal Tee Push-in |
| PMT-8M8-GA | 1/2 inch Male NPT by 1/2 inch OD Gray Acetal Tee Push-in |
| PMT-8M8-PP | 1/2 inch Male NPT by 1/2 inch OD Polypropylene Tee Push-in |
| PMT-8M8-WA | 1/2 inch Male NPT by 1/2 inch OD White Acetal Tee Push-in |

PMR SERIES



PMR Series Male NPT to Push-to-Connect Swivel Tee connector configuration available in Acetal and select sizes in Polypropylene, and Kynar®. Push-to-Connect sizes range from 5/32 inch to 1/2 inch and Threads ranging from 1/2 inch MNPT to 1/8 inch MNPT. This is a swivel tee configuration using the [PT Series](#) and the [PSM Series](#) fittings. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|--------------|--|
| PMR-2M4-GA | 1/8 inch Male NPT by 1/4 inch Gray Acetal Male Run Tee Push-in |
| PMR-2M4-K | 1/8 inch Male NPT by 1/4 inch PVDF Male Run Tee Push-in |
| PMR-2M4-PP | 1/8 inch Male NPT by 1/4 inch Natural Polypropylene Male Run Tee Push-in |
| PMR-2M4-WA | 1/8 inch Male NPT by 1/4 inch White Acetal Male Run Tee Push-in |
| PMR-2M532-GA | 1/8 inch Male NPT by 5/32 inch Gray Acetal Male Run Tee Push-in |
| PMR-2M532-WA | 1/8 inch Male NPT by 5/32 inch White Acetal Male Run Tee Push-in |
| PMR-2M5-GA | 1/8 inch Male NPT by 5/16 inch Gray Acetal Male Run Tee Push-in |
| PMR-2M5-WA | 1/8 inch Male NPT by 5/16 inch White Acetal Male Run Tee Push-in |
| PMR-4M4-GA | 1/4 inch Male NPT by 1/4 inch Gray Acetal Male Run Tee Push-in |
| PMR-4M4-K | 1/4 inch Male NPT by 1/4 inch PVDF Male Run Tee Push-in |
| PMR-4M4-PP | 1/4 inch Male NPT by 1/4 inch Natural Polypropylene Male Run Tee Push-in |
| PMR-4M4-WA | 1/4 inch Male NPT by 1/4 inch White Acetal Male Run Tee Push-in |
| PMR-4M532-GA | 1/4 inch Male NPT by 5/32 inch Gray Acetal Male Run Tee Push-in |
| PMR-4M532-WA | 1/4 inch Male NPT by 5/32 inch White Acetal Male Run Tee Push-in |
| PMR-4M5-GA | 1/4 inch Male NPT by 5/16 inch Gray Acetal Male Run Tee Push-in |
| PMR-4M5-WA | 1/4 inch Male NPT by 5/16 inch White Acetal Male Run Tee Push-in |
| PMR-4M6-GA | 1/4 inch Male NPT by 3/8 inch Gray Acetal Male Run Tee Push-in |
| PMR-4M6-K | 1/4 inch Male NPT by 3/8 inch PVDF Male Run Tee Push-in |
| PMR-4M6-PP | 1/4 inch Male NPT by 3/8 inch Natural Polypropylene Male Run Tee Push-in |
| PMR-4M6-WA | 1/4 inch Male NPT by 3/8 inch White Acetal Male Run Tee Push-in |

| SKU | Description |
|------------|--|
| PMR-4M8-GA | 1/4 inch Male NPT by 1/2 inch Gray Acetal Male Run Tee Push-in |
| PMR-4M8-WA | 1/4 inch Male NPT by 1/2 inch White Acetal Male Run Tee Push-in |
| PMR-6M5-GA | 3/8 inch Male NPT by 5/16 inch Gray Acetal Male Run Tee Push-in |
| PMR-6M5-WA | 3/8 inch Male NPT by 5/16 inch White Acetal Male Run Tee Push-in |
| PMR-6M6-GA | 3/8 inch Male NPT by 3/8 inch Gray Acetal Male Run Tee Push-in |
| PMR-6M6-K | 3/8 inch Male NPT by 3/8 inch PVDF Male Run Tee Push-in |
| PMR-6M6-PP | 3/8 inch Male NPT by 3/8 inch Natural Polypropylene Male Run Tee Push-in |
| PMR-6M6-WA | 3/8 inch Male NPT by 3/8 inch White Acetal Male Run Tee Push-in |
| PMR-6M8-GA | 3/8 inch Male NPT by 1/2 inch Gray Acetal Male Run Tee Push-in |
| PMR-6M8-WA | 3/8 inch Male NPT by 1/2 inch White Acetal Male Run Tee Push-in |
| PMR-8M8-GA | 1/2 inch Male NPT by 1/2 inch Gray Acetal Male Run Tee Push-in |
| PMR-8M8-WA | 1/2 inch Male NPT by 1/2 inch White Acetal Male Run Tee Push-in |



PMES SERIES

PMES Series Push-to-Connect to Male NPT Swivel Elbow connectors available in Acetal and select sizes in Polypropylene, and Kynar®. Push-to-Connect sizes range from 5/32 inch to 1/2 inch and Threads ranging from 1/2 inch MNPT to 1/8 inch MNPT. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene. For non-swivel elbows see [PME Series](#).

| SKU | Description |
|------------|--|
| PMES-2M4 | 1/8 MNPT by 1/4 OD Swivel Elbow Push-to-Connect |
| PMES-2M532 | 1/8 MNPT by 5/32 OD Swivel Elbow Push-to-Connect |
| PMES-2M5 | 1/8 MNPT by 5/16 OD Swivel Elbow Push-to-Connect |
| PMES-2M6 | 1/8 MNPT by 3/8 OD Swivel Elbow Push-to-Connect |
| PMES-4M4 | 1/4 MNPT by 1/4 OD Swivel Elbow Push-to-Connect |
| PMES-4M532 | 1/4 MNPT by 5/32 OD Swivel Elbow Push-to-Connect |
| PMES-4M5 | 1/4 MNPT by 5/16 OD Swivel Elbow Push-to-Connect |
| PMES-4M6 | 1/4 MNPT by 3/8 OD Swivel Elbow Push-to-Connect |
| PMES-4M8 | 1/4 MNPT by 1/2 OD Swivel Elbow Push-to-Connect |
| PMES-6M4 | 3/8 MNPT by 1/4 OD Swivel Elbow Push-to-Connect |
| PMES-6M5 | 3/8 MNPT by 5/16 OD Swivel Elbow Push-to-Connect |
| PMES-6M6 | 3/8 MNPT by 3/8 OD Swivel Elbow Push-to-Connect |
| PMES-6M8 | 3/8 MNPT by 1/2 OD Swivel Elbow Push-to-Connect |
| PMES-8M8 | 1/2 MNPT by 1/2 OD Swivel Elbow Push-to-Connect |



PME THREADED PUSH-TO-CONNECT ELBOW

PM Series Male Thread to Push-to-Connect Elbow connectors available in Acetal and select sizes in Polypropylene, and Kynar®. Push-in sizes range from 1/4 inch to 3/8 inch and Threads ranging from 3/8inch MNPT to 1/8 inch MNPT. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|---------|---|
| PME-2M4 | 1/8 MNPT by 1/4 OD Push-to-Connect Elbow |
| PME-4M4 | 1/4 MNPT by 1/4 OD Push-to-Connect Elbow |
| PME-4M5 | 1/4 MNPT by 5/16 OD Push-to-Connect Elbow |
| PME-4M6 | 1/4 MNPT by 3/8 OD Push-to-Connect Elbow |
| PME-6M4 | 3/8 MNPT by 1/4 OD Push-to-Connect Elbow |
| PME-6M5 | 3/8 MNPT by 5/16 OD Push-to-Connect Elbow |
| PME-6M6 | 3/8 MNPT by 3/8 OD Push-to-Connect Elbow |
| PME-6M8 | 3/8 MNPT by 1/2 OD Push-to-Connect Elbow |



PM THREAD TO PUSH-TO-CONNECT STRAIGHT CONNECTOR

PM Series Straight Male Thread to Push-to-Connect connectors available in Acetal and select sizes in Polypropylene, and Kynar®. Push-in izes range from 5/32 inch to 5/8 inch and Threads ranging from 3/4 inch MNPT to 1/8 inch MNPT. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|-----------|--|
| PM-12M10 | 3/4 MNPT by 5/8 OD Straight Push-to-Connect |
| PM-2M3 | 1/8 MNPT by 3/16 OD Straight Push-to-Connect |
| PM-2M4 | 1/8 MNPT by 1/4 OD Straight Push-to-Connect |
| PM-2M532 | 1/8 MNPT by 5/32 OD Straight Push-to-Connect |
| PM-2M5 | 1/8 MNPT by 5/16 OD Straight Push-to-Connect |
| PM-2M6 | 1/8 MNPT by 3/8 OD Straight Push-to-Connect |
| PM-4BSPT6 | 1/4 BSPT by 3/8 OD Straight Push-to-Connect |
| PM-4M4 | 1/4 MNPT by 1/4 OD Straight Push-to-Connect |
| PM-4M532 | 1/4 MNPT by 5/32 OD Straight Push-to-Connect |
| PM-4M5 | 1/4 MNPT by 5/16 OD Straight Push-to-Connect |
| PM-4M6 | 1/4 MNPT by 3/8 OD Straight Push-to-Connect |

| SKU | Description |
|--------|--|
| PM-6M4 | 3/8 MNPT by 1/4 OD Straight Push-to-Connect |
| PM-6M5 | 3/8 MNPT by 5/16 OD Straight Push-to-Connect |
| PM-6M6 | 3/8 MNPT by 3/8 OD Straight Push-to-Connect |
| PM-6M8 | 3/8 MNPT by 1/2 OD Straight Push-to-Connect |
| PM-8M6 | 1/2 MNPT by 3/8 OD Straight Push-to-Connect |
| PM-8M8 | 1/2 MNPT by 1/2 OD Straight Push-to-Connect |



PF SERIES

Push-to-Connect to Female NPT Straight connectors available in Acetal, Polypropylene, and Kynar® used to join tubing of Polyethylene, Brass, or Copper. Push-to-Connect sizes range from 1/2 inch to 1/4 inch and Thread sizes ranging from 1/2 FNPT to 1/8 inch FNPT. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|--------|--|
| PF-2F4 | 1/8 FNPT by 1/4 OD Straight Push-to-Connect |
| PF-4F4 | 1/4 FNPT by 1/4 OD Straight Push-to-Connect |
| PF-4F5 | 1/4 FNPT by 5/16 OD Straight Push-to-Connect |
| PF-4F6 | 1/4 FNPT by 3/8 OD Straight Push-to-Connect |
| PF-6F5 | 3/8 FNPT by 5/16 OD Straight Push-to-Connect |
| PF-6F6 | 3/8 FNPT by 3/8 OD Straight Push-to-Connect |
| PF-6F8 | 3/8 FNPT by 1/2 OD Straight Push-to-Connect |

PEB SERIES



The PEB Series Stem connector to Elbow Barbed Fittings comes in Acetal, Polypropylene, and Kynar® which can be added to a Push-to-Connect connector to terminate in a barbed connection for use with Polyethylene, Vinyl, or braided Vinyl tubing. Stem sizes range from 1/2 inch to 1/4 inch reducing to a 1/4 inch Barbed Fitting. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|---------|---------------------------------|
| PEB-4 | 1/4 OD Stem by 1/4 Barb Elbow |
| PEB-4S5 | 1/4 OD Stem by 5/16 Barb Elbow |
| PEB-5 | 5/16 OD Stem by 5/16 Barb Elbow |
| PEB-5S4 | 5/16 OD Stem by 1/4 Barb Elbow |
| PEB-5S5 | 5/16 OD Stem by 5/16 Barb Elbow |
| PEB-6 | 3/8 OD Stem by 3/8 Barb Elbow |
| PEB-6S4 | 3/8 OD Stem by 1/4 Barb Elbow |
| PEB-6S5 | 3/8 OD Stem by 5/16 Barb Elbow |

PE SERIES



Push-to-Connect Elbow connectors available in Acetal, Polypropylene, and Kynar® used to join tubing of Polyethylene, Brass, or Copper. Sizes range from 5/32 inch OD to 1/2 inch OD including reducing sizes. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|----------|--|
| PE-3 | 3/16 OD Push-to-Connect Elbow |
| PE-4 | 1/4 OD Push-to-Connect Elbow |
| PE-532 | 5/32 OD Push-to-Connect Elbow |
| PE-5-3 | 5/16 OD by 3/16 OD Push-to-Connect Elbow |
| PE-5-4 | 5/16 OD by 1/4 OD Push-to-Connect Elbow |
| PE-5-532 | 5/16 OD by 5/32 OD Push-to-Connect Elbow |
| PE-5 | 5/16 OD Push-to-Connect Elbow |
| PE-6-3 | 3/8 OD by 3/16 OD Push-to-Connect Elbow |
| PE-6-4 | 3/8 OD by 1/4 OD Push-to-Connect Elbow |
| PE-6-5 | 3/8 OD by 5/16 OD Push-to-Connect Elbow |
| PE-6 | 3/8 OD OD Push-to-Connect Elbow PP PVDF |
| PE-8-6 | 1/2 OD by 3/8 OD Push-to-Connect Elbow |



PC SERIES

Push-to-Connect Straight Fittings connectors available in Acetal, Polypropylene, and Kynar® used to join tubing of Polyethylene, Brass, or Copper. Sizes range from 5/32 inch OD to 1/2 inch OD including reducing sizes. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | | Description |
|----------|--------------------------------------|-------------|
| PC-3 | 3/16 OD Equal Connector | |
| PC-4 | 1/4 OD Equal Connector | |
| PC-5 | 5/16 OD Equal Connector | |
| PC-532 | 5/32 OD Equal Connector | |
| PC-6 | 3/8 OD Equal Connector | |
| PC-8 | 1/2 OD Equal Connector | |
| PC-4-3 | 1/4 OD by 3/16 OD Reducer Connector | |
| PC-5-532 | 5/16 OD by 5/32 OD Reducer Connector | |
| PC-5-3 | 5/16 OD by 3/16 OD Reducer Connector | |
| PC-5-4 | 5/16 OD by 1/4 OD Reducer Connector | |
| PC-6-3 | 3/8 OD by 3/16 OD Reducer Connector | |
| PC-6-4 | 3/8 OD by 1/4 OD Reducer Connector | |
| PC-6-5 | 3/8 OD by 5/16 OD Reducer Connector | |
| PC-8-5 | 1/2 OD by 5/16 OD Reducer Connector | |



PB SERIES

Push-to-Connect Panel Mount connectors available in Acetal, Polypropylene, and Kynar® used to join tubing of Polyethylene, Brass, or Copper. Sizes range from 5/32 inch OD to 1/2 inch OD including reducing sizes. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

| SKU | Description |
|--------|---|
| PB-3 | 3/16 OD Push-to-Connect Bulkhead |
| PB-4 | 1/4 OD Push-to-Connect Bulkhead |
| PB-532 | 5/32 OD Push-to-Connect Bulkhead |
| PB-5 | 5/16 OD Push-to-Connect Bulkhead |
| PB-6-4 | 3/8 OD by 1/4 OD Push-to-Connect Bulkhead |
| PB-6 | 3/8 OD Push-to-Connect Bulkhead |
| PB-8-4 | 1/2 OD by 1/4 OD Push-to-Connect Bulkhead |



PACX SERIES

Push-to-Connect Cross connectors available in Acetal used to join tubing of Polyethylene, Brass, or Copper. Sizes range from 3/8 inch OD size only. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. Also available with double O-ring EPDM seals. For other options see our PUCX Series Push-ins.

| SKU | Description |
|----------|----------------------------------|
| PACX-6-A | 3/8 inch OD Cross made of Acetal |

CT SERIES




The CT Series Three port Compression Fittings are for 1/8 inch to 7/8 inch tubing connection without kinking attached tubing. Available in NSF approved Glass-Filled White Polypropylene, FDA and NSF approved Acetal (POM) for use with hot water applications, FDA and NSF approved Nylon, and UV resistant FDA and NSF rated PVDF. Provided with Poly gripper (except for 1/8 inch units) for us up to 220 psi. Available in a select number of reducing sizes.

| SKU | Description |
|----------------|---|
| CT-12-AC-PG | 1/2 inch OD Tee Connector Acetal Compression with Poly Gripper |
| CT-12-GFPP-PG | 1/2 inch OD Tee Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-12-NN-PG | 1/2 inch OD Tee Connector Natural Nylon Compression with Poly Gripper |
| CT-12-PVDF-PG | 1/2 inch OD Tee Connector PVDF Compression with Poly Gripper |
| CT-14-AC-PG | 1/4 inch OD Tee Connector Acetal Compression with Poly Gripper |
| CT-14-GFPP-PG | 1/4 inch OD Tee Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-14-K-PG | 1/4 inch OD Tee Connector PVDF Compression with Poly Gripper |
| CT-14-NN-PG | 1/4 inch OD Tee Connector Natural Nylon Compression with Poly Gripper |
| CT-18-AC-PG | 1/8 inch OD Tee Connector Acetal Compression with Poly Gripper |
| CT-18-GFPP-PG | 1/8 inch OD Tee Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-18-NN-PG | 1/8 inch OD Tee Connector Natural Nylon Compression with Poly Gripper |
| CT-18-PVDF-PG | 1/8 inch OD Tee Connector PVDF Compression with Poly Gripper |
| CT-34-AC-PG | 3/4 inch OD Tee Connector Acetal Compression with Poly Gripper |
| CT-34-GFPP-PG | 3/4 inch OD Tee Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-34-NN-PG | 3/4 inch OD Tee Connector Natural Nylon Compression with Poly Gripper |
| CT-34-PVDF-PG | 3/4 inch OD Tee Connector PVDF Compression with Poly Gripper |
| CT-38-AC-PG | 3/8 inch OD Tee Connector Acetal Compression with Poly Gripper |
| CT-38-GFPP-PG | 3/8 inch OD Tee Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-38-K | 3/8 inch OD Tee Connector PVDF Compression |
| CT-38-K-PG | 3/8 inch OD Tee Connector PVDF Compression with Poly Gripper |
| CT-38-NN-PG | 3/8 inch OD Tee Connector Natural Nylon Compression with Poly Gripper |
| CT-516-AC-PG | 5/16 inch OD Tee Connector Acetal Compression with Poly Gripper |
| CT-516-GFPP-PG | 5/16 inch OD Tee Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-516-NN-PG | 5/16 inch OD Tee Connector Natural Nylon Compression with Poly Gripper |
| CT-516-PVDF-PG | 5/16 inch OD Tee Connector PVDF Compression with Poly Gripper |
| CT-58-AC-PG | 5/8 inch OD Tee Connector Acetal Compression with Poly Gripper |

| SKU | Description |
|-------------------|--|
| CT-58-GFPP-PG | 5/8 inch OD Tee Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-58-NN-PG | 5/8 inch OD Tee Connector Natural Nylon Compression with Poly Gripper |
| CT-58-PVDF-PG | 5/8 inch OD Tee Connector PVDF Compression with Poly Gripper |
| CT-5838-AC-PG | 5/8 inch OD by 3/8 inch OD Reducing Tee Acetal Compression with Poly Gripper |
| CT-5838-GFPP-PG | 5/8 inch OD by 3/8 inch OD Reducing Tee Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-5838-K-PG | 5/8 inch OD by 3/8 inch OD Reducing Tee PVDF Compression with Poly Gripper |
| CT-5838-NN-PG | 5/8 inch OD by 3/8 inch OD Reducing Tee Natural Nylon Compression with Poly Gripper |
| CT-78-AC-PG | 7/8 inch OD Tee Connector Acetal Compression with Poly Gripper |
| CT-78-GFPP-PG | 7/8 inch OD Tee Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-78-NN-PG | 7/8 inch OD Tee Connector Natural Nylon Compression with Poly Gripper |
| CT-78-PVDF-PG | 7/8 inch OD Tee Connector PVDF Compression with Poly Gripper |
| CT-7858-AC-PG | 7/8 inch OD by 3/8 inch OD Reducing Tee Acetal Compression with Poly Gripper |
| CT-7858-GFPP-PG | 7/8 inch OD by 3/8 inch OD Reducing Tee Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-7858-NN-PG | 7/8 inch OD by 3/8 inch OD Reducing Tee Natural Nylon Compression with Poly Gripper |
| CT-7858-PVDF-PG | 7/8 inch OD by 3/8 inch OD Reducing Tee PVDF Compression with Poly Gripper |
| CT-785858-AC-PG | 7/8 inch OD by 5/8 inch by 5/8 inch OD Reducing Tee Acetal Compression with Poly Gripper |
| CT-785858-GFPP-PG | 7/8 inch OD by 5/8 inch by 5/8 inch OD Reducing Tee Glass-Filled Polypropylene Compression with Poly Gripper |
| CT-785858-NN-PG | 7/8 inch OD by 5/8 inch by 5/8 inch OD Reducing Tee Natural Nylon Compression with Poly Gripper |
| CT-785858-PVDF-PG | 7/8 inch OD by 5/8 inch by 5/8 inch OD Reducing Tee PVDF Compression with Poly Gripper |

CMR SERIES



The CMR Series Male Thread Run with a compression connection on the branch. Male pipe threads are 1/8 inch to 3/4 inch. Compression Branch allows tubing connections of 1/4 inch to 7/8 inch without kinking attached tubing. Available in NSF approved Glass-Filled White Polypropylene, FDA and NSF approved Acetal (POM) for use with hot water applications, FDA and NSF approved Nylon, and UV resistant FDA and NSF rated PVDF. Provided with Poly gripper (except for 1/8 inch units) for use up to 220 psi.

| SKU | Description |
|-------------------|---|
| CMR-1212-AC-PG | 1/2 inch Male NPT 1/2 inch OD Run Acetal with Poly Gripper |
| CMR-1212-GFPP-PG | 1/2 inch Male NPT 1/2 inch OD Run Glass Filled Polypropylene with Poly Gripper |
| CMR-1212-NPP-PG | 1/2 inch Male NPT 1/2 inch OD Run Natural Polypropylene with Poly Gripper |
| CMR-1212-PG | 1/2 inch Male NPT 1/2 inch OD Run with Poly Gripper |
| CMR-1234-AC-PG | 1/2 inch Male NPT 3/4 inch OD Run Acetal with Poly Gripper |
| CMR-1234-GFPP-PG | 1/2 inch Male NPT 3/4 inch OD Run Glass Filled Polypropylene with Poly Gripper |
| CMR-1234-NPP-PG | 1/2 inch Male NPT 3/4 inch OD Run Natural Polypropylene with Poly Gripper |
| CMR-1234-PG | 1/2 inch Male NPT 3/4 inch OD Run with Poly Gripper |
| CMR-1258-AC-PG | 1/2 inch Male NPT 5/8 inch OD Run Acetal with Poly Gripper |
| CMR-1258-GFPP-PG | 1/2 inch Male NPT 5/8 inch OD Run Glass Filled Polypropylene with Poly Gripper |
| CMR-1258-NPP-PG | 1/2 inch Male NPT 5/8 inch OD Run Natural Polypropylene with Poly Gripper |
| CMR-1258-PG | 1/2 inch Male NPT 5/8 inch OD Run with Poly Gripper |
| CMR-1414-AC-PG | 1/4 inch Male NPT 1/4 inch OD Run Acetal with Poly Gripper |
| CMR-1414-K-PG | 1/4 inch Male NPT 1/4 inch OD Run PVDF with Poly Gripper |
| CMR-1414-NPP-PG | 1/4 inch Male NPT 1/4 inch OD Run Natural Polypropylene with Poly Gripper |
| CMR-1414-PG | 1/4 inch Male NPT 1/4 inch OD Run Glass Filled Polypropylene with Poly Gripper |
| CMR-1438-AC-PG | 1/4 inch Male NPT 3/8 inch OD Run Acetal with Poly Gripper |
| CMR-1438-K-PG | 1/4 inch Male NPT 3/8 inch OD Run PVDF with Poly Gripper |
| CMR-1438-NPP-PG | 1/4 inch Male NPT 3/8 inch OD Run Natural Polypropylene with Poly Gripper |
| CMR-1438-PG | 1/4 inch Male NPT 3/8 inch OD Run Glass Filled Polypropylene with Poly Gripper |
| CMR-14516-AC-PG | 1/4 inch Male NPT 5/16 inch OD Run Acetal with Poly Gripper |
| CMR-14516-NPP-PG | 1/4 inch Male NPT 5/16 inch OD Run Natural Polypropylene with Poly Gripper |
| CMR-14516-PG | 1/4 inch Male NPT 5/16 inch OD Run Glass Filled Polypropylene with Poly Gripper |
| CMR-14516-PVDF-PG | 1/4 inch Male NPT 5/16 inch OD Run PVDF with Poly Gripper |
| CMR-1814-AC-PG | 1/8 inch Male NPT 1/4 inch OD Run Acetal with Poly Gripper |
| CMR-1814-NPP-PG | 1/8 inch Male NPT 1/4 inch OD Run Natural Polypropylene with Poly Gripper |

| SKU | Description |
|------------------|--|
| CMR-1814-PG | 1/8 inch Male NPT 1/4 inch OD Run Glass Filled Polypropylene with Poly Gripper |
| CMR-1814-PVDF-PG | 1/8 inch Male NPT 1/4 inch OD Run PVDF with Poly Gripper |
| CMR-3434-AC-PG | 3/4 inch Male NPT 3/4 inch OD Run Acetal with Poly Gripper |
| CMR-3434-NPP-PG | 3/4 inch Male NPT 3/4 inch OD Run Natural Polypropylene with Poly Gripper |
| CMR-3434-PG | 3/4 inch Male NPT 3/4 inch OD Run Glass Filled Polypropylene with Poly Gripper |
| CMR-3434-PVDF-PG | 3/4 inch Male NPT 3/4 inch OD Run PVDF with Poly Gripper |
| CMR-3478-AC-PG | 3/4 inch Male NPT 7/8 inch OD Run Acetal with Poly Gripper |
| CMR-3478-NPP-PG | 3/4 inch Male NPT 7/8 inch OD Run Natural Polypropylene with Poly Gripper |
| CMR-3478-PG | 3/4 inch Male NPT 7/8 inch OD Run Glass Filled Polypropylene with Poly Gripper |
| CMR-3478-PVDF-PG | 3/4 inch Male NPT 7/8 inch OD Run PVDF with Poly Gripper |
| CMR-3812-AC-PG | 3/8 inch Male NPT 1/2 inch OD Run Acetal with Poly Gripper |
| CMR-3812-GFPP-PG | 3/8 inch Male NPT 1/2 inch OD Run Glass Filled Polypropylene with Poly Gripper |
| CMR-3812-PG | 3/8 inch Male NPT 1/2 inch OD Run Natural Polypropylene with Poly Gripper |
| CMR-3812-PVDF-PG | 3/8 inch Male NPT 1/2 inch OD Run PVDF with Poly Gripper |
| CMR-3838-AC-PG | 3/8 inch Male NPT 3/8 inch OD Run Acetal with Poly Gripper |
| CMR-3838-GFPP-PG | 3/8 inch Male NPT 3/8 inch OD Run Glass Filled Polypropylene NP |
| CMR-3838-K-PG | 3/8 inch Male NPT 3/8 inch OD Run PVDF with Poly Gripper |
| CMR-3838-NPP-PG | 3/8 inch Male NPT 3/8 inch OD Run Natural Polypropylene with Poly Gripper |

CME SERIES



The CME Series are Male NPT Compression Fittings to an OD Elbow configuration. Use for Manifolds, Valves, Regulators, or mechanical instruments. They are molded of either Glass-Filled White Polypropylene, NSF approved FDA approved Acetal for use with hot water applications, NSF approved FDA approved Nylon, or NSF approved FDA approved UV resistant PVDF. Provided with a poly gripper for use up to 220 psi. 1/8 inch units do not have a poly gripper.

| SKU | Description |
|------------------|---|
| CME-1212-AC-PG | 1/2 inch MNPT by 1/2 inch OD Acetal Elbow with Poly Gripper |
| CME-1212-NN-PG | 1/2 inch MNPT by 1/2 inch OD Natural Nylon Elbow with Poly Gripper |
| CME-1212-PG | 1/2 inch MNPT by 1/2 inch OD Glass-Filled Polypropylene Elbow with Poly Gripper |
| CME-1212-PVDF-PG | 1/2 inch MNPT by 1/2 inch OD PVDF Elbow with Poly Gripper |
| CME-1258-AC-PG | 1/2 inch MNPT by 5/8 inch OD Acetal Elbow with Poly Gripper |
| CME-1258-NN-PG | 1/2 inch MNPT by 5/8 inch OD Natural Nylon Elbow with Poly Gripper |

| SKU | Description |
|------------------|--|
| CME-1258-PG | 1/2 inch MNPT by 5/8 inch OD Glass-Filled Polypropylene Elbow with Poly Gripper |
| CME-1258-PVDF PG | 1/2 inch MNPT by 5/8 inch OD PVDF Elbow with Poly Gripper |
| CME-1412-AC-PG | 1/4 inch MNPT by 1/2 inch OD Acetal Elbow with Poly Gripper |
| CME-1412-GFPP-PG | 1/4 inch MNPT by 1/2 inch OD Glass-Filled Polypropylene Elbow with Poly Gripper |
| CME-1412-K-PG | 1/4 inch MNPT by 1/2 inch OD PVDF Elbow with Poly Gripper |
| CME-1412-NN-PG | 1/4 inch MNPT by 1/2 inch OD Natural Nylon Elbow with Poly Gripper |
| CME-1414-AC-PG | 1/4 inch MNPT by 1/4 inch OD Acetal Elbow with Poly Gripper |
| CME-1414-GFPP-PG | 1/4 inch MNPT by 1/4 inch OD Glass-Filled Polypropylene Elbow with Poly Gripper |
| CME-1414-K-PG | 1/4 inch MNPT by 1/4 inch OD PVDF Elbow with Poly Gripper |
| CME-1414-NN-PG | 1/4 inch MNPT by 1/4 inch OD Natural Nylon Elbow with Poly Gripper |
| CME-1438-AC-PG | 1/4 inch MNPT by 3/8 inch OD Acetal Elbow with Poly Gripper |
| CME-1438-K | 1/4 inch MNPT by 3/8 inch OD PVDF Elbow |
| CME-1438-K-PG | 1/4 inch MNPT by 3/8 inch OD PVDF Elbow with Poly Gripper |
| CME-1438-NN-PG | 1/4 inch MNPT by 3/8 inch OD Natural Nylon Elbow with Poly Gripper |
| CME-1438-PG | 1/4 inch MNPT by 3/8 inch OD Glass-Filled Polypropylene Elbow with Poly Gripper |
| CME-14516AC--PG | 1/4 inch MNPT by 5/16 inch OD Acetal Elbow with Poly Gripper |
| CME-14516-K-PG | 1/4 inch MNPT by 5/16 inch OD PVDF Elbow with Poly Gripper |
| CME-14516-NN-PG | 1/4 inch MNPT by 5/16 inch OD Natural Nylon Elbow with Poly Gripper |
| CME-14516-PG | 1/4 inch MNPT by 5/16 inch OD Glass Filled Polypropylene Elbow with Poly Gripper |
| CME-1814 | 1/8 inch MNPT by 1/4 inch OD Glass-Filled Polypropylene Elbow |
| CME-1814-AC-PG | 1/8 inch MNPT by 1/4 inch OD Acetal Elbow with Poly Gripper |
| CME-1814-K | 1/8 inch MNPT by 1/4 inch OD PVDF Elbow |
| CME-1814-NN-PG | 1/8 inch MNPT by 1/4 inch OD Natural Nylon Elbow with Poly Gripper |
| CME-1814-PVDF-PG | 1/8 inch MNPT by 1/4 inch OD PVDF Elbow with Poly Gripper |
| CME-1818 | 1/8 inch MNPT by 1/8 inch OD Glass-Filled Polypropylene Elbow |
| CME-1818-AC | 1/8 inch MNPT by 1/8 inch OD Acetal Elbow |
| CME-1818-K | 1/8 inch MNPT by 1/8 inch OD PVDF Elbow |
| CME-1818-NN | 1/8 inch MNPT by 1/8 inch OD Natural Nylon Elbow |
| CME-3812-AC-PG | 3/8 inch MNPT by 1/2 inch OD Acetal Elbow with Poly Gripper |
| CME-3812-K-PG | 3/8 inch MNPT by 1/2 inch OD PVDF Elbow with Poly Gripper |
| CME-3812-NN-PG | 3/8 inch MNPT by 1/2 inch OD Natural Nylon Elbow with Poly Gripper |
| CME-3812-PG | 3/8 inch MNPT by 1/2 inch OD Glass-Filled Polypropylene Elbow with Poly Gripper |
| CME-3814-AC-PG | 3/8 inch MNPT by 1/4 inch OD Acetal Elbow with Poly Gripper |
| CME-3814-K-PG | 3/8 inch MNPT by 1/4 inch OD PVDF Elbow with Poly Gripper |
| CME-3814-NN-PG | 3/8 inch MNPT by 1/4 inch OD Natural Nylon Elbow with Poly Gripper |

| SKU | Description |
|------------------|--|
| CME-3814-PG | 3/8 inch MNPT by 1/4 inch OD Glass-Filled Polypropylene Elbow with Poly Gripper |
| CME-3838-AC-PG | 3/8 inch MNPT by 3/8 inch OD Acetal Elbow with Poly Gripper |
| CME-3838-K-PG | 3/8 inch MNPT by 3/8 inch OD PVDF Elbow with Poly Gripper |
| CME-3838-NN-PG | 3/8 inch MNPT by 3/8 inch OD Natural Nylon Elbow with Poly Gripper |
| CME-3838-PG | 3/8 inch MNPT by 3/8 inch OD Glass-Filled Polypropylene Elbow with Poly Gripper |
| CME-38516-AC-PG | 3/8 inch MNPT by 5/16 inch OD Acetal Elbow with Poly Gripper |
| CME-38516-K-PG | 3/8 inch MNPT by 5/16 inch OD PVDF Elbow with Poly Gripper |
| CME-38516-NN-PG | 3/8 inch MNPT by 5/16 inch OD Natural Nylon Elbow with Poly Gripper |
| CME-38516-PG | 3/8 inch MNPT by 5/16 inch OD Glass-Filled Polypropylene Elbow with Poly Gripper |
| CME-3858-AC-PG | 3/8 inch MNPT by 5/8 inch OD Acetal Elbow with Poly Gripper |
| CME-3858-GFPP-PG | 3/8 inch MNPT by 5/8 inch OD Glass-Filled Polypropylene Elbow with Poly Gripper |
| CME-3858-NN-PG | 3/8 inch MNPT by 5/8 inch OD Natural Nylon Elbow with Poly Gripper |
| CME-3858-PVDF-PG | 3/8 inch MNPT by 5/8 inch OD PVDF Elbow with Poly Gripper |



CFE 90° ELBOW COMPRESSION FITTING

The CFE Series Compression to Female Pipe Thread Fittings are to Valves or Plastic Pipe Fittings for tube connection without kinking attached tubing. Available in NSF approved Glass-Filled White Polypropylene, FDA and NSF approved Acetal (POM) for use with hot water applications, FDA and NSF approved Nylon, and UV resistant FDA and NSF rated PVDF. Provided with Poly gripper (except for 1/8 inch units) for us up to 220 psi.

| SKU | Description |
|-----------|---------------------------------------|
| CFE-1814 | 1/8 FNPT by 1/4 OD Compression Elbow |
| CFE-1418 | 1/4 FNPT by 1/8 OD Compression Elbow |
| CFE-1414 | 1/4 FNPT by 1/4 OD Compression Elbow |
| CFE-14516 | 1/4 FNPT by 5/16 OD Compression Elbow |
| CFE-1438 | 1/4 FNPT by 3/8 OD Compression Elbow |
| CFE-3838 | 3/8 FNPT by 3/8 OD Compression Elbow |
| CFE-3812 | 3/8 FNPT by 1/2 OD Compression Elbow |
| CFE-1212 | 1/2 FNPT by 1/2 OD Compression Elbow |
| CFE-1258 | 1/2 FNPT by 5/8 OD Compression Elbow |

CF SERIES



The CF Series Compression Female Pipe Threads, 1/8 inch to 1/2 inch, with compression fittings ranging from 1/4 inch to 5/8 inch tube connection without kinking attached tubing. Available in NSF approved Glass-Filled White Polypropylene, FDA and NSF approved Acetal (POM) for use with hot water applications, FDA and NSF approved Nylon, and UV resistant FDA and NSF rated PVDF. Provided with Poly gripper (except for 1/8 inch units) for us up to 220 psi.

| SKU | Description |
|-----------------|---|
| CF-1212-AC-PG | 1/2 inch OD by 1/2 inch Female Connector Acetal Compression with Poly Gripper |
| CF-1212-NN-PG | 1/2 inch OD by 1/2 inch Female Connector Natural Nylon Compression with Poly Gripper |
| CF-1212-PG | 1/2 inch OD by 1/2 inch Female Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CF-1212-PVDF-PG | 1/2 inch OD by 1/2 inch Female Connector PVDF Compression with Poly Gripper |
| CF-1238-AC-PG | 3/8 inch OD by 1/2 inch Female Connector Acetal Compression with Poly Gripper |
| CF-1238-GFPP-PG | 3/8 inch OD by 1/2 inch Female Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CF-1238-K-PG | 3/8 inch OD by 1/2 inch Female Connector PVDF Compression with Poly Gripper |
| CF-1238-NN-PG | 3/8 inch OD by 1/2 inch Female Connector Natural Nylon Compression with Poly Gripper |
| CF-1258-AC-PG | 5/8 inch OD by 1/2 inch Female Connector Acetal Compression with Poly Gripper |
| CF-1258-GFPP-PG | 5/8 inch OD by 1/2 inch Female Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CF-1258-PG | 5/8 inch OD by 1/2 inch Female Connector Natural Nylon Compression with Poly Gripper |
| CF-1258-PVDF-PG | 5/8 inch OD by 1/2 inch Female Connector PVDF Compression with Poly Gripper |
| CF-1414 | 1/4 inch OD by 1/4 inch Female Connector Polypropylene Compression |
| CF-1414-AC-PG | 1/4 inch OD by 1/4 inch Female Connector Acetal Compression with Poly Gripper |
| CF-1414-F257 | 1/4 inch OD by 1/4 inch Female Polypropylene Compression with thru hole |
| CF-1414-GFPP-PG | 1/4 inch OD by 1/4 inch Female Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CF-1414-K | 1/4 inch OD by 1/4 inch Female Connector PVDF Compression |
| CF-1414-K-PG | 1/4 inch OD by 1/4 inch Female Connector PVDF Compression with Poly Gripper |
| CF-1414-NN-PG | 1/4 inch OD by 1/4 inch Female Connector Natural Nylon Compression with Poly Gripper |

| SKU | Description |
|------------------|---|
| CF-1418-AC-PG | 1/4 inch OD by 1/8 inch Female Connector Acetal Compression with Poly Gripper |
| CF-1418-GFPP-PG | 1/4 inch OD by 1/8 inch Female Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CF-1418-PG | 1/4 inch OD by 1/8 inch Female Connector Natural Nylon Compression with Poly Gripper |
| CF-1418-PVDF-PG | 1/4 inch OD by 1/8 inch Female Connector PVDF Compression with Poly Gripper |
| CF-1438-AC-PG | 3/8 inch OD by 1/4 inch Female Connector Acetal Compression with Poly Gripper |
| CF-1438-GFPP-PG | 3/8 inch OD by 1/4 inch Female Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CF-1438-K | 3/8 inch OD by 1/4 inch Female Connector PVDF Compression |
| CF-1438-K-PG | 3/8 inch OD by 1/4 inch Female Connector PVDF Compression with Poly Gripper |
| CF-1438-NN-PG | 3/8 inch OD by 1/4 inch Female Connector Natural Nylon Compression with Poly Gripper |
| CF-14516-AC-PG | 5/16 OD by 1/4 inch Female Connector Acetal Compression with Poly Gripper |
| CF-14516-GFPP-PG | 5/16 OD by 1/4 inch Female Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CF-14516-NN-PG | 5/16 OD by 1/4 inch Female Connector Natural Nylon Compression with Poly Gripper |
| CF-14516-PVDF-PG | 5/16 OD by 1/4 inch Female Connector PVDF Compression with Poly Gripper |
| CF-1814-AC-PG | 1/8 inch Female NPT by 1/4 inch OD Acetal Compression with Poly Gripper |
| CF-1814-GFPP-PG | 1/8 inch Female NPT by 1/4 inch OD Glass-Filled Polypropylene Compression with Poly Gripper |
| CF-1814-K-PG | 1/8 inch Female NPT by 1/4 inch OD PVDF Compression with Poly Gripper |
| CF-1814-NN-PG | 1/8 inch Female NPT by 1/4 inch OD Natural Nylon Compression with Poly Gripper |
| CF-3812-AC-PG | 1/2 inch OD by 3/8 inch Female Acetal Compression with Poly Gripper |
| CF-3812-GFPP-PG | 1/2 inch OD by 3/8 inch Female Glass-Filled Polypropylene Compression with Poly Gripper |
| CF-3812-K-PG | 1/2 inch OD by 3/8 inch Female PVDF Compression with Poly Gripper |
| CF-3812-NN-PG | 1/2 inch OD by 3/8 inch Female Natural Nylon Compression with Poly Gripper |
| CF-3838 | 3/8 inch OD by 3/8 inch Female Connector Compression |
| CF-3838-AC-PG | 3/8 inch OD by 3/8 inch Female Connector Acetal Compression with Poly Gripper |
| CF-3838-GFPP-PG | 3/8 inch OD by 3/8 inch Female Connector Glass-Filled Polypropylene Compression with Poly Gripper |
| CF-3838-K-PG | 3/8 inch OD by 3/8 inch Female Connector PVDF Compression with Poly Gripper |
| CF-3838-NN-PG | 3/8 inch OD by 3/8 inch Female Connector Natural Nylon Compression with Poly Gripper |

CE SERIES



The CE Series Plastic Compression Elbow Fittings are used to allow a 90 degree tube connection without kinking attached tubing. Available in NSF approved Glass-Filled White Polypropylene, FDA and NSF approved Acetal (POM) for use with hot water applications, FDA and NSF approved Nylon, and UV resistant FDA and NSF rated PVDF. Provided with Poly gripper (except for 1/8 inch units) for us up to 220 psi.

| SKU | Description |
|---------------|---|
| CE-12-K-PG | 1/2 inch OD by 1/2 inch OD Elbow Compression PVDF Compression with Poly Gripper |
| CE-12-PG | 1/2 inch OD by 1/2 inch OD Elbow Compression |
| CE-12-NN-PG | 1/2 inch OD by 1/2 inch OD Elbow Compression Natural Nylon with Poly Gripper |
| CE-14 | 1/4 inch OD by 1/4 inch OD Elbow Compression Polypropylene |
| CE-14-K | 1/4 inch OD by 1/4 inch OD PVDF |
| CE-14-K-PG | 1/4 inch OD by 1/4 inch OD Elbow Compression PVDF with Poly Gripper |
| CE-14-PG | 1/4 inch OD Elbow Compression Polypropylene with Poly Gripper |
| CE-14-NN-PG | 1/4 inch OD Elbow Compression Natural Nylon with Poly Gripper |
| CE-38-K-PG | 3/8 inch OD by 3/8 inch OD Elbow Compression PVDF with Poly Gripper |
| CE-38-PG | 3/8 inch OD by 3/8 inch OD Elbow Compression Natural Nylon with Poly Gripper |
| CE-3814-K | 3/8 inch OD by 1/4 inch OD Elbow Compression PVDF |
| CE-3814-NN | 3/8 inch OD by 1/4 inch OD Elbow Compression Natural Nylon |
| CE-516-K-PG | 5/16 inch OD by 5/16 inch OD Elbow Compression PVDF with Poly Gripper |
| CE-516-PG | 5/16 inch OD by 5/16 inch OD Elbow Compression Natural Nylon with Poly Gripper |
| CE-58-PG | 5/8 inch OD by 5/8 inch OD Elbow Compression Natural Nylon with Poly Gripper |
| CE-58-PVDF-PG | 5/8 inch OD by 5/8 inch OD Elbow Compression PVDF with Poly Gripper |
| CE-78-PG | 7/8 inch OD by 7/8 inch OD Elbow Compression Natural Nylon with Poly Gripper |
| CE-78-PVDG-PG | 7/8 inch OD by 7/8 inch OD Elbow Compression PVDF with Poly Gripper |



CB SERIES

The CB Series Compression Bulkheads allow Air or Fluid lines to be passed through walls for a clean connection for use with tubing ranges of 1/4 inch to 7/8 inch Outside Diameter in tanks and for service lines. Available in NSF approved Glass-Filled White Polypropylene, FDA and NSF approved Acetal (POM) for use with hot water applications, FDA and NSF approved Nylon, and UV resistant FDA and NSF rated PVDF. Provided with Poly gripper (except for 1/8 inch units) for up to 220 psi.

| SKU | Description |
|---------------|--|
| CB-12-GFPP | 1/2 inch OD Glass-Filled Polypropylene Bulkhead |
| CB-12-KO | 1/2 inch OD PVDF Bulkhead |
| CB-12-PG | 1/2 inch OD Polypropylene Bulkhead with Gripper |
| CB-14-GFPP | 1/4 inch OD Glass-Filled Polypropylene Bulkhead |
| CB-14-K | 1/4 inch OD PVDF Bulkhead |
| CB-14-PG | 1/4 inch OD Polypropylene Bulkhead with Gripper |
| CB-1814R-AC | 1/4 inch Short with 1/8 Cap Acetal Bulkhead |
| CB-1814R-GFPP | 1/4 inch Short with 1/8 Cap Polypropylene Bulkhead |
| CB-1814R-K | 1/4 inch Short with 1/8 Cap PVDF Bulkhead |
| CB-1814R-NN | 1/4 inch Short with 1/8 Cap Natural Nylon Bulkhead |
| CB-34-AC | 3/4 inch OD Acetal Bulkhead |
| CB-34-GFPP | 3/4 inch OD Glass-Filled Polypropylene Bulkhead |
| CB-34-K | 3/4 inch OD PVDF Bulkhead |
| CB-34-NN | 3/4 inch OD Natural Nylon Bulkhead |
| CB-34-PG | 3/4 inch OD Glass-Filled Polypropylene Bulkhead with Gripper |
| CB-38-GFPP | 3/8 inch OD Glass-Filled Polypropylene Bulkhead |
| CB-38-K | 3/8 inch OD PVDF Bulkhead |
| CB-38-PG | 3/8 inch OD Polypropylene Bulkhead with Gripper |
| CB-516-GFPP | 5/16 inch OD Glass-Filled Polypropylene Bulkhead |
| CB-516-K | 5/16 inch OD PVDF Bulkhead |
| CB-516-PG | 5/16 inch OD Polypropylene Bulkhead with Gripper |
| CB-78-AC | 7/8 inch OD Acetal Bulkhead |
| CB-78-GFPP | 7/8 inch OD Glass-Filled Polypropylene Bulkhead |
| CB-78-K | 7/8 inch OD PVDF Bulkhead |
| CB-78-NN | 7/8 inch OD Natural Nylon Bulkhead |
| CB-78-PG | 7/8 inch OD Polypropylene Bulkhead with Gripper |



CA STRAIGHT THREADED COMPRESSION FITTINGS

The CA Series Male Straight Pipe Compression Fittings allow tubing to be connected to Pipes, Valves, and Manifolds for attaching Tube lines. Available for 1/8 inch to 7/8 inch tubing and Male NPT 1/8 inch to 3/4 inch tube connection without kinking attached tubing. Available in FDA and NSF approved Acetal (POM) for use with hot water applications, FDA and NSF approved Nylon, and UV resistant FDA and NSF rated PVDF. Provided with Poly gripper (except for 1/8 inch units) for use up to 220 psi.

| SKU | Descriptions |
|------------------|--|
| CA-1212-AC-PG | 1/2 inch MNPT by 1/2 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-1212-K-PG | 1/2 inch MNPT by 1/2 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-1212-NN-PG | 1/2 inch MNPT by 1/2 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-1212-PG | 1/2 inch MNPT by 1/2 inch OD Polypropylene Compression Fitting with Poly Gripper |
| CA-1234-AC-PG | 1/2 inch MNPT by 3/4 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-1234-NN-PG | 1/2 inch MNPT by 3/4 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-1234-PG | 1/2 inch MNPT by 3/4 inch OD Polypropylene Compression Fitting with Poly Gripper |
| CA-1234-PVDF-PG | 1/2 inch MNPT by 3/4 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-1238-AC-PG | 1/2 inch MNPT by 3/8 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-1238-K-PG | 1/2 inch MNPT by 3/8 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-1238-NN-PG | 1/2 inch MNPT by 3/8 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-1238-PG | 1/2 inch MNPT by 3/8 inch OD Polypropylene Compression Fitting with Poly Gripper |
| CA-12516-AC-PG | 1/2 inch MNPT by 5/16 inch OD Acetal Compression Fitting with Poly Gripper 2 piece unit |
| CA-12516-NN-PG | 1/2 inch MNPT by 5/16 inch OD Natural Nylon Compression Fitting with Poly Gripper 2 piece unit |
| CA-12516-PVDF-PG | 1/2 inch MNPT by 5/16 inch OD PVDF Compression Fitting with Poly Gripper 2 piece unit |
| CA-1258-AC-PG | 1/2 inch MNPT by 5/8 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-1258-NN-PG | 1/2 inch MNPT by 5/8 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-1258-PG | 1/2 inch MNPT by 5/8 inch OD Polypropylene Compression Fitting with Poly Gripper |
| CA-1258-PVDF-PG | 1/2 inch MNPT by 5/8 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-1412-AC-PG | 1/4 inch MNPT by 1/2 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-1412-K-PG | 1/4 inch MNPT by 1/2 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-1412-NN-PG | 1/4 inch MNPT by 1/2 inch OD Natural Nylon Compression Fitting with Poly Gripper |

| SKU | Descriptions |
|-----------------|---|
| CA-1412-PG | 1/4 inch MNPT by 1/2 inch OD Polypropylene Compression Fitting with Poly Gripper |
| CA-1414 | 1/4 inch MNPT by 1/4 inch OD Polypropylene Compression Fitting with O-Ring |
| CA-1414-AC-PG | 1/4 inch MNPT by 1/4 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-1414-K-PG | 1/4 inch MNPT by 1/4 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-1414-NN-PG | 1/4 inch MNPT by 1/4 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-1438-AC-PG | 1/4 inch MNPT by 3/8 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-1438-K-PG | 1/4 inch MNPT by 3/8 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-1438-NN-PG | 1/4 inch MNPT by 3/8 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-14516 | 1/4 inch MNPT by 5/16 inch OD Polypropylene Compression Fitting with O-Ring |
| CA-14516-AC-PG | 1/4 inch MNPT by 5/16 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-14516-PP-PG | 1/4 inch MNPT by 5/16 inch OD Polypropylene Compression Fitting with Poly Gripper |
| CA-14516-K-PG | 1/4 inch MNPT by 5/16 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-14516-NN-PG | 1/4 inch MNPT by 5/16 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-1812-AC-PG | 1/8 inch MNPT by 1/2 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-1812-NN-PG | 1/8 inch MNPT by 1/2 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-1812-PVDF-PG | 1/8 inch MNPT by 1/2 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-1814-PP | 1/8 inch MNPT by 1/4 inch OD Polypropylene Compression Fitting with O-Ring |
| CA-1814-K | 1/8 inch MNPT by 1/4 inch OD PVDF Compression Fitting with O-Ring |
| CA-1814-K-PG | 1/8 inch MNPT by 1/4 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-1818-PP | 1/8 inch MNPT by 1/8 inch OD Polypropylene Compression Fitting with O-Ring |
| CA-1818-AC-PG | 1/8 inch MNPT by 1/8 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-1818-K | 1/8 inch MNPT by 1/8 inch OD PVDF Compression Fitting with O-Ring |
| CA-1818-NN-PG | 1/8 inch MNPT by 1/8 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-1838-AC-PG | 1/8 inch MNPT by 3/8 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-1838-K-PG | 1/8 inch MNPT by 3/8 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-1838-NN-PG | 1/8 inch MNPT by 3/8 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-3434-AC-PG | 3/4 inch MNPT by 3/4 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-3434-NN-PG | 3/4 inch MNPT by 3/4 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-3434-PVDF-PG | 3/4 inch MNPT by 3/4 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-3478-AC-PG | 3/4 inch MNPT by 7/8 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-3478-NN-PG | 3/4 inch MNPT by 7/8 inch OD Natural Nylon Compression Fitting with Poly Gripper |

| SKU | Descriptions |
|-----------------|---|
| CA-3478-PVDF-PG | 3/4 inch MNPT by 7/8 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-3812-AC-PG | 3/8 inch MNPT by 1/2 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-3812-K-PG | 3/8 inch MNPT by 1/2 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-3812-NN-PG | 3/8 inch MNPT by 1/2 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-3814-AC-PG | 3/8 inch MNPT by 1/4 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-3814-K-PG | 3/8 inch MNPT by 1/4 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-3814-NN-PG | 3/8 inch MNPT by 1/4 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-3814-PP-PG | 3/8 inch MNPT by 1/4 inch OD Polypropylene Compression Fitting with Gripper |
| CA-3838-AC-PG | 3/8 inch MNPT by 3/8 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-3838-K-PG | 3/8 inch MNPT by 3/8 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-3838-NN-PG | 3/8 inch MNPT by 3/8 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-3838-PP-PG | 3/8 inch MNPT by 3/8 inch OD Polypropylene Compression Fitting with Poly Gripper |
| CA-38516-AC-PG | 3/8 inch MNPT by 5/16 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-38516-K-PG | 3/8 inch MNPT by 5/16 inch OD PVDF Compression Fitting with Poly Gripper |
| CA-38516-NN-PG | 3/8 inch MNPT by 5/16 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-3858-AC-PG | 3/8 inch MNPT by 5/8 inch OD Acetal Compression Fitting with Poly Gripper |
| CA-3858-NN-PG | 3/8 inch MNPT by 5/8 inch OD Natural Nylon Compression Fitting with Poly Gripper |
| CA-3858-PP-PG | 3/8 inch MNPT by 5/8 inch OD Polypropylene Compression Fitting with Poly Gripper |
| CA-3858-PVDF-PG | 3/8 inch MNPT by 5/8 inch OD PVDF Compression Fitting with Poly Gripper |

AO-IG SERIES



The AO-IG Series is a thread-to-barb fitting made of FDA approved Polysulfone with an integral precision orifice. The threads are 10-32 inch male UNF threads and the barbs are either 1/8 inch or 1/16 inch. The maximum operating pressure is 100 psi.

| SKU | Description |
|-----------------|--|
| AO-IG-10X1B-004 | 10-32 inch Male UNF by 1/16 inch, .004 Polysulfone Adapter Orifice |
| AO-IG-10X1B-005 | 10-32 inch Male UNF by 1/16 inch, .005 Polysulfone Adapter Orifice |
| AO-IG-10X1B-006 | 10-32 inch Male UNF by 1/16 inch, .006 Polysulfone Adapter Orifice |
| AO-IG-10X1B-007 | 10-32 inch Male UNF by 1/16 inch, .007 Polysulfone Adapter Orifice |
| AO-IG-10X1B-010 | 10-32 inch Male UNF by 1/16 inch, .010 Polysulfone Adapter Orifice |
| AO-IG-10X1B-012 | 10-32 inch Male UNF by 1/16 inch, .012 Polysulfone Adapter Orifice |
| AO-IG-10X1B-016 | 10-32 inch Male UNF by 1/16 inch, .016 Polysulfone Adapter Orifice |
| AO-IG-10X1B-020 | 10-32 inch Male UNF by 1/16 inch, .020 Polysulfone Adapter Orifice |
| AO-IG-10X1B-025 | 10-32 inch Male UNF by 1/16 inch, .025 Polysulfone Adapter Orifice |
| AO-IG-10X1B-030 | 10-32 inch Male UNF by 1/16 inch, .030 Polysulfone Adapter Orifice |
| AO-IG-10X1B-040 | 10-32 inch Male UNF by 1/16 inch, .040 Polysulfone Adapter Orifice |
| AO-IG-10X2B-004 | 10-32 inch Male UNF by 1/8 inch, .004 Polysulfone Adapter Orifice |
| AO-IG-10X2B-005 | 10-32 inch Male UNF by 1/8 inch, .005 Polysulfone Adapter Orifice |
| AO-IG-10X2B-006 | 10-32 inch Male UNF by 1/8 inch, .006 Polysulfone Adapter Orifice |
| AO-IG-10X2B-007 | 10-32 inch Male UNF by 1/8 inch, .007 Polysulfone Adapter Orifice |
| AO-IG-10X2B-010 | 10-32 inch Male UNF by 1/8 inch, .010 Polysulfone Adapter Orifice |
| AO-IG-10X2B-012 | 10-32 inch Male UNF by 1/8 inch, .012 Polysulfone Adapter Orifice |
| AO-IG-10X2B-016 | 10-32 inch Male UNF by 1/8 inch, .016 Polysulfone Adapter Orifice |
| AO-IG-10X2B-020 | 10-32 inch Male UNF by 1/8 inch, .020 Polysulfone Adapter Orifice |
| AO-IG-10X2B-025 | 10-32 inch Male UNF by 1/8 inch, .025 Polysulfone Adapter Orifice |
| AO-IG-10X2B-030 | 10-32 inch Male UNF by 1/8 inch, .030 Polysulfone Adapter Orifice |
| AO-IG-10X2B-040 | 10-32 inch Male UNF by 1/8 inch, .040 Polysulfone Adapter Orifice |

INDEX

A

AO-IG Series 26

C

CA STRAIGHT THREADED COMPRESSION FITTINGS 23

CB Series 22

CE Series 21

CF Series 19

CFE 90° ELBOW COMPRESSION FITTING 18

CME Series 16

CMR Series 15

CT Series 13

P

PACX Series 12

PB Series 12

PC Series 11

PE Series 10

PEB Series 10

PF Series 9

PM THREAD TO PUSH-TO-CONNECT STRAIGHT CONNECTOR 8

PME THREADED PUSH-TO-CONNECT ELBOW 8

PMES Series 7

PMR Series 6

PMT Series 5

PSB Series 4

PSM THREAD TO MALE PIPE CONNECTOR Push to Connect 3

PSP Series 2

PT Series 2

S

SPE - Push-to-Connect Elbow Stem Connector 1