

FITTING



GHT SERIES

Take control of your water flow with the **GHT Series Male Garden Hose**, designed for **maximum durability and reliability**. Featuring **dual barbed fittings**, this powerhouse ensures a **secure, leak-proof grip** for **high-performance fluid transfers**. Constructed from **rugged Nylon or Black Polypropylene**, it's built to **withstand the elements** and deliver **consistent strength in demanding applications**. Available in **3/8", 1/2", 5/8", and 3/4" barb sizes**, this hose is **ready for action in both residential and commercial setups**.



GP-MTP SERIES

Engineered for reliability, this male thread plug is crafted from medical-grade, gamma-sterilizable polypropylene, ensuring superior chemical resistance. Designed with NPT threads, it comes in both valved and non-valved versions, available in grey or natural hues.

NON-VALVED	VALVED	THREAD SIZE	L(nv/v)	WIDTH	HEIGHT
20PPX-PE1-02	20PPV-PE1-02	1/8" NPT	1.27"/1.39"	.50"	.50"
20PPX-PE1-02MALD	20PPV-PE1-02MALD	1/8" NPT	1.27"/1.39"	.50"	.50"
40PPX-PE1-04	40PPV-PE1-04	1/4" NPT	1.50"/1.65"	.63"	.63"
40PPX-PE1-04MALD	40PPV-PE1-04MALD	1/4" NPT	1.50"/1.65"	.63"	.63"
50PPX-PE1-04	50PPV-PE1-04	1/4" NPT	1.60"/1.75"	.63"	.63"
50PPX-PE1-06	50PPV-PE1-06	3/8" NPT	1.60"/1.75"	.75"	.75"

PUC SERIES



Compact Straight Fitting with two push-to-connect ports in opposite directions. The body is PBT resin. The working pressure is 150 psi and the temperature range is 32° F to 140° F. Suitable for applications involving compressed air and inert gases.

SKU	DESCRIPTION
PUC-12P	1/2 OD PBT Push-to-Connect Union
PUC-14P	1/4 OD PBT Push-to-Connect Union
PUC-18P	1/8 OD PBT Push-to-Connect Union
PUC-316P	3/16 OD PBT Push-to-Connect Union
PUC-38-P	3/8 OD PBT Push-to-Connect Union
PUC-516-P	5/16 OD PBT Push-to-Connect Union
PUC-532-P	5/32 OD PBT Push-to-Connect Union
PUC-58P	5/8 OD PBT Push-to-Connect Union
PUC-4MM-P	4 mm OD PBT Push-to-Connect Union
PUC-6MM-P	6 mm OD PBT Push-to-Connect Union
PUC-8MM-P	8 mm OD PBT Push-to-Connect Union
PUC-10MM-P	10 mm OD PBT Push-to-Connect Union
PUC-18BR	1/8 OD Brass Push-to-Connect Union

PUT SERIES- EQUAL PUSH-TO-CONNECTS



The PUT Series is a Union Tee Fitting that has 3 push-to-connect ports of equal sizes. The body is PBT resin. In addition, the working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

SKU	DESCRIPTION
PUT-12N	1/2 OD Push-to-Connect Tee Nylon
PUT-14P	1/4 OD PBT Push-to-Connect Tee
PUT-18P	1/8 OD PBT Push-to-Connect Tee
PUT-316P	3/16 OD PBT Push-to-Connect Tee
PUT-38-P	3/8 OD PBT Push-to-Connect Tee

SKU	DESCRIPTION
PUT-532-P	5/32 OD PBT Push-to-Connect Tee
PUT-5P	5/16 OD PBT Push-to-Connect Tee
PUT-4MM-P	4 mm OD PBT Push-to-Connect Tee
PUT-6MM-P	6 mm OD PBT Push-to-Connect Tee
PUT-8MM-P	8 mm OD PBT Push-to-Connect Tee

PUTR SERIES



Union Tee fitting with 2 push-to-connect ports of equal sizes and 1 push-to-connect port that is a reducer located 90° apart. The body is PBT resin. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

SKU	Description
PUTR-12-38P	1/2 OD by 3/8 OD PBT Reducing Tee
PUTR-12-516P	1/2 OD by 5/16 OD PBT Reducing Tee
PUTR-14-18P	1/4 OD by 1/8 OD PBT Reducing Tee
PUTR-14-316P	1/4 OD by 3/16 OD PBT Reducing Tee
PUTR-316-532P	3/16 OD by 5/32 OD PBT Reducing Tee
PUTR-38-14P	1/4 OD by 3/8 OD PBT Reducing Tee
PUTR-38-516P	3/8 OD by 5/16 OD PBT Reducing Tee
PUTR-4532P	1/4 OD by 5/32 OD PBT Reducing Tee
PUTR-516-14P	5/16 OD by 1/4 OD PBT Reducing Tee
PUTR-516-532P	5/16 OD by 5/32 OD PBT Reducing Tee



PEA SERIES

Push-to-connect adjustable male swivel 90° Elbow with NPT and UNF threads. The working pressure is 150 psi, and the temperature range is 32° F to 140° F. This series is made of PBT resin, nickel-plated brass with a Buna-N O-ring, and a Stainless Steel grip ring. For use with compressed air and inert gases. This fitting is also available in metric sizes. In fact, these fittings can swivel a full 360°.

SKU	DESCRIPTION
PEA-10U14P	10-32 Male UNF by 1/4 OD PBT Adjustable Elbow
PEA-10U18P	10-32 Male UNF by 1/8 OD PBT Adjustable Elbow
PEA-10U316P	10-32 Male UNF by 3/16 OD PBT Adjustable Elbow
PEA-10U532P	10-32 Male UNF by 5/32 OD PBT Adjustable Elbow
PEA-2M14P	1/8 MNPT by 1/4 OD PBT Adjustable Elbow
PEA-2M18P	1/8 MNPT by 1/8 OD PBT Adjustable Elbow
PEA-2M316P	1/8 MNPT by 3/16 OD PBT Adjustable Elbow
PEA-2M516P	1/8 MNPT by 5/16 OD PBT Adjustable Elbow
PEA-2M532P	1/8 MNPT by 5/32 OD PBT Adjustable Elbow
PEA-4M14P	1/4 MNPT by 1/4 OD PBT Adjustable Elbow
PEA-4M316P	1/4 MNPT by 3/16 OD PBT Adjustable Elbow
PEA-4M516P	1/4 MNPT by 5/16 OD PBT Adjustable Elbow
PEA-6M12P	3/8 MNPT by 1/2 OD PBT Adjustable Elbow
PEA-6M14P	3/8 MNPT by 1/4 OD PBT Adjustable Elbow
PEA-6M316P	3/8 MNPT by 3/16 OD PBT Adjustable Elbow
PEA-6M38P	3/8 MNPT by 3/8 OD PBT Adjustable Elbow
PEA-6M516P	3/8 MNPT by 5/16 OD PBT Adjustable Elbow
PEA-8M12P	1/2 MNPT by 1/2 OD PBT Adjustable Elbow
PEA-8M38P	1/2 MNPT by 3/8 OD PBT Adjustable Elbow

PBFC BULKHEAD SERIES



Push-to-connect female Bulkhead Union fitting with female NPT and BSPT threads. It is made of nickel-plated brass with PBT resin. The working pressure is 150 psi and the temperature range is 32° F to 140° F. It can be used with compressed air and inert gases.

SKU	DESCRIPTION
PBFC-2F-14P	1/8 FNPT by 1/4 PBT Push-to-Connect Bulkhead
PBFC-2F-316P	1/8 FNPT by 3/16 PBT Push-to-Connect Bulkhead
PBFC-2F-516P	1/8 FNPT by 5/16 PBT Push-to-Connect Bulkhead
PBFC-2F-532P	1/8 FNPT by 5/32 PBT Push-to-Connect Bulkhead
PBFC-4F-14P	1/4 FNPT by 1/4 PBT Push-to-Connect Bulkhead
PBFC-4F-316P	1/4 FNPT by 3/16 PBT Push-to-Connect Bulkhead
PBFC-4F-38P	1/4 FNPT by 3/8 PBT Push-to-Connect Bulkhead
PBFC-4F-516P	1/4 FNPT by 5/16 PBT Push-to-Connect Bulkhead
PBFC-4G6MM-P	1/4 Female BSPT by 6mm PBT Push-to-Connect Bulkhead
PBFC-4G8MM-P	1/4 Female BSPT by 8mm PBT Push-to-Connect Bulkhead
PBFC-4R6MM-P	1/4 Female BSPT by 6mm PBT Push-to-Connect Bulkhead
PBFC-4R8MM-P	1/4 Female BSPT by 8mm PBT Push-to-Connect Bulkhead
PBFC-6F-516P	3/8 FNPT by 5/16 PBT Push-to-Connect Bulkhead
PBFC-6F-6P	3/8 FNPT by 3/8 PBT Push-to-Connect Bulkhead
PBFC-6F-8P	3/8 FNPT by 1/2 PBT Push-to-Connect Bulkhead
PBFC-6G6MM-P	3/8 Female BSPT by 6mm PBT Push-to-Connect Bulkhead



PEM45 SERIES- PUSH-TO-CONNECT

The PEM45 Series is a male push-to-connect fitting configured with a 45° elbow. The working pressure is 150 psi and the temperature range is 32° F to 140° F. Also, the metal body material is Nickel-plated Brass and the resin is PBT. This product is intended for use with compressed air and inert gases.

SKU	DESCRIPTION
PEM45-10U18P	PEM45 10-32 Male UNF by 1/8 OD PBT Elbow
PEM45-10U316P	PEM45 10-32 Male UNF by 3/16 OD PBT Elbow
PEM45-10U14P	PEM45 10-32 Male UNF by 1/4 OD PBT Elbow
PEM45-10U532P	PEM45 10-32 Male UNF by 5/32 OD PBT Elbow
PEM45-2M18P	PEM45 1/8 MNPT by 1/8 OD PBT Elbow
PEM45-2M316P	PEM45 1/8 MNPT by 3/16 OD PBT Elbow
PEM45-2M14P	PEM45 1/8 MNPT by 1/4 OD PBT Elbow
PEM45-2M516P	PEM45 1/8 MNPT by 5/16 OD PBT Elbow
PEM45-2M532P	PEM45 1/8 MNPT by 5/32 OD PBT Elbow
PEM45-2M38P	PEM45 1/8 MNPT by 3/8 OD PBT Elbow
PEM45-4M14P	PEM45 1/4 MNPT by 1/4 OD PBT Elbow
PEM45-4M516P	PEM45 1/4 MNPT by 5/16 OD PBT Elbow
PEM45-4M38P	PEM45 1/4 MNPT by 3/8 OD PBT Elbow
PEM45-4M12P	PEM45 1/4 MNPT by 1/2 OD PBT Elbow
PEM45-6M14P	PEM45 3/8 MNPT by 1/4 OD PBT Elbow
PEM45-6M516P	PEM45 3/8 MNPT by 5/16 OD PBT Elbow
PEM45-6M38P	PEM45 3/8 MNPT by 3/8 OD PBT Elbow
PEM45-6M12P	PEM45 3/8 MNPT by 1/2 OD PBT Elbow
PEM45-8M14P	PEM45 1/2 MNPT by 1/4 OD PBT Elbow
PEM45-8M38P	PEM45 1/2 MNPT by 3/8 OD PBT Elbow
PEM45-8M12P	PEM45 1/2 MNPT by 1/2 OD PBT Elbow



PUY SERIES- PUSH-TO-CONNECT

Compact straight fitting with three push-to-connect ports in a Wye pattern with two ports side by side opposite the third port. The body is PBT resin with Nickel-Plated Brass threads. The working pressure is 150 psi and the temperature range is 32° F to 140° F. For use with compressed air and inert gases.

SKU	DESCRIPTION
PUY-12P	1/2 OD Parallel PBT Wye
PUY-14P	1/4 OD Parallel PBT Wye
PUY-18P	1/8 OD Parallel PBT Wye
PUY-316P	3/16 OD Parallel PBT Wye
PUY-38P	3/8 OD Parallel PBT Wye
PUY-516P	5/16 OD Parallel PBT Wye
PUY-532P	5/32 OD Parallel PBT Wye



SSCX SERIES

SSCX Series is a Stainless Steel Cross with equal female NPT threads. It is available in both 304 and 316.

SKU	DESCRIPTION
SSCX-2F	1/8 inch Female Cross 304 only
SSCX-4F	1/4 inch Female Cross
SSCX-6F	3/8 inch Female Cross
SSCX-8F	1/2 inch Female Cross
SSCX-12F	3/4 inch Female Cross
SSCX-16F	1 inch Female Cross
SSCX-20F	1-1/4 inch Female Cross
SSCX-24F	1-1/2 inch Female Cross
SSCX-32F	2 inch Female Cross

DTP SERIES



The DTP Series is a brass barbed tube plug. This fitting has excellent vibration resistance and requires no clamp. The maximum working pressure is 150 psi and the temperature range is -65° F to 90° F. This fitting can be used in humidifiers, pneumatic systems, and filters.

SKU	DESCRIPTION
DTP-33214	Tube Plug 3/32 ID by 1/4 ID
DTP-375	Tube Plug .375 ID
DTP-250	Tube Plug .250 ID
DTP-170	Tube Plug .170 ID

STF SERIES



The STF Series is a Forged Brass female-run Street Tee. These fittings can be used with iron, copper, or brass pipe. They can be used for water, chemicals, flammable gases, and fire sprinkler systems.

SKU	DESCRIPTION
STF-2F2MM	1/8 FNPT Inlet 1/8 MNPT Forged Tee
STF-4F4MM	1/4 FNPT Inlet 1/4 MNPT Forged Tee



CMT SERIES

The CMT Series is a branch tee with either a poly gripper or a ferrule nut with an integral sleeve. The materials available are Acetal, Polypropylene, Nylon, and PVDF. The Male NPT sizes range from 1/8 inch to 3/4 inch and the OD tube sizes are 1/4 inch to 7/8 inch. The recommended temperature range is -80° F to 275° F.

SKU	Description
CMT-1212	1/2 inch MNPT by 1/2 inch OD Compression Tee
CMT-1234	1/2 inch MNPT by 3/4 inch OD Compression Tee
CMT-1258	1/2 inch MNPT by 5/8 inch OD Compression Tee
CMT-1414	1/4 inch MNPT by 1/4 inch OD Compression Tee
CMT-1438	1/4 inch MNPT by 3/8 inch OD Compression Tee
CMT-14516	1/4 inch MNPT by 5/16 inch OD Compression Tee
CMT-1814	1/8 inch MNPT by 1/4 inch OD Compression Tee
CMT-3434	3/4 inch MNPT by 3/4 inch OD Compression Tee
CMT-3478	3/4 inch MNPT by 7/8 inch OD Compression Tee
CMT-3812	3/8 inch MNPT by 1/2 inch OD Compression Tee
CMT-3838	3/8 inch MNPT by 3/8 inch OD Compression Tee



TGF SERIES

TGF Series is a PFA compression-reducing adapter with female NPT threads to a gripper ring. OD sizes range from 1/8 inch to 3/4 inch.

SKU	Description
TGF-4F4	PFA 1/4 inch FNPT by 1/4 inch OD Compression Adapter
TGF-2F-2	PFA 1/8 inch FNPT by 1/8 inch OD Compression Adapter
TGF-2F-4	PFA 1/8 inch FNPT by 1/4 inch OD Compression Adapter
TGF-4F-2	PFA 1/4 inch FNPT by 1/8 inch OD Compression Adapter
TGF-4F-6	PFA 1/4 inch FNPT by 3/8 inch OD Compression Adapter
TGF-4F-8	PFA 1/4 inch FNPT by 1/2 inch OD Compression Adapter
TGF-6F-4	PFA 3/8 inch FNPT by 1/4 inch OD Compression Adapter
TGF-6F-6	PFA 3/8 inch FNPT by 3/8 inch OD Compression Adapter

SKU	Description
TGF-6F-8	PFA 3/8 inch FNPT by 1/2 inch OD Compression Adapter
TGF-8F-4	PFA 1/2 inch FNPT by 1/4 inch OD Compression Adapter
TGF-8F-6	PFA 1/2 inch FNPT by 3/8 inch OD Compression Adapter
TGF-8F-8	PFA 1/2 inch FNPT by 1/2 inch OD Compression Adapter
TGF-8F-12	PFA 1/2 inch FNPT by 3/4 inch OD Compression Adapter
TGF-12F-8	PFA 3/4 inch FNPT by 1/2 inch OD Compression Adapter
TGF-12F-12	PFA 3/4 inch FNPT by 3/4 inch OD Compression Adapter

TGA SERIES



TGA Series is a PFA compression reducer connector with male NPT threads to gripper rings. OD sizes range from 1/8 inch to 3/4 inch, the thread sizes are also from 1/8 inch to 3/4 inch.

SKU	Description
TGA-12M-8	PFA 3/4 inch MNPT by 1/2 inch OD Compression Adapter
TGA-12M-12	PFA 3/4 inch MNPT by 3/4 inch OD Compression Adapter
TGA-2M-2	PFA 1/8 inch MNPT by 1/8 inch OD Compression Adapter
TGA-2M-4	PFA 1/8 inch MNPT by 1/4 inch OD Compression Adapter
TGA-4M-2	PFA 1/4 inch MNPT by 1/8 inch OD Compression Adapter
TGA-4M-4	PFA 1/4 inch MNPT by 1/4 inch OD Compression Adapter
TGA-4M-6	PFA 1/4 inch MNPT by 3/8 inch OD Compression Adapter
TGA-4M-8	PFA 1/4 inch MNPT by 1/2 inch OD Compression Adapter
TGA-6M-4	PFA 3/8 inch MNPT by 1/4 inch OD Compression Adapter
TGA-6M-6	PFA 3/8 inch MNPT by 3/8 inch OD Compression Adapter
TGA-6M-8	PFA 3/8 inch MNPT by 1/2 inch OD Compression Adapter
TGA-8M-4	PFA 1/2 inch MNPT by 1/4 inch OD Compression Adapter
TGA-8M-6	PFA 1/2 inch MNPT by 3/8 inch OD Compression Adapter
TGA-8M8	PFA 1/2 inch MNPT by 1/2 inch OD Compression Adapter
TGA-8M-12	PFA 1/2 inch MNPT by 3/4 inch OD Compression Adapter

MCC SERIES



The MCC Series is a Chrome-Plated Brass Ferrules Compression fitting. The pressure range is vacuum to 100 psi and the working temperature range is -40°F to 180°F. Tubing options for use with this fitting are Polyethylene, Polyurethane, and PVC. Sizes available for pipe thread are 10-32 inch male UNF, 1/8 inch MNPT, and 1/4 inch MNPT. Available tubing sizes are 1/8 inch, 1/4 inch, and 3/8 inch.

SKU	Description
MCC-1018	10-32 inch Male UNF with 5/64 inch ID by 1/8 inch OD Chrome-Plated Brass Compression Fitting
MCC-1014	10-32 inch Male UNF with .170 inch ID by 1/4 inch OD Chrome-Plated Brass Compression Fitting
MCC-2M18	1/8 inch MNPT with 5/64 inch ID by 1/8 inch OD Chrome-Plated Brass Compression Fitting
MCC-2M14	1/8 inch MNPT with .170 inch ID by 1/4 inch OD Chrome-Plated Brass Compression Fitting
MCC-2M38	1/8 inch MNPT with 1/4 inch ID by 3/8 inch OD Chrome-Plated Brass Compression Fitting
MCC-4M14	1/4 inch MNPT with .170 inch ID by 1/4 inch OD Chrome-Plated Brass Compression Fitting
MCC-4M38	1/4 inch MNPT with 1/4 inch ID by 3/8 inch OD Chrome-Plated Brass Compression Fitting



FGMS SERIES

Upgrade your setup with the **FGMS Series Female Garden Hose**, featuring **precision-engineered Male NPT swivel fittings** for **secure, flexible connections**. Crafted from **durable Nylon**, this connector delivers **long-lasting reliability** in both residential and industrial applications. Available in **1/4", 3/8", and 1/2" MNPT thread sizes**, it ensures **effortless installation and optimal performance** for various watering and fluid transfer needs.

SKU	Description
FGHMS-2F-N	FGH by 1/8 inch FNPT Nylon Garden Hose Swivel
FGHMS-2M-N	FGH by 1/8 inch MNPT Nylon Garden Hose Swivel
FGHMS-4M-N	FGH by 1/4 inch MNPT Nylon Garden Hose Swivel
FGHMS-6M-N	FGH by 3/8 inch MNPT Nylon Garden Hose Swivel
FGHMS-8M-N	FGH by 1/2 inch MNPT Nylon Garden Hose Swivel



FPC SERIES-PLASTIC FITTING

The FPC Series are equal connectors, and the FPRC Series are reducing connectors. Both series are available in Natural Nylon and Black Polypropylene. **The female threads allow a connection to two male fittings.** The female NPT threads range from 1/8 inch to 3 inches in both equal and reducing configurations. Reducing connectors 1 inch and above are not available in Natural Nylon.

SKU	Description
FPC-2F-BPP	1/8 inch FNPT Black Polypropylene Pipe Connector
FPC-2F-NN	1/8 inch FNPT Natural Nylon Pipe Connector
FPC-2FS-BPP	1/8 inch FNPT Black Polypropylene Short Pipe Connector
FPC-2FS-NN	1/8 inch FNPT Natural Nylon Short Pipe Connector
FPC-4F-BPP	1/4 inch FNPT Black Polypropylene Pipe Connector
FPC-4F-NN	1/4 inch FNPT Natural Nylon Pipe Connector
FPC-4FS-BPP	1/4 inch FNPT Black Polypropylene Short Pipe Connector
FPC-4FS-NN	1/4 inch FNPT Natural Nylon Short Pipe Connector
FPC-6F-BPP	3/8 inch FNPT Black Polypropylene Pipe Connector
FPC-6F-NN	3/8 inch FNPT Natural Nylon Pipe Connector

SKU	Description
FPC-8F-BPP	1/2 inch FNPT Black Polypropylene Pipe Connector
FPC-8F-NN	1/2 inch FNPT Natural Nylon Pipe Connector
FPC-12F-BPP	3/4 inch FNPT Black Polypropylene Pipe Connector
FPC-12F-NN	3/4 inch FNPT Natural Nylon Pipe Connector
FPC-16F-BPP	1 inch FNPT Black Polypropylene Pipe Connector
FPC-16F-NN	1 inch FNPT Natural Nylon Pipe Connector
FPC-20F-BPP	1-1/4 inch FNPT Black Polypropylene Pipe Connector
FPC-20F-NN	1-1/4 inch FNPT Natural Nylon Pipe Connector
FPC-24F-BPP	1-1/2 inch FNPT Black Polypropylene Pipe Connector
FPC-24F-NN	1-1/2 inch FNPT Natural Nylon Pipe Connector
FPC-32F-BPP	2 inch FNPT Black Polypropylene Pipe Connector
FPC-32F-NN	2 inch FNPT Natural Nylon Pipe Connector
FPC-48F-BPP	3 inch FNPT Black Polypropylene Pipe Connector
FPRC-4F2F-BPP	1/4 inch FNPT by 1/8 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-4F2F-NN	1/4 inch FNPT by 1/8 inch FNPT Natural Nylon Reducing Pipe Connector
FPRC-6F2F-BPP	3/8 inch FNPT by 1/8 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-6F2F-NN	3/8 inch FNPT by 1/8 inch FNPT Natural Nylon Reducing Pipe Connector
FPRC-6F4F-BPP	3/8 inch FNPT by 1/4 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-6F4F-NN	3/8 inch FNPT by 1/4 inch FNPT Natural Nylon Reducing Pipe Connector
FPRC-8F6F-BPP	1/2 inch FNPT by 3/8 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-8F6F-NN	1/2 inch FNPT by 3/8 inch FNPT Natural Nylon Reducing Pipe Connector
FPRC-12F6F-BPP	3/4 inch FNPT by 3/8 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-12F6F-NN	3/4 inch FNPT by 3/8 inch FNPT Natural Nylon Reducing Pipe Connector
FPRC-12F8F-BPP	3/4 inch FNPT by 1/2 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-12F8F-NN	3/4 inch FNPT by 1/2 inch FNPT Natural Nylon Reducing Pipe Connector
FPRC-16F12F-BPP	1 inch FNPT by 3/4 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-24F16F-BPP	1-1/2 inch FNPT by 1 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-24F20F-BPP	1-1/2 inch FNPT by 1-1/4 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-32F16F-BPP	2 inch FNPT by 1 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-32F20F-BPP	2 inch FNPT by 1-1/4 inch FNPT Black Polypropylene Reducing Pipe Connector

SKU	Description
FPRC-32F24F-BPP	2 inch FNPT by 1-1/2 inch FNPT Black Polypropylene Reducing Pipe Connector
FPRC-48F32F-BPP	3 inch FNPT by 2 inch FNPT Black Polypropylene Reducing Pipe Connector

CX SERIES



The CX Series is a standard single barbed Cross fitting with no molded parting line on the barb. The barb will expand the tubing to 50% above its normal size. It is available in White Nylon and Natural Polypropylene. The available equal barb sizes are 1/16 inch, 3/32 inch, and 1/8 inch. This cross-fitting is recommended for medical and laboratory environments.

SKU	Description
CX-1B-NPP	1/16 inch Natural Polypropylene Standard Single Barbed Cross Connector
CX-1B-WN	1/16 inch White Nylon Standard Single Barbed Cross Connector
CX-332B-NPP	3/32 inch Natural Polypropylene Standard Single Barbed Cross Connector
CX-332B-WN	3/32 inch White Nylon Standard Single Barbed Cross Connector
CX-2B-NPP	1/8 inch Natural Polypropylene Standard Single Barbed Cross Connector
CX-2B-WN	1/8 inch White Nylon Standard Single Barbed Cross Connector



CMCV SERIES

The CMCV Series Brass Ball Check Valves are compression fittings. This series has Tube OD of 1/8 inch, 1/4 inch, and 3/8 inch. Male NPT thread sizes of 1/8 inch and 1/4 inch are available. The working pressure for the 1/8 inch tube OD is 400 psi, for the 1/4 inch it is 300 psi, and for the 3/8 inch, it is 200 psi. The temperature range is -65° F to 250°F at maximum operating pressures.

SKU	Description
CMCV-14C2M	1/4 inch by 1/8 inch NPT 3 psi Brass Compression Check Valve
CMCV-18C2M	1/8 inch Brass 3 psi by 1/8 inch NPT Brass Compression Check Valve
CMCV-2M14C	1/8 inch NPT by 1/4 inch OD tube 3 psi Brass Compression Check Valve
CMCV-2M18C	1/8 inch NPT by 1/8 inch OD Tube 3 psi Brass Compression Check Valve
CMCV-38C4M	3/8 inch OD tube 3 psi by 1/4 inch NPT Brass Compression Check Valve
CMCV-4M38C	1/4 inch NPT by 3/8 inch OD tube, 3 psi Brass Compression Check Valve

186-2 SERIES

186-2 Series is a Brass Barb Fittings are designed to fit .073 holes using a Loctite adhesive.



SKU	Description
186-2	1/16 inch Barbed Brass Bondable Insert