## **FKM**

### **SPC SERIES**



The SPC Series Plastic Check Valves are made of PVC and have a 302 Stainless Steel spring, 316 Stainless Steel ball, and EPDM seals. Optional materials are Polypropylene and Nylon. 1 psi spring is standard with optional 1/3, 3, 5, 7, 10, or 12 pound springs. Also PVDF bodies in 1/4 inch female NPT only. Hastelloy spring, PTFE ball, and FKM O-rings for aggressive environments are available.

| SKU                  | Description   |
|----------------------|---|
| SPC-2B2B-PB-12       | 1/8 inch Barb Valve Polypropylene Buna 12 psi                           |
| SPC-2B-PP-E-10       | 1/8 inch Barb Polypropylene EPDM 10 psi                                 |
| SPC-2B-V-12          | 1/8 inch Barb Viton® with 12 Spring                                     |
| SPC-2C2C             | 1/8 inch Compression by 1/8 inch Compression                            |
| SPC-2C2M-H-V         | 1/8 inch Compression by 1/8 inch MNPT Hastelloy® FKM                    |
| SPC-2F2F             | 1/8 inch Female by 1/8 inch Female                                      |
| SPC-2F2F-HV          | 1/8 inch Female NPT with Hastelloy® FKM Seals                           |
| SPC-2M2M             | 1/8 inch Male by 1/8 inch Male  |
| SPC-2M4F-E           | 1/8 inch NPT to 1/4 inch Female EPDM Seals                              |
| SPC-4B2M-HV-12       | 1/4 inch Barb to 1/8 inch MNPT Hastelloy® FKM 12 psi                    |
| SPC-4B2M-HV-3        | 1/4 inch Barb to 1/8 inch MNPT Hastelloy® FKM 3psi                      |
| SPC-4B4B             | 1/4 inch Barb by 1/4 inch Barb  |
| SPC-4B4B-HV          | 1/4 inch Barb Hastelloy® FKM .5 psi                                     |
| SPC-4B4B-V-12        | 1/4 inch Barb FKM with 12 spring  |
| SPC-4B4M-BKPP-HV-1/3 | 1/4 inch Barb 1/4 inch Male Black Polypropylene FKM Hastelloy® 1/3 psi  |
| SPC-4B4M-VH          | 1/4 inch Barb by 1/4 inch MNPT FKM/Hastelloy®                           |
| SPC-4B-V-12          | 1/4 inch Barb Viton® with 12 psi Spring                                 |
| SPC-4B-V-H-1         | 1/4 inch Barb PVC FKM PTFE/Hastelloy® 1 psi                             |
| SPC-4C2M-H-V         | 1/4 inch Compression by 1/8 inch MNPT Hastelloy® FKM                    |
| SPC-4C4C             | 1/4 inch Compression by 1/4 inch Compression                            |
| SPC-4C4M-K-H-V       | 1/4 inch Compression 1/4 inch Male PVDF Hastelloy® FKM                  |
| SPC-4F4F             | 1/4 inch Female by 1/4 inch Female                                      |
| SPC-4F4F-H-V         | 1/4 inch F by 1/4 inch Female Hastelloy® FKM                            |
| SPC-4F4F-K-H-V       | 1/4 inch Female PVDF Hastelloy® FKM                                     |
| SPC-4F4FPP-H-V-3     | 1/4 inch Female Polypropylene Hastelloy® FKM 3 psi                      |
| SPC-4F4M-H-V-90PP    | 1/4 inch Female by 1/4 inch NPT Polypropylene Hastelloy®/ FKM 90 Micron |
| SPC-4F4M-K-H-V       | 1/4 inch Female by 1/4 inch M PVDF Hastelloy® FKM                       |

| SKU              | Description  |
|------------------|--|
| SPC-4M4B-HV      | 1/4 inch Male 1/4 inch Barb FKM Hastelloy®             |
| SPC-4M4F-H-V     | 1/4 inch Male by 1/4 inch Female Hastelloy® FKM 1 psi  |
| SPC-4M4F-K-H-V   | 1/4 inch Male by 1/4 inch Female PVDF Hastelloy® FKM   |
| SPC-4M4M         | 1/4 inch Male by 1/4 inch Male                         |
| SPC-4M4M-H-V     | 1/4 inch Male by 1/4 inch Male Hastelloy® FKM 1 psi    |
| SPC-4M4P         | 1/4 inch Male 1/4 inch Push-in                         |
| SPC-4M6B         | 1/4 inch Male 3/8 inch Barb                            |
| SPC-4P2M-H-V     | 1/4 inch Push-in by 1/8 inch inch Male Hastelloy®      |
| SPC-4P4P         | 1/4 inch Push-in by 1/4 inch Push-in                   |
| SPC-4P4P-HV      | 1/4 inch Push-in Hastelloy® FKM                        |
| SPC-4P4P-SS-HV   | 1/4 inch Push-in Stainless Steel Ball Hastelloy® FKM   |
| SPC-4P6B-H-V-7   | 1/4 inch Push-in 3/8 inch Barb Hastelloy® FKM 7        |
| SPC-4PI2M-H-V    | 1/4 inch Push-in by 1/8 inch Male Hastelloy®/ FKM      |
| SPC-4S4P         | 1/4 inch Stem by 1/4 inch Push-in                      |
| SPC-6B6B         | 3/8 inch Barb by 3/8 inch Barb                         |
| SPC-6B-F-1/3     | 3/8 inch Barb Fluoroelastomer 1/3 psi                  |
| SPC-6P4F-H-V     | 3/8 inch Push-in by 1/4 inch Female Hastelloy®/ Viton® |
| SPC-6P4M-H-V     | 3/8 inch Push-in by 1/4 inch Male Hastelloy®/ Viton®   |
| SPC-6P-6B-H-V    | 3/8 inch Push-in 3/8 inch Barb Hastelloy® FKM 7 psi    |
| SPC-6P-6B-H-V-R  | 3/8 inch Push-in 3/8 inch Barb Hastelloy® FKM 7 psi    |
| SPC-6P6M-H-V RV1 | 3/8 inch Push-in by 3/8 inch Male Hastelloy®/ Viton®   |
| SPC-6S6P         | 3/8 inch Stem by 3/8 inch Push-in                      |
| SPC-8B8B         | 1/8 inch Male by 1/8 inch Male                         |

#### **MCV SERIES - CHECK VALVES**



The MCV Series Check Valves are available in various materials: White Nylon is standard, with Black Nylon optional; White Polypropylene is standard with Black Polypropylene optional. Black PVDF is also available. O -ring Seals are Buna-N, EPDM, Viton®, Silicone. The standard spring is 302 Stainless Steel with 316 Stainless Steel ball. The maximum operating pressure is 125 psi. and the maximum operating temperature is 140° F. The Standard barb inlet and outlet sizes are for 1/8 inch, 3/16 inch, and 1/4 inch ID tubing. Outlet side is available with a 1/8 Male NPT or ¼ MNPT. PVDF is sold with PTFE seals and a Hastelloy Spring.

#### **Spring Options:**

1/2 psi - 302 Stainless 1 psi - 302 Stainless 2 psi - 302 Stainless 3 psi - 302 Stainless

### MCV SERIES PRODUCT LIST

| Pneuline Part Number | Size                  | Body          | Seal    | PSI     |
|----------------------|-----------------------|---------------|---------|---------|
| MCV-4B-PPE-1         | 1/4 (4B)              | Polypropylene | EPDM    | 1 PSI   |
| MCV-4B-NV-1/2        | 1/4 (4B)              | Nylon         | Viton ® | 1/2 PSI |
| MCV-4B-NV-1          | 1/4 (4B)              | Nylon         | Viton ® | 1 PSI   |
| MCV-4B3B-NB-2        | 1/4 (4B) by 3/16 (3B) | Nylon         | Buna    | 2 PSI   |
| MCV-3B-PPV-3         | 3/16 (3B)             | Polypropylene | Viton ® | 3 PSI   |
| MCV-3B-PPV-1/2       | 3/16 (3B)             | Polypropylene | Viton ® | 1/2 PSI |
| MCV-3B-PPV-1         | 3/16 (3B)             | Polypropylene | Viton ® | 1 PSI   |
| MCV-3B-PPE-2         | 3/16 (3B)             | Polypropylene | EPDM    | 2 PSI   |
| MCV-3B-PPE-1/2       | 3/16 (3B)             | Polypropylene | EPDM    | 1/2 PSI |
| MCV-3B-PPE-1         | 3/16 (3B)             | Polypropylene | EPDM    | 1 PSI   |
| MCV-3B-NV-1          | 3/16 (3B)             | Nylon         | Viton ® | 1 PSI   |
| MCV-3B-NV-2          | 3/16 (3B)             | Nylon         | Viton ® | 2 PSI   |
| MCV-3B4B-PPV-3       | 3/16 (3B) by 1/4 (4B) | Polypropylene | Viton ® | 3 PSI   |
| MCV-3B4B-PPE-3       | 3/16 (3B) by 1/4 (4B) | Polypropylene | EPDM    | 3 PSI   |
| MCV-2B-PPV-2         | 1/8 (2B)              | Polypropylene | Viton ® | 2 PSI   |
| MCV-2B-PPV-1/2       | 1/8 (2B)              | Polypropylene | Viton ® | 1/2 PSI |
| MCV-2B-PPE-3         | 1/8 (2B)              | Polypropylene | EPDM    | 3 PSI   |
| MCV-2B-PPE-2         | 1/8 (2B)              | Polypropylene | EPDM    | 2 PSI   |
| MCV-2B-PPE-1/2       | 1/8 (2B)              | Polypropylene | EPDM    | 1/2 PSI |
| MCV-2B-PPE-1         | 1/8 (2B)              | Polypropylene | EPDM    | 1 PSI   |

| MCV-2B-PPB-2     | 1/8 (2B)             | Polypropylene | Buna    | 2 PSI   |
|------------------|----------------------|---------------|---------|---------|
| MCV-2B-NV-1/2    | 1/8 (2B)             | Nylon         | Viton ® | 1/2 PSI |
| MCV-2B-NV-1      | 1/8 (2B)             | Nylon         | Viton ® | 1 PSI   |
| MCV-2B-NB-1      | 1/8 (2B)             | Nylon         | Buna    | 1 PSI   |
| MCV-2B4B-PPV-2   | 1/8 (2B) by 1/4 (4B) | Polypropylene | Viton ® | 2 PSI   |
| MCV-2B4B-PPE-1/2 | 1/8 (2B) by 1/4 (4B) | Polypropylene | EPDM    | 1/2 PSI |
| MCV-2B2M-PPV-2   | 1/8 (2B) 1/8 MNPT    | Polypropylene | Viton ® | 2 PSI   |
| MCV-4B4B-PPV-1   | 1/4 (4B)             | Polypropylene | Viton ® | 1 PSI   |



#### **LP SERIES**

The LP Series are low profile Bowl Filters that stand just 2.5 inches tall. The standard configuration is a Nylon top with a clear Nylon bowl. Black Polypropylene is optional. The available gaskets are: Buna, EPDM, or FKM. Filters are: 20, 40, 80, 100 or 250 mesh 303 Stainless Steel; 90 micron Polyethylene filter. Male and Female NPT thread sizes are: 1/8 inch, 1/4 inch, 3/8 inch, and 1/2 inch. Barb sizes are: 1/4 inch, 3/8 inch, and 1/2 inch. Used in agriculture, dental and semi-conductor and vacuum applications for water and chemicals. Not for use with potable water.

| SKU      | Description                                   |
|----------|---|
| LP-20    | Low Profile 20 Mesh Stainless Steel           |
| LP-40    | Low Profile 40 Mesh Stainless Steel           |
| LP-B     | Low profile Buna Gasket                       |
| LP-E     | Low profile EPDM Gasket                       |
| LP-NB    | Low profile White Nylon Bowl                  |
| LP-NCB   | Low profile Nylon Clear Bowl                  |
| LP-PB    | Low Profile Polypropylene Bowl                |
| LP-V     | Low profile FKM Gasket                        |
| LP-90PE  | Low Profile 90 Micron Polyethylene Filter     |
| LP-80    | Low Profile 80 Mesh Stainless Steel           |
| LP-2F-PT | 1/8 FNPT Polypropylene Top Low Profile Filter |
| LP-4F-PT | 1/4 FNPT Polypropylene Top Low Profile Filter |
| LP-6F-NT | 3/8 FNPT Nylon Top Low Profile                |
| LP-6F-PT | 3/8 FNPT Polypropylene Top Low Profile        |
| LP-2M-PT | 1/8 MNPT Polypropylene Top Low Profile        |
| LP-4M-NT | 1/4 MNPT Nylon Top Low Profile                |
| LP-4M-PT | 1/4 MNPT Polypropylene Top Low Profile        |
| LP-4B-NT | 1/4 Barb Nylon Top Low Profile                |
| LP-4B-PT | 1/4 Barb Polypropylene Top Low Profile        |
| LP-6M-PT | 3/8 MNPT Polypropylene Top Low Profile        |
| LP-6B-NT | 3/8 Barb Nylon Top Low Profile                |

| SKU             | Description  |
|-----------------|--|
| LP-6B-PT        | 3/8 Barb Polypropylene Top Low Profile                   |
| LP-2M-NNC-E-40  | 1/8 MNPT Nylon Clear Bowl EPDM-40                        |
| LP-4M-N-E-20    | 1/4 MNPT Nylon BOWL EPDM-20 Mesh                         |
| LP-4M-NNC-E-20  | 1/4 MNPT Nylon Clear Bowl E 20 Mesh Filter               |
| LP-4M-NNC-E-40  | 1/4 MNPT Nylon Clear Bowl EPDM-40                        |
| LP-4M-PP-E-40   | 1/4 MNPT Polypropylene Top and Bowl E 40 Mesh            |
| LP-6M-PP-E-40   | Low Profile 3/8 MNPT Polypropylene E 40                  |
| LP-2F-NNC-V-40  | 1/8 FNPT Nylon Clear Bowl FKM-40                         |
| LP-2F-PNC-E-40  | Low Profile 1/8 FNPT Polypropylene Clearbowl E 40        |
| LP-2F-PP-E-40   | Low Profile 1/8 FNPT Polypropylene E 40                  |
| LP-2F-PNC-V-40  | Low Profile 1/8 FNPT Polypropylene with Clearbowl FKM 40 |
| LP-4F-PNC-E-40  | Low Profile 1/4 FNPT Polypropylene Clearbowl E 40        |
| LP-4F-NNC-V-40  | 1/4 FNPT Nylon Clear Bowl FKM-40                         |
| LP-6F-NNC-V-40  | 3/8 FNPT Nylon Clear Bowl FKM-40                         |
| LP-6F-PNC-E-100 | 3/8 FNPT Nylon Clear Bowl EPDM 100 Mic                   |
| LP-6F-PNC-V-80  | 3/8 FNPT Nylon Clear Bowl FKM-80 Mesh Filter             |
| LP-8F-NNC-V-40  | 1/2 FNPT Nylon Clear Bowl FKM-40                         |
| LP-8F-PNC-B-20  | 1/2 FNPT Nylon Clear Bowl Buna 20                        |
| LP-8F-PNC-V-20  | 1/2 FNPT Nylon Clear Bowl FKM 20                         |
| LP-6M-NNC-E-40  | 3/8 MNPT Nylon Clear Bowl EPDM-40                        |
| LP-6B-NNC-V-80  | 3/8 Barb Nylon with Clear Bowl FKM-80                    |
| LP-4B-NNC-V-80  | 1/4 Barb Nylon with Clear Bowl FKM-80                    |
| LP-4B-PNC-V-80  | 1/4 Barb Polypropylene Clear Bowl FKM-80                 |
| LP-6B-PNC-E-80  | 3/8 Barb Polypropylene Top Clear Bowl EPDM-80            |
| LP-6B-PNC-V-80  | 3/8 Barb Polypropylene Clear Bowl FKM-80 mesh            |
| LP-8B-PNC-V-80  | 1/2 Barb Polypropylene Clear Bowl FKM-80                 |



# DCV SERIES - BI-DIRECTIONAL DOUBLE CHECK VALVE

#### THIS PRODUCT IS NO LONGER AVAILABLE

The DCV Series is a bi-directional double Check Valve made of Radiation-Stable Polycarbonate with a Silicone disc. It has two available inlet ports connecting to a female luer aspiration and male luer discharge port, and is USP Class IV certified. It has a low cracking pressure of 2-5 psi and a high flow rate.

| SKU     | Description   |
|---------|---|
| DCV-114 | Tubing Pocket Chimney Port PCS Double Check Valve               |
| DCV-115 | Tubing Pocket Chimney Port / Rotating LL PCS Double Check Valve |
| DCV-118 | FL Chimney Port PCS Double Check Valve                          |

#### **CVK SERIES - MALE CHECK VALVES**



The CVK Series are male-by-male Check Valves made of natural PVDF. It has a 316 Stainless Steel spring and ball Viton® O-ring. Other O-ring options are EPDM and Fluorosilicone (blue). These check valves have a 1-2.5 psi cracking pressure with a maximum operating pressure of 220 psi and a maximum working temperature of 180°F. Available with a Hastelloy® spring and PTFE ball. Available Male NPT thread sizes are: 1/8 inch, 1/4 inch, 3/8 inch, and 1/2 inch.

| SKU          | Description                                      |
|--------------|--|
| CVK-2M       | 1/8 inch NPT Check Valve PVDF                    |
| CVK-4M       | 1/4 NPT Check Valve PVDF                         |
| CVK-6M       | 3/8 inch NPT Check Valve PVDF                    |
| CVK-6M-HPTFE | 3/8 inch M Check Valve PVDF, Hastelloy®/PTFE/FKM |
| CVK-8M       | 1/2 inch NPT Check Valve PVDF                    |
| CVK-8M-HPTFE | 1/2 inch M Check Valve PVDF, Hastelloy®/PTFE/FKM |



#### **CMKV SERIES**

The CMKV Series Plastic Check Valves are 1/8 inch Male NPT by Barb sizes of 1/8 inch, 3/16 inch, 1/4 inch, and 3/8 inch. The flow is from thread to barb. Material / Disc combinations are available in PVDF with FKM, Polypropylene with FKM, Polycarbonate with Neoprene, Polycarbonate with Silicone, Nylon with Silicone, and Nylon with Neoprene.

| SKU         | Description                                     |
|-------------|---|
| CMKV-18B    | 1/8 MNPT by 1/8 Barb PVDF/FKM Check Valve       |
| CMKV-14B-NS | 1/8 MNPT by 1/4 Barb Nylon/Silicone Check Valve |
| CMKV-316B   | 1/8 MNPT by 3/16 Barb PVDF/FKM Check Valve      |

## **INDEX**

C

CMKV Series 7 CVK Series - Male Check Valves 6

D

DCV Series - Bi-Directional Double Check Valve 6

L

LP Series 4

M

MCV Series - Check Valves 3

S

SPC Series 1