HIGH-FLOW

NMP SERIES



The NMP Series high-flow Muffler is made of Glass-Filled Nylon with a 40 micron sintered bronze screen. It is available with MNPT threads of 1/8 inch, 1/4 inch, and 3/8 inch. The maximum working pressure is 150 psi and the working temperature range is 35° F to 120° F.

SKU	Description
NMP-2M	1/8 inch MNPT 40 Micron Glass Filled Nylon Speed Muffler

FSPV SERIES - POPPET CHECK VALVES

The FSPV Series Poppet Check Valves come in Black PVDF, Black Polypropylene, and White Polypropylene with a choice of Buna-N, EPDM, Viton® or Kalrez® seal. Standard spring is 302 Stainless Steel with a cracking pressure of 1/3 psi. Optional springs of 1 or 7 psi are available. These high-flow valves can be used in pressures up to 125 psi. Hastelloy spring is optional. The inlet and outlet sizes are Female NPT 1/4 inch, 3/8 inch, 1/2 inch, and 3/4 inch and Male NPT size of 1/2 inch.

Description
1/2 FNPT Poly Poppet Check Valve
1/2 FNPT by 1/2 MNPT Poly Poppet Check Valve
1/2 MNPT by 1/2 MNPT Poly Poppet Check Valve
1/2 MNPT Valve Hastelloy® FKM Poppet Check Valve
1/4 FNPT Poly FKM 302 1 psi Poppet Check Valve
1/4 FNPT White Poly EPDM Seals $1/3$ psi Poppet Check Valve
1/4 FNPT Poly FKM Hastelloy® 1 psi Poppet Check Valve
3/4 FNPT Poly FKM Disk 1/3 psi Poppet Check Valve
3/4 FNPT Poly FKM 11" C 1/3 psi Poppet Check Valve
3/4 FNPT Poly FKM 5" WC Poppet Check Valve

PNEULINE SUPPLY INC.

SKU	Description
FSPV-34F-HV	3/4 FNPT Poly FKM Disk Hastelloy® 1/3 psi Poppet Check Valve
FSPV-34F-HV7	$3/4$ FNPT Poly FKM O-Ring Hastelloy $\!\!^{\otimes}$.7 psi Poppet Check Valve
FSPV-34F-HV-1.5	3/4 FNPT Poly FKM O-Ring Hastelloy® 1.5 psi Poppet Check Valve
FSPV-34F-HV-11WC	3/4 FNPT Poly FKM O-Ring Hastelloy® 11 WC Poppet Check Valve
FSPV-38F	3/8 FNPT Poly FKM 302 1/3 psi Poppet Check Valve
FSPV-38F-E-9	3/8 FNPT Poly FKM 302 1 psi Poppet Check Valve
FSPV-38F-HV-2	3/8 FNPT Poly Hastelloy® FKM #2 O-Ring Poppet Check Valve

PNEULINE SUPPLY INC.

INDEX

F

FSPV Series - Poppet Check Valves 1

Ν

NMP Series 1