HIGH-PRESSURE



Y-S SERIES

The Y-S Series Wye tube fitting has equal single barbs and works well with flexible tubing. The barbs can expand tubing up to 50% above its normal size. This allows higher pressure capabilities. Available materials are White and Black Nylon, Natural Polypropylene, Polycarbonate, and PVDF. Barb sizes are 1/16 inch, 3/32 inch, 1/18 inch, 5/32 inch, 3/16 inch, and 1/4 inch. These Wyes are used primarily in laboratory and medical environments.

| SKU | Description |
|---------------|---|
| Y-S-1B-WN | 1/16 inch White Nylon Single Barbed Wye Connector |
| Y-S-1B-BN | 1/16 inch Black Nylon Single Barbed Wye Connector |
| Y-S-1B-NPP | 1/16 inch Natural Polypropylene Single Barbed Wye Connector |
| Y-S-1B-PC | 1/16 inch Polycarbonate Single Barbed Wye Connector |
| Y-S-1B-PVDF | 1/16 inch PVDF Single Barbed Wye Connector |
| Y-S-332B-WN | 3/32 inch White Nylon Single Barbed Wye Connector |
| Y-S-332B-BN | 3/32 inch Black Nylon Single Barbed Wye Connector |
| Y-S-332B-NPP | 3/32 inch Natural Polypropylene Single Barbed Wye Connector |
| Y-S-332B-PC | 3/32 inch Polycarbonate Single Barbed Wye Connector |
| Y-S-332B-PVDF | 3/32 inch PVDF Single Barbed Wye Connector |
| Y-S-2B-WN | 1/8 inch White Nylon Single Barbed Wye Connector |
| Y-S-2B-BN | 1/8 inch Black Nylon Single Barbed Wye Connector |
| Y-S-2B-NPP | 1/8 inch Natural Polypropylene Single Barbed Wye Connector |
| Y-S-2B-PC | 1/8 inch Polycarbonate Single Barbed Wye Connector |
| Y-S-2B-PVDF | 1/8 inch PVDF Single Barbed Wye Connector |
| Y-S-532-WN | 5/32 inch White Nylon Single Barbed Wye Connector |
| Y-S-532-BN | 5/32 inch Black Nylon Single Barbed Wye Connector |
| Y-S-532-NPP | 5/32 inch Natural Polypropylene Single Barbed Wye Connector |
| Y-S-532-PC | 5/32 inch Polycarbonate Single Barbed Wye Connector |
| Y-S-532-PVDF | 5/32 inch PVDF Single Barbed Wye Connector |
| Y-S-3B-WN | 3/16 inch White Nylon Single Barbed Wye Connector |
| Y-S-3B-BN | 3/16 inch Black Nylon Single Barbed Wye Connector |
| Y-S-3B-NPP | 3/16 inch Natural Polypropylene Single Barbed Wye Connector |
| Y-S-3B-PC | 3/16 inch Polycarbonate Single Barbed Wye Connector |
| Y-S-3B-PVDF | 3/16 inch PVDF Single Barbed Wye Connector |
| Y-S-4B-WN | 1/4 inch White Nylon Single Barbed Wye Connector |
| Y-S-4-BN | 1/4 inch Black Nylon Single Barbed Wye Connector |

PNEULINE SUPPLY INC.

| SKU | Description |
|-------------|--|
| Y-S-4-NPP | 1/4 inch Natural Polypropylene Single Barbed Wye Connector |
| Y-S-4B-PC | 1/4 inch Polycarbonate Single Barbed Wye Connector |
| Y-S-4B-PVDF | 1/4 inch PVDF Single Barbed Wye Connector |



DTF-S SERIES

The DTF-S Series is a three-port F style fitting usually used with flexible tubing. It can expand tubing by 50% of its normal ID. This permits high-pressure capabilities. This fitting is available in White Nylon and Natural Polypropylene. All three ports are equal. Available barb sizes are: 1/16 inch, 3/32 inch, and 1/8 inch.

| | SKU | Description |
|---|---------------|---|
| | DTF-S-1B-NPP | 1/16 inch Natural Polypropylene F-Style Single Barbed Double Tube Tee Connector |
| | DTF-S-1B-WN | 1/16 inch White Nylon F-Style Single Barbed Double Tube Tee Connector |
| | DTF-S-2B-NPP | 1/8 inch Natural Polypropylene F-Style Single Barbed Double Tube Tee Connector |
| | DTF-S-2B-WN | 1/8 inch White Nylon F-Style Single Barbed Double Tube Tee Connector |
| | DTF-S-332B-WN | 3/32 inch White Nylon F-Style Single Barbed Double Tube Tee Connector |
| D | DTF-S-332-P | 3/32 inch Natural Polypropylene F-Style Single Barbed Double Tube Tee |
| | | Connector |

PNEULINE SUPPLY INC.

INDEX

D

DTF-S Series 2



Y-S Series 1