

MALE UNF

USTM SERIES



The USTM Series is a male UNF thread by single barb Adapter. The available Male UNF thread size is 5/16-24 inch, and the available barb sizes are 3/32 inch, 1/8 inch, 5/32 inch, and 3/16 inch. These adapters are made of Acetal. It is sterilizable with Gamma Radiation, EtO and Autoclave.

SKU	Description
USTM-332AC	5/16-24 inch Male UNF by 3/32 inch Acetal Single Barbed Adapter
USTM-2AC	5/16-24 inch Male UNF by 1/8 inch Acetal Single Barbed Adapter
USTM-532AC	5/16-24 inch Male UNF by 5/32 inch Acetal Single Barbed Adapter
USTM-3AC	5/16-24 inch Male UNF by 3/16 inch Acetal Single Barbed Adapter

MCC SERIES



The MCC Series is a Chrome-Plated Brass Ferrules Compression fitting. The pressure range is vacuum to 100 psi and the working temperature range is -40°F to 180°F. Tubing options for use with this fitting are Polyethylene, Polyurethane, and PVC. Sizes available for pipe thread are: 10-32 inch male UNF, 1/8 inch MNPT and 1/4 inch MNPT. Available tubing sizes are: 1/8 inch, 1/4 inch, and 3/8 inch.

SKU	Description
MCC-1018	10-32 inch Male UNF with 5/64 inch ID by 1/8 inch OD Chrome-Plated Brass Compression Fitting
MCC-1014	10-32 inch Male UNF with .170 inch ID by 1/4 inch OD Chrome-Plated Brass Compression Fitting
MCC-2M18	1/8 inch MNPT with 5/64 inch ID by 1/8 inch OD Chrome-Plated Brass Compression Fitting
MCC-2M14	1/8 inch MNPT with .170 inch ID by 1/4 inch OD Chrome-Plated Brass Compression Fitting
MCC-2M38	1/8 inch MNPT with 1/4 inch ID by 3/8 inch OD Chrome-Plated Brass Compression Fitting
MCC-4M14	1/4 inch MNPT with .170 inch ID by 1/4 inch OD Chrome-Plated Brass Compression Fitting

SKU	Description
MCC-4M38	1/4 inch MNPT with 1/4 inch ID by 3/8 inch OD Chrome-Plated Brass Compression Fitting

ALS-IG SWIVEL ADAPTER ELBOW



The ALS-IG Series Swivel Adapter Elbow allows tubing to be rotated 360° into position without crimping. These Swivel Elbows are made of Black Nylon. The male threads are 10-32 inch UNF or 1/8 inch and 1/4 inch male NPT. The barb sizes are 1/16 inch, 3/32 inch, and 1/8 inch. The 10-32 inch UNF threads are self-sealing, and the 1/8 inch and 1/4 inch threads seal with a Buna-N, EPDM, or Viton® O-Ring. The working pressure is 125 psi and the working temperature range is -50° F to 180° F.

SKU	Description
ALS-IG-10X1B	10-32 inch Male UNF by 1/16 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-10X332B	10-32 inch Male UNF by 3/32 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-10X2B	10-32 inch Male UNF by 1/8 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-2MX1B	1/8 inch MNPT by 1/16 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-2MX332B	1/8 inch MNPT by 3/32 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-2MX2B	1/8 inch MNPT by 1/8 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-4MX1B	1/4 inch MNPT by 1/16 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-4MX332B	1/4 inch MNPT by 3/32 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-4MX2B	1/4 inch MNPT by 1/8 inch Black Nylon Single Barbed Elbow Swivel

INDEX

A

ALS-IG SWIVEL ADAPTER ELBOW 2

M

MCC Series 1

U

USTM Series 1