PNEULINE SUPPLY INC.

MOMENTARY



MV - MINIATURE BRASS NICKEL-PLATED PANEL MOUNT TOGGLE

MV Series miniature Panel Mount Nickel-plated Brass Toggle Valves are Two-way normally closed or normally open, Exhausting or Non-Exhausting. Standard is 10-32 Female UNF outlet with 10-32 Female UNF inlet, 1/8 inch Male NPT, or 1/8 inch Female NPT inlet at the base. Seals are Buna, EPDM or optional FKM. 1/8 inch ported and 1/16 inch barbed Air Pilot Valves with 35 psi activation are also available. Valves can be equipped with an actuator of either: Toggle Momentary, or Toggle Detent, a Push Button, Ball, Roller, or Long Cam.

SKU	Description
MV-TD-1010-C-E	10-32 F, In/Out Normally Closed Exhausting Detent Toggle Valve
MV-TM-1010-O-NE	10-32 In/Out Normally Open Non-Exhausting Momentary Toggle Valve
MV-PB-2M10-O-NE	1/8 inch Male NPT Inlet 10-32 Female UNF Outlet, Push Button, Open, Non-
	Exhausting

Request a Quote Today!

PNEULINE SUPPLY INC.

INDEX

Μ

MV - Miniature Brass Nickel-Plated Panel Mount Toggle 1