

PLASTIC SWIVEL

AM-U SERIES



The AM-U Series is a 1/4-28 inch UNF bottom sealing Swivel fitting. It is available with Polypropylene or PVDF interiors with a Nylon encasement. The Nylon comes in five colors: white, black, red, blue, or green. There are three barb sizes: 1/16 inch, 3/32 inch, and 1/8 inch.

SKU	Description
AM-U-14S1B-NP	1/4-28 inch UNF by 1/16 inch Nylon over Polypropylene Single Barbed Swivel
AM-U-14S1B-PVDF	1/4-28 inch UNF by 1/16 inch Nylon over PVDF Single Barbed Swivel
AM-U-14S1B-WN	1/4-28 inch UNF by 1/16 inch White Nylon Single Barbed Swivel
AM-U-14S1B-BN	1/4-28 inch UNF by 1/16 inch Black Nylon Single Barbed Swivel
AM-U-14S1B-RD	1/4-28 inch UNF by 1/16 inch Red Nylon Single Barbed Swivel
AM-U-14S1B-BL	1/4-28 inch UNF by 1/16 inch Blue Nylon Single Barbed Swivel
AM-U-14S1B-GN	1/4-28 inch UNF by 1/16 inch Green Nylon Single Barbed Swivel
AM-U-14S2B-NP	1/4-28 inch UNF by 1/8 inch Nylon over Polypropylene Single Barbed Swivel
AM-U-14S2B-PVDF	1/4-28 inch UNF by 1/8 inch Nylon over PVDF Single Barbed Swivel
AM-U-14S2B-WN	1/4-28 inch UNF by 1/8 inch White Nylon Single Barbed Swivel
AM-U-14S2B-BN	1/4-28 inch UNF by 1/8 inch Black Nylon Single Barbed Swivel
AM-U-14S2B-RD	1/4-28 inch UNF by 1/8 inch Red Nylon Single Barbed Swivel
AM-U-14S2B-BL	1/4-28 inch UNF by 1/8 inch Blue Nylon Single Barbed Swivel
AM-U-14S2B-GN	1/4-28 inch UNF by 1/8 inch Green Nylon Single Barbed Swivel
AM-U-14S332B-NPP	1/4-28 inch UNF by 3/32 inch Natural Polypropylene Single Barbed Swivel
AM-U-14S332B-WNP	1/4-28 inch UNF by 3/32 inch Nylon over Polypropylene Single Barbed Swivel
AM-U-14S332B-BN	1/4-28 inch UNF by 3/32 inch Black Nylon Single Barbed Swivel
AM-U-14S332B-PVDF	1/4-28 inch UNF by 3/32 inch Nylon over PVDF Single Barbed Swivel
AM-U-14S332B-RD	1/4-28 inch UNF by 3/32 inch Red Nylon Single Barbed Swivel
AM-U-14S332B-BL	1/4-28 inch UNF by 3/32 inch Blue Nylon Single Barbed Swivel
AM-U-14S332BGN	1/4-28 inch UNF by 3/32 inch Green Nylon Single Barbed Swivel

ALS-IG SWIVEL ADAPTER ELBOW



The ALS-IG Series Swivel Adapter Elbow allows tubing to be rotated 360° into position without crimping. These Swivel Elbows are made of Black Nylon. The male threads are 10-32 inch UNF or 1/8 inch and 1/4 inch male NPT. The barb sizes are 1/16 inch, 3/32 inch, and 1/8 inch. The 10-32 inch UNF threads are self-sealing, and the 1/8 inch and 1/4 inch threads seal with a Buna-N, EPDM, or Viton® O-Ring. The working pressure is 125 psi and the working temperature range is -50° F to 180° F.

SKU	Description
ALS-IG-10X1B	10-32 inch Male UNF by 1/16 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-10X332B	10-32 inch Male UNF by 3/32 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-10X2B	10-32 inch Male UNF by 1/8 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-2MX1B	1/8 inch MNPT by 1/16 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-2MX332B	1/8 inch MNPT by 3/32 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-2MX2B	1/8 inch MNPT by 1/8 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-4MX1B	1/4 inch MNPT by 1/16 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-4MX332B	1/4 inch MNPT by 3/32 inch Black Nylon Single Barbed Elbow Swivel
ALS-IG-4MX2B	1/4 inch MNPT by 1/8 inch Black Nylon Single Barbed Elbow Swivel

INDEX

A

ALS-IG SWIVEL ADAPTER ELBOW 2
AM-U Series 1