

POLYPROPYLENE

PJV SERIES



The PJV Series Micro Ball Valves are of Polypropylene and reinforced fiberglass with a 90 degree rotating handle and FKM O-rings. Standard pressure is 150 psi with maximum temperature of 150° with a a maximum pressure of 300 psi at 70° F.

| SKU      | Description  |
|----------|--|
| PJV-38B  | 3/8 inch Barbed Glass-Filled Polypropylene Micro Ball Valve with FKM Seals |
| PJV-38F  | 3/8 inch Female Glass-Filled Polypropylene Micro Ball Valve with FKM Seals |
| PJV-4F4M | 1/4 inch Female by 1/4 inch Male   |
| PJV-4B   | 1/4 inch Barbed Polypropylene Micro Ball Valve                             |
| PJV-6F6M | 3/8 inch Female by 3/8 inch Male Polypropylene Micro Ball Valve            |
| PJV-6B   | 3/8 inch Barbed Polypropylene Micro Ball Valve                             |
| PJV-8F8M | 1/2 inch Female by 1/2 inch Male Polypropylene Micro Ball Valve            |
| PJV-8B   | 1/2 inch Barbed Polypropylene Micro Ball Valve                             |
| PJV-12B  | 1/2 inch Barbed Polypropylene Micro Ball Valve                             |

INDEX

P

PJV Series 1