

STRAIGHT



SSBM SERIES

The SSBM Series Multi-Barbed Hose Splicer Fitting is made of 303 Stainless Steel and is available in straight barb sizes of 1/4 inch and 3/8 inch. The available reducing barb size is 3/8 inch by 1/4 inch.

SKU	Description
SSBM-4B4B	1/4 Barb by 1/4 Barb Stainless Steel Splicer
SSBM-6B6B	3/8 Barb by 3/8 Barb Stainless Steel Splicer
SSBM-6B4B	3/8 Barb by 1/4 Barb Stainless Steel Splicer Reducer



SFWS SERIES

The SFWS Series is a female Brass multi-barb Swivel adapter with a gasket. It has female NPT threads to a hose barb attachment. The swivel has a full 360° rotation. The temperature range for this swivel is -40° F to 160° F at 150 psi.

This swivel is not recommended for water because of the fiber gasket. Air only.

SKU	Description
SFWS-2F4B	1/8 FNPT by 1/4 Barb Brass Swivel
SFWS-4F4B	1/4 FNPT by 1/4 Barb Brass Swivel
SFWS-4F5B	1/4 FNPT by 5/16 Barb Brass Swivel
SFWS-4F6B	1/4 FNPT by 3/8 Barb Brass Swivel
SFWS-6F4B	3/8 FNPT by 1/4 Barb Brass Swivel
SFWS-6F6B	3/8 FNPT by 3/8 Barb Brass Swivel
SFWS-6F8B	3/8 FNPT by 1/2 Barb Brass Swivel
SFWS-8F6B	1/2 FNPT by 3/8 Barb Brass Swivel
SFWS-8F8B	1/2 FNPT by 1/2 Barb Brass Swivel
SFWS-12F8B	3/4 FNPT by 1/2 Barb Brass Swivel

SKU	Description
SFWS-12F10B	3/4 FNPT by 5/8 Barb Brass Swivel



PY SERIES

Push-to-Connect Straight Divider Wye connectors available in Acetal, Polypropylene, and Kynar® used to split or reduce a tubing connections of Polyethylene, Brass, or Copper. Sizes range from 1/4 inch OD to 3/8 inch OD including reducing sizes. Available in 1 inlet to 2 onlets, or 1 inlet to 3 outlets. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

SKU	Description
PY-4	1/4 Equal In/Out Push-to-Connect Wye
PY-5	5/16 Equal In/Out Push-to-Connect Wye
PY-6-5	3/8 to Dual 5/16 In/Out Push-to-Connect Wye
PY-6	3/8 Equal In/Out Push-to-Connect Wye
PY-8	1/2 Equal In/Out Push-to-Connect Wye



PM THREAD TO PUSH-TO-CONNECT STRAIGHT CONNECTOR

PM Series Straight Male Thread to Push-to-Connect connectors available in Acetal and select sizes in Polypropylene, and Kynar®. Push-in izes range from 5/32 inch to 5/8 inch and Threads ranging from 3/4 inch MNPT to 1/8 inch MNPT. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

SKU	Description
PM-12M10	3/4 MNPT by 5/8 OD Straight Push-to-Connect
PM-2M3	1/8 MNPT by 3/16 OD Straight Push-to-Connect
PM-2M4	1/8 MNPT by 1/4 OD Straight Push-to-Connect
PM-2M532	1/8 MNPT by 5/32 OD Straight Push-to-Connect
PM-2M5	1/8 MNPT by 5/16 OD Straight Push-to-Connect
PM-2M6	1/8 MNPT by 3/8 OD Straight Push-to-Connect
PM-4BSPT6	1/4 BSPT by 3/8 OD Straight Push-to-Connect
PM-4M4	1/4 MNPT by 1/4 OD Straight Push-to-Connect

SKU	Description
PM-4M532	1/4 MNPT by 5/32 OD Straight Push-to-Connect
PM-4M5	1/4 MNPT by 5/16 OD Straight Push-to-Connect
PM-4M6	1/4 MNPT by 3/8 OD Straight Push-to-Connect
PM-6M4	3/8 MNPT by 1/4 OD Straight Push-to-Connect
PM-6M5	3/8 MNPT by 5/16 OD Straight Push-to-Connect
PM-6M6	3/8 MNPT by 3/8 OD Straight Push-to-Connect
PM-6M8	3/8 MNPT by 1/2 OD Straight Push-to-Connect
PM-8M6	1/2 MNPT by 3/8 OD Straight Push-to-Connect
PM-8M8	1/2 MNPT by 1/2 OD Straight Push-to-Connect



PF SERIES

Push-to-Connect to Female NPT Straight connectors available in Acetal, Polypropylene, and Kynar® used to join tubing of Polyethylene, Brass, or Copper. Push-to-Connect sizes range from 1/2 inch to 1/4 inch and Thread sizes ranging from 1/2 FNPT to 1/8 FNPT. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

SKU	Description
PF-2F4	1/8 FNPT by 1/4 OD Straight Push-to-Connect
PF-4F4	1/4 FNPT by 1/4 OD Straight Push-to-Connect
PF-4F5	1/4 FNPT by 5/16 OD Straight Push-to-Connect
PF-4F6	1/4 FNPT by 3/8 OD Straight Push-to-Connect
PF-6F5	3/8 FNPT by 5/16 OD Straight Push-to-Connect
PF-6F6	3/8 FNPT by 3/8 OD Straight Push-to-Connect
PF-6F8	3/8 FNPT by 1/2 OD Straight Push-to-Connect



PC SERIES

Push-to-Connect Straight Fittings connectors available in Acetal, Polypropylene, and Kynar® used to join tubing of Polyethylene, Brass, or Copper. Sizes range from 5/32 inch OD to 1/2 inch OD including reducing sizes. Gray or White Acetal are NSF and FDA approved and have Buna seals for use in air, gases, and potable water applications. White Polypropylene with EPDM seals or PVDF with FKM seals. Maximum temperature 140°F at 60 psi for Polypropylene.

SKU	Description
PC-3	3/16 OD Equal Connector
PC-4	1/4 OD Equal Connector
PC-5	5/16 OD Equal Connector
PC-532	5/32 OD Equal Connector
PC-6	3/8 OD Equal Connector
PC-8	1/2 OD Equal Connector
PC-4-3	1/4 OD by 3/16 OD Reducer Connector
PC-5-532	5/16 OD by 5/32 OD Reducer Connector
PC-5-3	5/16 OD by 3/16 OD Reducer Connector
PC-5-4	5/16 OD by 1/4 OD Reducer Connector
PC-6-3	3/8 OD by 3/16 OD Reducer Connector
PC-6-4	3/8 OD by 1/4 OD Reducer Connector
PC-6-5	3/8 OD by 5/16 OD Reducer Connector
PC-8-5	1/2 OD by 5/16 OD Reducer Connector

MBF PANEL MOUNT BULKHEAD WITH FLANGE



These are bulkheads with panel mountings of 5/16-24 UNF threads, 1/8" and 1/4" NPS threads and a mounting flange. The first barb size is outside the panel, the second on the inside. Available in Black Nylon, Natural Nylon, Polypropylene and PVDF. Barb sizes are 1/16", 3/32", 1/8", 5/32", 3/16" and 1/4". (order as BN, NN, PP, PVDF)

SKU	Description
MBF2-1B3B	1/8 NPS-1/16 by 3/16 Bulkhead
MBF2-1B4B	1/8 NPS-1/16 by 1/4 Bulkhead
MBF2-2B3B	1/8 NPS-1/8 by 3/16 Bulkhead
MBF2-2B4B	1/8 NPS-1/8 by 1/4 Bulkhead
MBF2-3323B	1/8 NPS-3/32 by 3/16 Bulkhead
MBF2-3B	1/8 NPS-3/16 by 3/16 Bulkhead

SKU	Description
MBF2-3B4B	1/8 NPS-3/16 by 1/4 Bulkhead
MBF2-4B	1/8 NPS-1/4 by 1/4 Bulkhead
MBF2-532B3B	1/8 NPS-5/32 by 3/16 Bulkhead
MBF2-532B4B	1/8 NPS-5/32 by 1/4 Bulkhead
MBF4-1B3B	1/4 NPS-1/16 by 3/16 Bulkhead
MBF4-1B4B	1/4 NPS-1/16 by 1/4 Bulkhead
MBF4-2B3B	1/4 NPS-1/8 by 3/16 Bulkhead
MBF4-2B4B	1/4 NPS-1/8 by 1/4 Bulkhead
MBF4-332B3B	1/4 NPS-3/32 by 3/16 Bulkhead
MBF4-332B4B	1/4 NPS-3/32 by 1/4 Bulkhead
MBF4-3B4B	1/4 NPS-3/16 by 1/4 Bulkhead
MBF4-3B	1/4 NPS-3/16 by 3/16 Bulkhead
MBF4-4B4B	1/4 NPS-1/4 by 1/4 Bulkhead
MBF4-4B516B	1/4 NPS-1/4 by 5/16 Bulkhead
MBF4-4B6B	1/4 NPS-1/4 by 3/8 Bulkhead
MBF4-516B6B	1/4 NPS-5/16 by 3/8 Bulkhead
MBF4-532B3B	1/4 NPS-5/32 by 3/16 Bulkhead
MBF4-532B4B	1/4 NPS-5/32 by 1/4 Bulkhead
MBF4-5B5B	1/4 NPS-5/16 by 5/16 Bulkhead
MBF4-6B6B	1/4 NPS-3/8 by 3/8 Bulkhead
MBF516-1B332B	5/16-24 UNF 1/16 by 3/32 Bulkhead
MBF516-1B3B	5/16-24 UNF 1/16 by 3/16 Bulkhead
MBF516-2B3B	5/16-24 UNF 1/8 by 3/16 Bulkhead
MBF516-2B532B	5/16-24 UNF 1/8 by 3/32 Bulkhead
MBF516-332B3B	5/16-24 UNF 3/32 by 3/16 Bulkhead
MBF516-332B532B	5/16-24 UNF 3/32 by 5/32 Bulkhead
MBF516-3B	5/16-24 UNF 3/16 by 3/16 Bulkhead
MBF516-532	5/16-24 UNF 5/32 by 5/32 Bulkhead



FBH BRASS BULKHEADS

The FBH Series Straight and Elbow Bulkheads are made of Brass, Nickel-Plated Brass, or Zinc-Plated Steel sizes ranging 1/8 inch to 3/8 inch Female to UNF, Male to Female, and Female to Female.

SKU	Description
FBH-12F	1/2 inch Female 1-1/8, 14 UNS Bulkhead
FBH-12F12M	1/2 inch Female by 1/2 inch Male Bulkhead
FBH-12M	1/2 inch Male by 1/2 inch Male Bulkhead
FBH-12M14F	1/2 inch Male 1/4 inch Female Bulkhead
FBH-12M38F	1/2 inch Male 3/8 inch Female Bulkhead
FBH-14F	1/4 inch Female 3/4-16 UNF Bulkhead
FBH-14X	1/4 inch Female 3/4-16 UNF 1 1/2 inch length Bulkhead
FBH-18F	1/8 Female 5/8-18 UNF Bulkhead
FBH-38F	3/8 inch Female 1/14 UNF Bulkhead
FBH-38F12M	3/8 inch Female by 1/2 inch Male Bulkhead
FBH-38F-E	3/8 inch Female by 3/8 inch Female Elbow Bulkhead



CA STRAIGHT THREADED COMPRESSION FITTINGS

The CA Series Male Straight Pipe Compression Fittings allow tubing to be connected to Pipes, Valves, and Manifolds for attaching Tube lines. Available for 1/8 inch to 7/8 inch tubing and Male NPT 1/8 inch to 3/4 inch tube connection without kinking attached tubing. Available in FDA and NSF approved Acetal (POM) for use with hot water applications, FDA and NSF approved Nylon, and UV resistant FDA and NSF rated PVDF. Provided with Poly gripper (except for 1/8 inch units) for up to 220 psi.

SKU	Descriptions
CA-1212-AC-PG	1/2 inch MNPT by 1/2 inch OD Acetal Compression Fitting with Poly Gripper
CA-1212-K-PG	1/2 inch MNPT by 1/2 inch OD PVDF Compression Fitting with Poly Gripper
CA-1212-NN-PG	1/2 inch MNPT by 1/2 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-1212-PG	1/2 inch MNPT by 1/2 inch OD Polypropylene Compression Fitting with Poly Gripper
CA-1234-AC-PG	1/2 inch MNPT by 3/4 inch OD Acetal Compression Fitting with Poly Gripper
CA-1234-NN-PG	1/2 inch MNPT by 3/4 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-1234-PG	1/2 inch MNPT by 3/4 inch OD Polypropylene Compression Fitting with Poly Gripper

PNEULINE SUPPLY INC.

SKU	Descriptions
CA-1234-PVDF-PG	1/2 inch MNPT by 3/4 inch OD PVDF Compression Fitting with Poly Gripper
CA-1238-AC-PG	1/2 inch MNPT by 3/8 inch OD Acetal Compression Fitting with Poly Gripper
CA-1238-K-PG	1/2 inch MNPT by 3/8 inch OD PVDF Compression Fitting with Poly Gripper
CA-1238-NN-PG	1/2 inch MNPT by 3/8 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-1238-PG	1/2 inch MNPT by 3/8 inch OD Polypropylene Compression Fitting with Poly Gripper
CA-12516-AC-PG	1/2 inch MNPT by 5/16 inch OD Acetal Compression Fitting with Poly Gripper 2 piece unit
CA-12516-NN-PG	1/2 inch MNPT by 5/16 inch OD Natural Nylon Compression Fitting with Poly Gripper 2 piece unit
CA-12516-PVDF-PG	1/2 inch MNPT by 5/16 inch OD PVDF Compression Fitting with Poly Gripper 2 piece unit
CA-1258-AC-PG	1/2 inch MNPT by 5/8 inch OD Acetal Compression Fitting with Poly Gripper
CA-1258-NN-PG	1/2 inch MNPT by 5/8 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-1258-PG	1/2 inch MNPT by 5/8 inch OD Polypropylene Compression Fitting with Poly Gripper
CA-1258-PVDF-PG	1/2 inch MNPT by 5/8 inch OD PVDF Compression Fitting with Poly Gripper
CA-1412-AC-PG	1/4 inch MNPT by 1/2 inch OD Acetal Compression Fitting with Poly Gripper
CA-1412-K-PG	1/4 inch MNPT by 1/2 inch OD PVDF Compression Fitting with Poly Gripper
CA-1412-NN-PG	1/4 inch MNPT by 1/2 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-1412-PG	1/4 inch MNPT by 1/2 inch OD Polypropylene Compression Fitting with Poly Gripper
CA-1414	1/4 inch MNPT by 1/4 inch OD Polypropylene Compression Fitting with O-Ring
CA-1414-AC-PG	1/4 inch MNPT by 1/4 inch OD Acetal Compression Fitting with Poly Gripper
CA-1414-K-PG	1/4 inch MNPT by 1/4 inch OD PVDF Compression Fitting with Poly Gripper
CA-1414-NN-PG	1/4 inch MNPT by 1/4 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-1438-AC-PG	1/4 inch MNPT by 3/8 inch OD Acetal Compression Fitting with Poly Gripper
CA-1438-K-PG	1/4 inch MNPT by 3/8 inch OD PVDF Compression Fitting with Poly Gripper
CA-1438-NN-PG	1/4 inch MNPT by 3/8 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-14516	1/4 inch MNPT by 5/16 inch OD Polypropylene Compression Fitting with O-Ring
CA-14516-AC-PG	1/4 inch MNPT by 5/16 inch OD Acetal Compression Fitting with Poly Gripper
CA-14516-PP-PG	1/4 inch MNPT by 5/16 inch OD Polypropylene Compression Fitting with Poly Gripper
CA-14516-K-PG	1/4 inch MNPT by 5/16 inch OD PVDF Compression Fitting with Poly Gripper
CA-14516-NN-PG	1/4 inch MNPT by 5/16 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-1812-AC-PG	1/8 inch MNPT by 1/2 inch OD Acetal Compression Fitting with Poly Gripper

SKU	Descriptions
CA-1812-NN-PG	1/8 inch MNPT by 1/2 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-1812-PVDF-PG	1/8 inch MNPT by 1/2 inch OD PVDF Compression Fitting with Poly Gripper
CA-1814-PP	1/8 inch MNPT by 1/4 inch OD Polypropylene Compression Fitting with O-Ring
CA-1814-K	1/8 inch MNPT by 1/4 inch OD PVDF Compression Fitting with O-Ring
CA-1814-K-PG	1/8 inch MNPT by 1/4 inch OD PVDF Compression Fitting with Poly Gripper
CA-1818-PP	1/8 inch MNPT by 1/8 inch OD Polypropylene Compression Fitting with O-Ring
CA-1818-AC-PG	1/8 inch MNPT by 1/8 inch OD Acetal Compression Fitting with Poly Gripper
CA-1818-K	1/8 inch MNPT by 1/8 inch OD PVDF Compression Fitting with O-Ring
CA-1818-NN-PG	1/8 inch MNPT by 1/8 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-1838-AC-PG	1/8 inch MNPT by 3/8 inch OD Acetal Compression Fitting with Poly Gripper
CA-1838-K-PG	1/8 inch MNPT by 3/8 inch OD PVDF Compression Fitting with Poly Gripper
CA-1838-NN-PG	1/8 inch MNPT by 3/8 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-3434-AC-PG	3/4 inch MNPT by 3/4 inch OD Acetal Compression Fitting with Poly Gripper
CA-3434-NN-PG	3/4 inch MNPT by 3/4 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-3434-PVDF-PG	3/4 inch MNPT by 3/4 inch OD PVDF Compression Fitting with Poly Gripper
CA-3478-AC-PG	3/4 inch MNPT by 7/8 inch OD Acetal Compression Fitting with Poly Gripper
CA-3478-NN-PG	3/4 inch MNPT by 7/8 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-3478-PVDF-PG	3/4 inch MNPT by 7/8 inch OD PVDF Compression Fitting with Poly Gripper
CA-3812-AC-PG	3/8 inch MNPT by 1/2 inch OD Acetal Compression Fitting with Poly Gripper
CA-3812-K-PG	3/8 inch MNPT by 1/2 inch OD PVDF Compression Fitting with Poly Gripper
CA-3812-NN-PG	3/8 inch MNPT by 1/2 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-3814-AC-PG	3/8 inch MNPT by 1/4 inch OD Acetal Compression Fitting with Poly Gripper
CA-3814-K-PG	3/8 inch MNPT by 1/4 inch OD PVDF Compression Fitting with Poly Gripper
CA-3814-NN-PG	3/8 inch MNPT by 1/4 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-3814-PP-PG	3/8 inch MNPT by 1/4 inch OD Polypropylene Compression Fitting with Gripper
CA-3838-AC-PG	3/8 inch MNPT by 3/8 inch OD Acetal Compression Fitting with Poly Gripper
CA-3838-K-PG	3/8 inch MNPT by 3/8 inch OD PVDF Compression Fitting with Poly Gripper
CA-3838-NN-PG	3/8 inch MNPT by 3/8 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-3838-PP-PG	3/8 inch MNPT by 3/8 inch OD Polypropylene Compression Fitting with Poly Gripper
CA-38516-AC-PG	3/8 inch MNPT by 5/16 inch OD Acetal Compression Fitting with Poly Gripper
CA-38516-K-PG	3/8 inch MNPT by 5/16 inch OD PVDF Compression Fitting with Poly Gripper

SKU	Descriptions
CA-38516-NN-PG	3/8 inch MNPT by 5/16 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-3858-AC-PG	3/8 inch MNPT by 5/8 inch OD Acetal Compression Fitting with Poly Gripper
CA-3858-NN-PG	3/8 inch MNPT by 5/8 inch OD Natural Nylon Compression Fitting with Poly Gripper
CA-3858-PP-PG	3/8 inch MNPT by 5/8 inch OD Polypropylene Compression Fitting with Poly Gripper
CA-3858-PVDF-PG	3/8 inch MNPT by 5/8 inch OD PVDF Compression Fitting with Poly Gripper

BB SERIES



Brass Bulkheads with Bite-Style Barbs. 10-32 mounting Threads for 1/16 inch, .078, and 3/32 inch. 1/4-28 mounting Thread with 1/16 inch thru hole to 5/32 inch Barb. 5/16-24 mounting Thread with 1/16 inch thru hole to 3/16 inch Barb. 3/8-24 mounting Thread with 1/16 inch thru hole to 3/8 inch Barb. Mixed sizes are available for Straight and Elbow models.

SKU	Description
BB-10-170B078B	10-32 by .170 by .078 Barb Brass Reducing Bulkhead
BB-10-170B332B	10-32 by .170 by 3/32 Barb Brass Reducing Bulkhead
BB-10-1B	10-32 by 1/16 Barb Brass Bulkhead
BB-10-2B1B	10-32 by 1/8 by 1/16 Barb Brass Reducing Bulkhead
BB-10-332B	10-32 by 3/32 Barb Brass Bulkhead
BB-10-332B1B	10-32 by 3/32 by 1/16 Barb Brass Reducing Bulkhead
BB-10-332B1B-NP	10-32 by 3/32 by 1/16 Barb Nickel Plated Bulkhead
BB-14-2B	1/4-28 by 1/8 Barb Brass Bulkhead
BB-14-6B1B	1/4-28 by 3/8 by 1/16 Barb Brass Reducing Bulkhead
BB-14-O-2B	1/4-28 by 1/8 Barb Brass Reducing Bulkhead O-ring
BB-1M-5B332B	1/16 NPT 5/16 by 3/32 Barb Brass Reducing Bulkhead
BB-2M-5B332B	1/8 NPT 5/16 by 3/32 Barb Brass Reducing Bulkhead
BB-2M-6B4B	1/8 NPT 3/8 by 1/4 Barb Brass Reducing Bulkhead
BB-38-3B-SS	3/8-24 3/16 Barb 303 Stainless Bulkhead
BB-38-4B	3/8-24 1/4 Barb Brass Bulkhead
BB-38-4B-170B	3/8-24 by 1/4 by .170 Barb Brass Reducing Bulkhead
BB-38-4B-170B-SS	3/8-24 by 1/4 by .170 Barb Stainless Steel Bulkhead
BB-38-4B-3B	3/8-24 by 1/4 by 3/16 Barb Brass Reducing Bulkhead
BB-38-4B-NP	3/8-24 by 1/4 Barb Brass Nickel Plated Bulkhead
BB-38-4B-SS	3/8-24 by 1/4 Barb 303 Stainless Bulkhead
BB-38-6B1B	3/8-24 by 3/8 by 1/16 Barb Brass Reducing Bulkhead
BB-38-6B2DB	3/8-24 by 3/8 by 1/8 Double Barb Brass Reducing Bulkhead

SKU	Description
BB-38-6B2DB-020	3/8-24 by 3/8 by 1/8 Double Barb, 020 Orifice Brass Reducing Bulkhead
BB-38-6B4B	3/8-24 by 3/8 by 1/4 Barb Brass Reducing Bulkhead
BB-516-170532	5/16-24 by .170 by 5/32 Barb Brass Reducing Bulkhead
BB-516-170732	5/16-24 by .170 by .732 Barb Brass Reducing Bulkhead
BB-516-170B	5/16-24 by .170 Barb Bulkhead



A-S & A-S-M SINGLE BARB THREADED ADAPTERS

The A-S Series is a series of single barbed adapters with 10-32 inch and 1/4-28 inch male UNF threads, available either tapered or straight. Combined with this series is the A-S-M Series, which are available in Metric thread sizes of 5m and 6m. Both adapters are available in Black and White Nylon, Natural Polypropylene, and PVDF.

SKU	Description
A-S-10332B-BN	10-32 inch Male UNF by 3/32 inch Black Nylon Single Barbed Adapter
A-S-10332B-WN	10-32 inch Male UNF by 3/32 inch White Nylon Single Barbed Adapter
A-S-10332B-NPP	10-32 inch Male UNF by 3/32 inch Natural Polypropylene Single Barbed Adapter
A-S-10332B-PVDF	10-32 inch Male UNF by 3/32 inch PVDF Single Barbed Adapter
A-S-101B-BN	10-32 inch Male UNF by 1/16 inch Black Nylon Single Barbed Adapter
A-S-101B-WN	10-32 inch Male UNF by 1/16 inch White Nylon Single Barbed Adapter
A-S-101B-NPP	10-32 inch Male UNF by 1/16 inch Natural Polypropylene Single Barbed Adapter
A-S-101B-PVDF	10-32 inch Male UNF by 1/16 inch PVDF Single Barbed Adapter
A-S-10532B-WN	10-32 inch Male UNF by 5/32 inch White Nylon Single Barbed Adapter
A-S-10532B-PP	10-32 inch Male UNF by 5/32 inch Natural Polypropylene Single Barbed Adapter
A-S-10532B-PVDF	10-32 inch Male UNF by 5/32 inch PVDF Single Barbed Adapter
A-S102B-BN	10-32 inch Male UNF by 1/8 inch Black Nylon Single Barbed Adapter
A-S-102B-WN	10-32 inch Male UNF by 1/8 inch White Nylon Single Barbed Adapter
A-S-102B-PP	10-32 inch Male UNF by 1/8 inch Polypropylene Single Barbed Adapter
A-S-102B-PVDF	10-32 inch Male UNF by 1/8 inch PVDF Single Barbed Adapter
A-S-14332B-WN	1/4-28 inch Male UNF by 3/32 inch White Nylon Single Barbed Adapter
A-S-14332B-NPP	1/4-28 inch Male UNF by 3/32 inch Natural Polypropylene Single Barbed Adapter
A-S-14332B-PVDF	1/4-28 inch Male UNF by 3/32 inch PVDF Single Barbed Adapter
A-S-141B-NPP	1/4-28 inch Male UNF by 1/16 inch Natural Polypropylene Single Barbed Adapter
A-S-141B-WN	1/4-28 inch Male UNF by 1/16 inch White Nylon Single Barbed Adapter
A-S-14532B-WN	1/4-28 inch Male UNF by 5/32 inch White Nylon Single Barbed Adapter
A-S-14532B-BK	1/4-28 inch Male UNF by 5/32 inch Black Nylon Single Barbed Adapter

SKU	Description
A-S-14532B-NPP	1/4-28 inch Male UNF by 5/32 inch Natural Polypropylene Single Barbed Adapter
A-S-14532B-PVDF	1/4-28 inch Male UNF by 5/32 inch PVDF Single Barbed Adapter
A-S-142B-WN	1/4-28 inch Male UNF by 1/8 inch White Nylon Single Barbed Adapter
A-S-142B-BN	1/4-28 inch Male UNF by 1/8 inch Black Nylon Single Barbed Adapter
A-S-142B-NPP	1/4-28 inch Male UNF by 1/8 inch Natural Polypropylene Single Barbed Adapter
A-S-142B-PVDF	1/4-28 inch Male UNF by 1/8 inch PVDF Single Barbed Adapter
A-S-143B-WN	1/4-28 inch Male UNF by 3/16 inch White Nylon Single Barbed Adapter
A-S-143B-BN	1/4-28 inch Male UNF by 3/16 inch Black Nylon Single Barbed Adapter
A-S-143B-NPP	1/4-28 inch Male UNF by 3/16 inch Natural Polypropylene Single Barbed Adapter
A-S-143B-PVDF	1/4-28 inch Male UNF by 3/16 inch PVDF Single Barbed Adapter
A-S-M5-1B-WN	5M Metric Thread by 1/16 inch White Nylon Single Barbed Adapter
A-S-M5-1B-BN	5M Metric Thread by 1/16 inch Black Nylon Single Barbed Adapter
A-S-M5-1B-NPP	5M Metric Thread by 1/16 inch Natural Polypropylene Single Barbed Adapter
A-S-M5-332B-WN	5M Metric Thread by 3/32 inch White Nylon Single Barbed Adapter
A-S-M5-332B-BN	5M Metric Thread by 3/32 inch Black Nylon Single Barbed Adapter
A-S-M5-332B-NPP	5M Metric Thread by 3/32 inch Natural Polypropylene Single Barbed Adapter
A-S-M5-532B-WN	5M Metric Thread by 5/32 inch White Nylon Single Barbed Adapter
A-S-M5-532B-NPP	5M Metric Thread by 5/32 inch Natural Polypropylene Single Barbed Adapter
A-S-M6-2B-WN	6M Metric Thread by 1/8 inch White Nylon Single Barbed Adapter
A-S-M6-2B-BN	6M Metric Thread by 1/8 inch Black Nylon Single Barbed Adapter
A-S-M6-2B-NPP	6M Metric Thread by 1/8 inch Natural Polypropylene Single Barbed Adapter
A-S-M6-3B-NPP	6M Metric Thread by 3/16 inch Natural Polypropylene Single Barbed Adapter
A-S-M6-3B-BN	6M Metric Thread by 3/16 inch Black Nylon Single Barbed Adapter
A-S-M6-3B-PVDF	6M Metric Thread by 3/16 inch PVDF Single Barbed Adapter

INDEX

A

A-S & A-S-M SINGLE BARB THREADED ADAPTERS 10

B

BB Series 9

C

CA STRAIGHT THREADED COMPRESSION FITTINGS 6

F

FBH BRASS BULKHEADS 6

M

MBF PANEL MOUNT BULKHEAD WITH FLANGE 4

P

PC Series 4

PF Series 3

PM THREAD TO PUSH-TO-CONNECT STRAIGHT CONNECTOR 2

PY Series 2

S

SFWS Series 1

SSBM Series 1